

1617A Coax - CATV Cable



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

Series 11, 14 AWG solid .064" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® IV quad shield (60% and 40% coverage), PVC jacket

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
Series Type	Series 11
AWG	14
Stranding	Solid
Conductor Diameter	.064 in.
Conductor Material	BCCS - Bare Copper Covered Steel

INSULATION:

Insulation Material	Gas-injected FPE - Foam Polyethylene
Insulation Diameter	.280 in.

OUTER SHIELD:

Outer Shield Material Trade Name	Duobond® IV Quad Shield
Outer Shield Type	Tape/Braid/Tape/Braid

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum-Foil-Polyester Tape-Aluminum Foil	100
2		Braid	AL - Aluminum Braid	60
3	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
4		Braid	AL - Aluminum Braid	40

Outer Shield %Coverage	100 %
------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.407 in.
--------------------------	----------

1617A Coax - CATV Cable

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
Bulk Cable Weight	59 lbs/1000 ft.
Max. Recommended Pulling Tension	308 lbs.
Min. Bend Radius (Install)	4.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CATV, CM
CEC/C(UL) Specification	CM
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

FLAME TEST:

UL Flame Test	UL1685 UL Loading
---------------	-------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 +/- 3 Ohms
Nom. Inductance	0.097 μ H/ft
Nom. Capacitance Conductor to Shield	16.2 pF/ft
Nominal Velocity of Propagation	83 %
Nominal Delay	1.2 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	11.0 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg.C	3 Ohms/1000 ft

Minimum Structural Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Structural Return Loss (dB)
		5	1000	20

Max. Attenuation :

1617A Coax - CATV Cable

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Attenuation (dB/100 ft.)
	5			.38
	55			.97
	211			1.81
	270			2.05
	300			2.15
	350			2.32
	400			2.47
	450			2.65
	550			2.94
	750			3.50
	870			3.84
	1000			4.23

Max. Operating Voltage - UL 300 V RMS

Max. Operating Voltage - Non-UL 300 V RMS

NOTES:

Notes Sweep tested 5 MHz to 1 GHz.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1617A 0101000	#14 GIFHDLDPPE DBL SH PVC	1000	65	BLACK	

Revision Number: 1 Revision Date: 09-07-2006

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.