Battery-Powered Crimp Tool Kits


Completely Portable Power Crimping



SDE Battery Powered Crimp Tool Kit, Dies not included

Part No. 1725837-() 110 V (-1 includes Ram Retract Switch; -3 without) Part No. 1725837-() 220 V

(-2 includes Ram Retract Switch; -4 without) See Customer Manual CM 409-10053



SDE Battery Powered Crimp Tool Kit, Dies not included

Part No. 1213890-() 110V

(-I includes Ram Retract Switch; -3 without)

Part No. 1213890-() 220V

(-2 includes Ram Retract Switch; -4 without) See Customer Manual CM 409-10065



Fast Facts

This fast, ergonomically-designed tool is ideal for use at the bench, on the line, or in the field.

- Completely portable—over 100 crimps per charge, 40 min charging time
- Terminates wires to 10 AWG [6 mm²]
- Lightweight—I.57 kg [3.48 lbs] with battery; compact—360 mm [14 in] length
- Kit includes tool, 2 batteries, charger
- Pressure-sensitive cycle control
- Engineered and manufactured using processes independently certified to internationally recognized quality standards ISO-9001:2000 and Telecommunications Industry Standard TL 9000.

Common COMPATIBLE SHOULDER DIES				
58423-I	58536-I	91900-1		
58425-I	58545-I	220189-1		

For closed-barrel terminals


Common COMPATIBLE PIN DIES				
58448-3	90546-2	90800-2		
58495-2	90758-2	217212-2		


For open-barrel terminals

CRIMPING TOOL (with Battery Installed)				
Length	356 mm [14 in]			
Width	60 mm [2 3/8 in]			
Depth	80 mm [3 1/8 in]			
Mass Weight (w/Battery)	I.5 kg [3.4 lb]			
Sound Level	75 dBA at 1 m			
Vibration	<2.5 m/s ²			
Hydraulic Oil	Shell Tellus® T 15			
CRIMPING CAPACITIES				
Maximum Crimping Force	15.6 kN [1.75 ton]			
Average Crimping Time	2 sec			
Average Crimps Per Charge	Approximately 100			
BATTERY				
Charging Voltage	9.6 V			
Charging Time	40 min			
SPARE PARTS (Applies to all battery kits)				
Battery, 9.6V	1725839-1			
Battery Charger I20 V	1725840-1			
Battery Charger 220 V	1725840-2			















CERTI-CRIMP, Large Die, C-Head Adapter Battery Powered Crimp Tool Kit, Dies not included

Part No. 1213840-() 110 V


(-1 includes Ram Retract Switch; -3 without)
Part No. 1213840-() 220V


(-2 includes Ram Retract Switch; -4 without)

See Customer Manual CM 409-10057









4-Ton Latch Head Battery Powered Crimp Tool Kit,

Dies not included


Part No. 1901343-() 110 V


(-1 includes Ram Retract Switch; -3 without)

Part No. 1901343-() 220V

(-2 includes Ram Retract Switch; -4 without)

See Customer Manual CM 409-10070





CRIMPING TOOL (with Battery Installed)			
356 mm [14 in]			
60 mm [2 3/8 in]			
80 mm [3 1/8 in]			
1.6 kg [3.5 lb]			
75 dBA at 1 meter			
<2.5 m/s ²			
Shell Tellus® T 15			
CRIMPING CAPACITIES			
35 kN [4 ton]			
4 sec			
Approx. 85			

Latch Head Crimping Dies for TERMINYL and PLASTI-GRIP Terminals and Splices				
AWG	Crimping Die	Die & Splice Color Code		
8	1901006-1	Red		
6	1901007-1	Blue		
Latch Head Crimping Dies for SOLISTRAND Terminals and Splices				
AWG	Die / Nest	Die / Indenter		
8	1901001-1	1901002-2		
6	1901000-1	1901002-1		
4	1901000-2	1901002-1		
2	1901000-3	1901002-1		
Latch Head Crimping Dies for AMPLI-BOND Connectors				
AWG	Die / Nest			
8	1901727-1			

©2006 by Tyco Electronics Corporation.

All Rights Reserved. AMP, AMPLI-BOND, CERTI-CRIMP, PLASTI-GRIP, SOLISTRAND, T-HEAD, TERMINYL and TYCO are trademarks. Belden is a trademark of Belden Wire and Cable of Cooper Industries.; ST-Trademark of American Telephone & Telegraph Co.; ${\tt MONTROSE-Trademark\ of\ MONTROSE\ Products\ Co.}$

tyco **Electronics** Need More Information?

For information about tooling, call 1-800-522-6752 or e-mail toolsales@tycoelectronics.com.

