



DESOLDERING BRAID

Desoldering braid is used to remove solder, which allows components to be replaced and excess solder to be cleaned off. Plato® desoldering braid combines innovative product design with proprietary processing. All this plus exacting quality control makes Plato® a premium name in wick!

ADVANCED BRAID DESIGN

The large surface area created by the one-over, one-under construction enhances the absorption and trapping of molten solder.

ULTRA-PURE PROCESS

To ensure fast, reliable wicking action, the copper braid is cleaned using a proprietary, multi-stage process that removes oxidation and other residues before flux is added.

VACUUM-PACKAGED

For longer shelf life, Plato® desoldering braid is vacuum sealed in durable clear plastic to protect it from moisture and other environmental elements.








ESD-SAFE BOBBINS



Plato desoldering braid comes in static dissipative bobbins (except 25', 50' and 100' spools) for static sensitive environments.

How To Order:

Specify "Part Number" and "Length."
For example: XL1-5 for 5 feet of #1 white desoldering braid.

#1 WHITE	#2 YELLOW	#3 GREEN	#4 BLUE	#5 BROWN
				
.035" (0.9mm)	.055" (1.4mm)	.075" (1.9mm)	.098" (2.5mm)	.130" (3.3mm)



PLATO-WICK XL PREMIUM DESOLDERING BRAID (PURE ROSIN)

For the fastest wicking action, rosin flux coated braid is ideal for high volume PCB production/repair environments.

Size/Color	XL1	XL2	XL3	XL4	XL5
Length	-5 -10 -25 -50 -100	-5 -10 -25 -50 -100	-5 -10 -25 -50 -100	-5 -10 -25 -50 -100	-5 -10 -25 -50 -100



PLATO-WICK NO-CLEAN DESOLDERING BRAID

The cleanest No-Clean braid in the industry. The proprietary flux formula is specially designed to avoid catastrophic and latent PCB failures caused by ionic flux residue.

Size/Color	XLNC1	XLNC2	XLNC3	XLNC4	XLNC5
Length	-5 -10	-5 -10	-5 -10	-5 -10	-5 -10

25', 50' and 100' spools not available in ESD bobbins.