


- Qualification in Accordance With AEC-Q100†
- Qualified for Automotive Applications
- Customer-Specific Configuration Control Can Be Supported Along With Major-Change Approval†
- ESD Protection Exceeds 2000 V Per MIL-STD-883, Method 3015; Using Human Body Model (C = 100 pF, R = 1500 Ω)
- 3-Pin SOT-23 Package
- Supply Current of 9 μA (Typical)
- Precision Supply Voltage Monitor
2.5 V, 3 V, 3.3 V, 5 V
- Power-On Reset Generator With Fixed Delay Time of 200 ms
- Pin-For-Pin Compatible With MAX 809

† Contact factory for details. Q100 qualification data available on request.




description

The TPS3809 family of supervisory circuits provides circuit initialization and timing supervision, primarily for DSPs and processor-based systems.

During power-on, $\overline{\text{RESET}}$ is asserted when the supply voltage V_{DD} becomes higher than 1.1 V. Thereafter, the supervisory circuit monitors V_{DD} and keeps $\overline{\text{RESET}}$ active as long as V_{DD} remains below the threshold voltage V_{IT} . An internal timer delays the return of the output to the inactive state (high) to ensure proper system reset. The delay time, $t_{\text{d(typ)}} = 200 \text{ ms}$, starts after V_{DD} has risen above the threshold voltage V_{IT} . When the supply voltage drops below the threshold voltage V_{IT} , the output becomes active (low) again. No external components are required. All the devices of this family have a fixed sense-threshold voltage V_{IT} set by an internal voltage divider.

The product spectrum is designed for supply voltages of 2.5 V, 3 V, 3.3 V, and 5 V. The circuits are available in a 3-pin SOT-23. The TPS3809xxxQ-Q1 devices are characterized for operation over a temperature range of -40°C to 125°C , and are qualified in accordance with AEC-Q100 stress test qualification for integrated circuits.

typical applications



- Applications Using Automotive DSPs, Microcontrollers, or Microprocessors
- Wireless Communication Systems
- Battery-Powered Equipment
- Programmable Controls
- Intelligent Instruments
- Industrial Equipment
- Automotive Systems

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

TPS3809J25-Q1, TPS3809L30-Q1, TPS3809K33-Q1, TPS3809I50-Q1 3-PIN SUPPLY VOLTAGE SUPERVISORS

SGLS142 – DECEMBER 2002

AVAILABLE OPTIONS


| T _A | DEVICE NAME | THRESHOLD VOLTAGE | MARKING |
|----------------|--------------------|-------------------|---------|
| -40°C to 125°C | TPS3809J25QDBVRQ1† | 2.25 V | PCZQ |
| | TPS3809L30QDBVRQ1† | 2.64 V | PDAQ |
| | TPS3809K33QDBVRQ1† | 2.93 V | PDBQ |
| | TPS3809I50QDBVRQ1† | 4.55 V | PDCQ |

† The DBVR passive indicates tape and reel of 3000 parts.


FUNCTION/TRUTH TABLE, TPS3809

| V _{DD} >V _{IT} | RESET |
|----------------------------------|-------|
| 0 | L |
| 1 | H |

ORDERING INFORMATION




functional block diagram



TPS3809J25-Q1, TPS3809L30-Q1, TPS3809K33-Q1, TPS3809I50-Q1 3-PIN SUPPLY VOLTAGE SUPERVISORS

SGLS142 – DECEMBER 2002

timing diagram



absolute maximum ratings over operating free-air temperature (unless otherwise noted)[†]

| | |
|--|------------------------------|
| Supply voltage, V_{DD} (see Note 1) | 7 V |
| All other pins (see Note 1) | -0.3 V to 7 V |
| Maximum low output current, I_{OL} | 5 mA |
| Maximum high output current, I_{OH} | -5 mA |
| Input clamp current, I_{IK} ($V_I < 0$ or $V_I > V_{DD}$) | ± 20 mA |
| Output clamp current, I_{OK} ($V_O < 0$ or $V_O > V_{DD}$) | ± 20 mA |
| Continuous total power dissipation | See Dissipation Rating Table |
| Operating free-air temperature range, T_A | -40°C to 125°C |
| Storage temperature range, T_{stg} | -65°C to 150°C |
| Soldering temperature | 260°C |

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltage values are with respect to GND. For reliable operation the device should not be operated at 7 V for more than $t=1000h$ continuously.

DISSIPATION RATING TABLE

| PACKAGE | $T_A < 25^\circ\text{C}$ POWER RATING | DERATING FACTOR ABOVE $T_A = 25^\circ\text{C}$ | $T_A = 70^\circ\text{C}$ POWER RATING | $T_A = 85^\circ\text{C}$ POWER RATING | $T_A = 125^\circ\text{C}$ POWER RATING |
|---------|--|---|--|--|---|
| DBV | 437 mW | 3.5 mW/°C | 280 mW | 227 mW | 87 mW |

recommended operating conditions at specified temperature range

| | MIN | MAX | UNIT |
|---|-----|-----|------|
| Supply voltage, V_{DD} | 2 | 6 | V |
| Operating free-air temperature range, T_A | -40 | 125 | °C |

TPS3809J25-Q1, TPS3809L30-Q1, TPS3809K33-Q1, TPS3809I50-Q1 3-PIN SUPPLY VOLTAGE SUPERVISORS

SGLS142 – DECEMBER 2002

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT | |
|-------------------------------------|---|---|---------------------------------|----------------------|------|------|---|
| V _{OH} | High-level output voltage | V _{DD} = 2.5 V to 6 V, I _{OH} = -500 μA | V _{DD} -0.2 | | | V | |
| | | V _{DD} = 3.3 V, I _{OH} = -2 mA | V _{DD} -0.4 | | | | |
| | | V _{DD} = 6 V, I _{OH} = -4 mA | T _A = -40°C to 25°C | V _{DD} -0.4 | | | |
| | | | T _A = 125°C | V _{DD} -0.5 | | | |
| V _{OL} | Low-level output voltage | V _{DD} = 2 V to 6 V, I _{OL} = 500 μA | | | 0.2 | V | |
| | | V _{DD} = 3.3 V, I _{OL} = 2 mA | | | 0.4 | | |
| | | V _{DD} = 6 V, I _{OL} = 4 mA | | | 0.4 | | |
| Power-up reset voltage (see Note 2) | | V _{DD} ≥ 1.1 V, I _{OL} = 50 μA | | | 0.2 | V | |
| V _{IT-} | Negative-going input threshold voltage (see Note 3) | TPS3809J25 | T _A = -40°C to 125°C | 2.20 | 2.25 | 2.30 | V |
| | | TPS3809L30 | | 2.58 | 2.64 | 2.70 | |
| | | TPS3809K33 | | 2.87 | 2.93 | 2.99 | |
| | | TPS3809I50 | T _A = -40°C to 85°C | 4.45 | 4.55 | 4.65 | |
| | | | T _A = -40°C to 125°C | 4.4 | 4.55 | 4.65 | |
| V _{hys} | Hysteresis | TPS3809J25 | | 30 | | mV | |
| | | TPS3809L30 | | 35 | | | |
| | | TPS3809K33 | | 40 | | | |
| | | TPS3809I50 | | 60 | | | |
| I _{DD} | Supply current | V _{DD} = 2 V, Output unconnected | | 9 | 15 | μA | |
| | | V _{DD} = 6 V, Output unconnected | | 20 | 30 | | |
| C _i | Input capacitance | V _I = 0 V to V _{DD} | | 5 | | pF | |

NOTES: 2. The lowest supply voltage at which $\overline{\text{RESET}}$ becomes active. $t_r, V_{DD} \geq 15 \mu\text{s/V}$.
3. To ensure best stability of the threshold voltage, a bypass capacitor (0.1 μF ceramic) should be placed near the supply terminals.

timing requirements at R_L = 1 MΩ, C_L = 50 pF, T_A = 25°C

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|----------------|-------------|--|-----|-----|-----|------|
| t _w | Pulse width | at V _{DD} V _{DD} = V _{IT-} + 0.2 V, V _{DD} = V _{IT-} - 0.2 V | 3 | | | μs |





switching characteristics at R_L = 1 MΩ, C_L = 50 pF, T_A = 25°C

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|------------------|--|---|-----|-----|-----|------|
| t _d | Delay time | V _{DD} ≥ V _{IT-} + 0.2 V, See timing diagram | 120 | 200 | 280 | ms |
| t _{PHL} | Propagation (delay) time, high-to-low-level output | V _{DD} to $\overline{\text{RESET}}$ delay V _{IL} = V _{IT-} - 0.2 V, V _{IH} = V _{IT-} + 0.2 V | | 1 | | μs |

TPS3809J25-Q1, TPS3809L30-Q1, TPS3809K33-Q1, TPS3809I50-Q1 3-PIN SUPPLY VOLTAGE SUPERVISORS

SGLS142 – DECEMBER 2002

TYPICAL CHARACTERISTICS



TPS3809J25-Q1, TPS3809L30-Q1, TPS3809K33-Q1, TPS3809I50-Q1 3-PIN SUPPLY VOLTAGE SUPERVISORS

SGLS142 – DECEMBER 2002

TYPICAL CHARACTERISTICS




Figure 5




Figure 6


TPS3809J25-Q1, TPS3809L30-Q1, TPS3809K33-Q1, TPS3809I50-Q1
 3-PIN SUPPLY VOLTAGE SUPERVISORS

SGLS142 – DECEMBER 2002

MECHANICAL DATA

DBV (R-PDSO-G3)

PLASTIC SMALL-OUTLINE



- NOTES: A. All linear dimensions are in millimeters.
 B. This drawing is subject to change without notice.
 C. Body dimensions do not include mold flash or protrusion.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Mailing Address:

Texas Instruments
Post Office Box 655303
Dallas, Texas 75265