



CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

查询CVCO55CL-0072-0076供应商


Voltage Controlled Oscillator-VCO CVCO55CL-0072-0076

集多邦 专业PCB打样工厂 24小时加急出货





PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			72	MHz
Upper Frequency:	76			MHz
Tuning Voltage:	0.3		3.0	VDC
Supply Voltage:	3.135	3.3	3.465	VDC
Output Power:	-2.0	0	+2.0	dBm
Supply Current:		5	7	mA
Harmonic Suppression (2 nd Harmonic):			-15	dBc
Pushing:			1.0	MHz/V
Pulling, all Phases:			2.0	MHz pk-pk
Tuning Sensitivity:		7		MHz/V
Phase Noise @ 10kHz offset:		-110		dBc/Hz
Phase Noise @ 100kHz offset:		-128		dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			60	pF
Operating Temperature Range:	-40		+85	$^{\circ}\text{C}$
Storage Temperature Range:	-45		+90	$^{\circ}\text{C}$

Phase Noise (1 Hz BW, Typical)



Tuning Curve (Typical)







CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

Voltage Controlled Oscillator-VCO

CVCO55CL-0072-0076



TAPE AND REEL



Drawing not to scale

Product Control:

Crystek Part Number:	CVCO55CL-0072-0076	Release Date:	31-March-08
Revision Level:	C	Responsible:	C. Vales

Specification is subject to change without notice



CRYSTEK