

查询CVCO55BE-1930-1990供应商
CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

捷多邦, 专业PCB打样工厂, 24小时加急出货


Voltage Controlled Oscillator-VCO

CVCO55BE-1930-1990





PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			1930	MHz
Upper Frequency:	1990			MHz
Tuning Voltage:	0.5		4.5	VDC
Supply Voltage:	4.75	5.0	5.25	VDC
Output Power:	0	+2.5	+5.0	dBm
Supply Current:		15	20	mA
Harmonic Suppression (2 nd Harmonic):		-15	-10	dBc
Pushing:		1.0	2.0	MHz/V
Pulling, all Phases:		11.0	13.0	MHz pk-pk
Tuning Sensitivity:		25		MHz/V
Phase Noise @ 10kHz offset:		-105	-101	dBc/Hz
Phase Noise @ 100kHz offset:		-122	-118	dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			33	pF
Operating Temperature Range:	-40		+70	$^{\circ}\text{C}$
Storage Temperature Range:	-45		+90	$^{\circ}\text{C}$

Phase Noise (1 Hz BW, Typical)



Tuning Curve (Typical)







CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

Voltage Controlled Oscillator-VCO

CVCO55BE-1930-1990



TAPE AND REEL



Drawing not to scale

Product Control:

Crystek Part Number:	CVCO55BE-1930-1990	Release Date:	12-March-08
Revision Level:	E	Responsible:	C. Vales

Specification is subject to change without notice



CRYSTEK

12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913