

查询B41691A5108Q009供应商

捷多邦，专业PCB打样工厂
，24小时加急出货



Aluminum electrolytic capacitors

Axial-lead and soldering star capacitors

Series/Type: B41691, B41791

Date: December 2006

© EPCOS AG 2007. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.




Applications

- For automotive applications up to 150 °C

Features

- Long useful life, 2000 h at up to 150 °C
- Low ESR also at 63 V DC
- High ripple current capability
- High vibration resistance
- Shelf life up to 15 years at storage temperatures up to 40 °C.
To ensure solderability, the capacitors should be built into the application within one year of delivery. After a total of two years' storage, the operating voltage must be applied for one hour to ensure the specified leakage current.



Construction

- Charge/discharge-proof, polar
- Aluminum case with insulating sleeve
- Negative pole connected to case

Terminals

- Axial leads, welded to ensure perfect electrical contact
- Also available with soldering stars


Taping and packing

- Axial-lead capacitors will be delivered in pallet package.
Capacitors with $d \times l \leq 16 \times 30$ mm are also available taped on reel.
- Soldering star capacitors are packed in cardboard.




B41691, B41791

Long useful life – up to 150 °C



Specifications and characteristics in brief

| | | | | | | | |
|--|---|---------------|---|----|----|----|-------|
| Rated voltage V_R | 25 ... 63 V DC | | | | | | |
| Surge voltage V_S | $1.15 \cdot V_R$ | | | | | | |
| Rated capacitance C_R | 100 ... 4000 μ F | | | | | | |
| Capacitance tolerance | -10/+30% \triangle Q | | | | | | |
| Leakage current I_{leak} (5 min, 20 °C) | $I_{leak} \leq 0.006 \mu A \cdot \left(\frac{C_R}{\mu F} \cdot \frac{V_R}{V} \right) + 4 \mu A$ | | | | | | |
| Self-inductance ESL ¹⁾ | Diameter d (mm) | | 12 | 14 | 16 | 18 | 20/21 |
| | Terminals | Length l (mm) | Approx. ESL (nH) | | | | |
| | axial | 25 | – | 22 | 26 | – | – |
| | | 29 | – | – | – | – | 38 |
| | | 30 | 21 | 24 | 29 | 34 | – |
| | | 39 | – | – | 33 | 38 | 45 |
| | | 49 | – | – | – | – | 50 |
| soldering star | 25 | – | 6 | 7 | – | – | |
| | 30 | 6 | 7 | 8 | 10 | – | |
| | 39 | – | – | 9 | 11 | – | |
| Useful life | | | Requirements: | | | | |
| 150 °C, V_R , $0.5 \cdot I_{AC,R}$ | > 2000 h | | $\Delta C/C \leq \pm 30\%$ of initial value | | | | |
| 125 °C, V_R , $I_{AC,R}$ | > 10000 h | | ESR ≤ 3 times initial specified limit | | | | |
| 125 °C, V_R , $I_{AC,max}$ | > 4000 h | | $I_{leak} \leq$ initial specified limit | | | | |
| 105 °C, V_R , $I_{AC,max}$ | > 8000 h | | | | | | |
| 85 °C, V_R , $I_{AC,max}$ | > 15000 h | | | | | | |
| 40 °C, V_R , $2.1 \cdot I_{AC,R}$ | > 500000 h | | | | | | |
| Voltage endurance test | | | Post test requirements: | | | | |
| 125 °C; V_R | 5000 h | | $\Delta C/C \leq \pm 10\%$ of initial value | | | | |
| | | | ESR $\leq 1.3\%$ initial specified limit | | | | |
| | | | $I_{leak} \leq$ initial specified limit | | | | |
| Vibration resistance test | To IEC 60068-2-6, test Fc: Displacement amplitude 1.5 mm, at 10 Hz ... 2 kHz, acceleration max. 20 g, duration 3 \times 2 h. Capacitor mounted by its wire leads at a distance of (6 \pm 1) mm from the case and additionally clamped by the case. | | | | | | |
| IEC climatic category | To IEC 60068-1: 55/125/56 (-55 °C/+125 °C/56 days damp heat test) | | | | | | |
| Detail specification | Similar to CECC 30301-802 | | | | | | |
| Sectional specification | IEC 60384-4 | | | | | | |




B41691, B41791

Long useful life – up to 150 °C

Axial-lead capacitors

Dimensional drawing




*) for d = 21 mm: 35-5

1.3+0.1

KAL0524-S-E


Dimensions, weights and packing units

| d × l mm | d _{max} × l _{max} mm | Approx. weight g | Packing units (pcs.) | |
|-------------|---|---------------------|----------------------|------|
| | | | Pallet | Reel |
| 12 × 30 | 12.5 × 30.5 | 5.1 | 288 | 450 |
| 14 × 25 | 14.5 × 25.5 | 5.7 | 200 | 350 |
| 14 × 30 | 14.5 × 30.5 | 6.8 | 200 | 350 |
| 16 × 30 | 16.5 × 30.5 | 8.9 | 180 | 250 |
| 16 × 39 | 16.5 × 40 | 11.7 | 180 | — |
| 18 × 30 | 18.5 × 30.5 | 11.1 | 160 | — |
| 18 × 39 | 18.5 × 40 | 14.7 | 160 | — |
| 20 × 29 | 20.5 × 29.5 | 13.5 | 140 | — |
| 21 × 39 | 21.5 × 40 | 20.0 | 140 | — |
| 21 × 49 | 21.5 × 50 | 25.0 | 110 | — |





Soldering star capacitors


Dimensional drawing



Mounting holes
d = 12 mm ... 14 mm




Mounting holes
d = 16 mm ... 18 mm



KAL0666-9

Dimensions, weights and packing units

| d × l mm | d _{max} × l _{max} mm | c ±0.1 mm | Approx. weight g | Packing units pcs. |
|-------------|---|--------------|---------------------|-----------------------|
| 12 × 30 | 13.5 × 32 | 12.5 | 5.4 | 480 |
| 14 × 25 | 15.5 × 27 | 14.5 | 6.1 | 480 |
| 14 × 30 | 15.5 × 32 | 14.5 | 7.2 | 480 |
| 16 × 30 | 17.5 × 32 | 16.5 | 9.4 | 300 |
| 16 × 39 | 17.5 × 41.5 | 16.5 | 12.2 | 200 |
| 18 × 30 | 19.5 × 32 | 18.5 | 11.8 | 300 |
| 18 × 39 | 19.5 × 41.5 | 18.5 | 15.4 | 200 |



B41691, B41791

Long useful life – up to 150 °C


Overview of available types

| V_R (V DC) | 25 | 40 | 63 |
|-------------------------|-----------------------------------|--------------------|--------------------|
| | Case dimensions $d \times l$ (mm) | | |
| C_R (μF) | | | |
| 100 | | | 12 × 30 |
| 150 | | | 14 × 25 |
| 220 | | | 14 × 30 |
| 330 | 12 × 30 | 12 × 30 | |
| 470 | 14 × 25 | 14 × 30 | 16 × 39 18 × 30 |
| 560 | | | 20 × 29 |
| 680 | | 16 × 30 | 18 × 39 |
| 1000 | 16 × 30 | 16 × 39 18 × 30 | 21 × 39 |
| 1200 | | 20 × 29 | 21 × 49 |
| 1500 | 16 × 39 18 × 30 | 18 × 39 | |
| 1800 | 20 × 29 | | |
| 2000 | 18 × 39 | | |
| 2200 | | 21 × 39 | |
| 2700 | | 21 × 49 | |
| 3000 | 21 × 39 | | |
| 4000 | 21 × 49 | | |



B41691, B41791


Long useful life – up to 150 °C



Case dimensions and ordering codes

| V_R | C_R | Case dimensions $d \times l$ mm | Ordering code Axial pallet | Ordering code Axial reel | Ordering code Soldering star |
|-------|---------|---------------------------------------|-------------------------------|-----------------------------|---------------------------------|
| V DC | μF | | | | |
| 25 | 330 | 12 × 30 | B41691A5337Q007 | B41691A5337Q009 | B41791A5337Q000 |
| | 470 | 14 × 25 | B41691A5477Q007 | B41691A5477Q009 | B41791A5477Q000 |
| | 1000 | 16 × 30 | B41691A5108Q007 | B41691A5108Q009 | B41791A5108Q000 |
| | 1500 | 16 × 39 | B41691A5158Q007 | | B41791A5158Q000 |
| | 1500 ▽ | 18 × 30 | B41691B5158Q007 | | B41791B5158Q000 |
| | 1800 | 20 × 29 | B41691A5188Q007 | | |
| | 2000 | 18 × 39 | B41691A5208Q007 | | B41791A5208Q000 |
| | 3000 | 21 × 39 | B41691A5308Q007 | | |
| | 4000 | 21 × 49 | B41691A5408Q007 | | |
| 40 | 330 | 12 × 30 | B41691A7337Q007 | B41691A7337Q009 | B41791A7337Q000 |
| | 470 | 14 × 30 | B41691A7477Q007 | B41691A7477Q009 | B41791A7477Q000 |
| | 680 | 16 × 30 | B41691A7687Q007 | B41691A7687Q009 | B41791A7687Q000 |
| | 1000 | 16 × 39 | B41691A7108Q007 | | B41791A7108Q000 |
| | 1000 ▽ | 18 × 30 | B41691B7108Q007 | | B41791B7108Q000 |
| | 1200 | 20 × 29 | B41691A7128Q007 | | |
| | 1500 | 18 × 39 | B41691A7158Q007 | | B41791A7158Q000 |
| | 2200 | 21 × 39 | B41691A7228Q007 | | |
| | 2700 | 21 × 49 | B41691A7278Q007 | | |
| 63 | 100 | 12 × 30 | B41691A8107Q007 | B41691A8107Q009 | B41791A8107Q000 |
| | 150 | 14 × 25 | B41691A8157Q007 | B41691A8157Q009 | B41791A8157Q000 |
| | 220 | 14 × 30 | B41691A8227Q007 | B41691A8227Q009 | B41791A8227Q000 |
| | 470 | 16 × 39 | B41691A8477Q007 | | B41791A8477Q000 |
| | 470 ▽ | 18 × 30 | B41691B8477Q007 | | B41791B8477Q000 |
| | 560 | 20 × 29 | B41691A8567Q007 | | |
| | 680 | 18 × 39 | B41691A8687Q007 | | B41791A8687Q000 |
| | 1000 | 21 × 39 | B41691A8108Q007 | | |
| | 1200 | 21 × 49 | B41691A8128Q007 | | |

▽ Variant with different case dimensions




B41691, B41791

Long useful life – up to 150 °C

Technical data


| C_R | ESR_{typ} | ESR_{max} | ESR_{max} | ESR_{max} | Z_{max} | $I_{AC,max}$ | $I_{AC,max}$ | $I_{AC,max}$ | $I_{AC,R}$ | $I_{AC,max}$ |
|-----------------------------------|-------------|-------------|-------------|-------------|------------|--------------|--------------|--------------|------------|--------------|
| 100 Hz | 100 Hz | 100 Hz | 100 Hz | 10 kHz | 100 kHz | 10 kHz | 10 kHz | 10 kHz | 10 kHz | 10 kHz |
| 20 °C | 20 °C | 20 °C | -40 °C | 20 °C | 20 °C | 85 °C | 105 °C | 125 °C | 125 °C | 150 °C |
| μF | m Ω | m Ω | m Ω | m Ω | m Ω | A | A | A | A | A |
| $V_R = 25 V DC$ | | | | | | | | | | |
| 330 | 175 | 290 | 1600 | 150 | 150 | 4.8 | 4.3 | 3.4 | 2.1 | 1.05 |
| 470 | 125 | 210 | 1200 | 110 | 102 | 5.1 | 4.6 | 3.7 | 2.2 | 1.1 |
| 1000 | 65 | 110 | 550 | 60 | 55 | 7.3 | 6.5 | 5.2 | 3.2 | 1.6 |
| 1500 | 44 | 73 | 370 | 42 | 39 | 10.1 | 9.0 | 7.2 | 4.4 | 2.2 |
| 1500 ▽ | 42 | 69 | 370 | 38 | 35 | 10.5 | 9.4 | 7.5 | 4.6 | 2.3 |
| 1800 | 35 | 58 | 300 | 32 | 30 | 11.3 | 10.1 | 8.1 | 4.9 | 2.4 |
| 2000 | 31 | 50 | 270 | 28 | 26 | 14.2 | 12.7 | 10.2 | 6.2 | 3.1 |
| 3000 | 22 | 37 | 180 | 22 | 21 | 16.1 | 14.3 | 11.5 | 7.0 | 3.5 |
| 4000 | 17 | 29 | 135 | 17 | 16 | 20.2 | 18 | 14.5 | 8.8 | 4.4 |
| $V_R = 40 V DC$ | | | | | | | | | | |
| 330 | 150 | 240 | 1250 | 115 | 105 | 5.3 | 4.8 | 3.8 | 2.3 | 1.15 |
| 470 | 110 | 170 | 900 | 85 | 77 | 6.4 | 5.7 | 4.6 | 2.8 | 1.4 |
| 680 | 80 | 120 | 600 | 65 | 60 | 7.3 | 6.5 | 5.2 | 3.1 | 1.5 |
| 1000 | 55 | 80 | 410 | 45 | 41 | 10.0 | 8.9 | 7.2 | 4.3 | 2.1 |
| 1000 ▽ | 52 | 77 | 410 | 40 | 37 | 10.3 | 9.2 | 7.4 | 4.5 | 2.2 |
| 1200 | 44 | 55 | 320 | 35 | 33 | 11.2 | 10.0 | 8.0 | 4.9 | 2.4 |
| 1500 | 35 | 53 | 270 | 27 | 25 | 14.2 | 12.7 | 10.2 | 6.2 | 3.1 |
| 2200 | 26 | 39 | 185 | 21 | 20 | 16.1 | 14.3 | 11.5 | 7.0 | 3.5 |
| 2700 | 21 | 30 | 150 | 18 | 17 | 20.1 | 17.9 | 14.4 | 8.7 | 4.3 |
| $V_R = 63 V DC$ | | | | | | | | | | |
| 100 | 350 | 350 | 1900 | 160 | 150 | 4.7 | 4.2 | 3.3 | 2.0 | 1.0 |
| 150 | 240 | 240 | 1300 | 115 | 110 | 5.1 | 4.5 | 3.6 | 2.2 | 1.1 |
| 220 | 165 | 170 | 900 | 80 | 76 | 6.5 | 5.8 | 4.6 | 2.8 | 1.4 |
| 470 | 80 | 120 | 410 | 42 | 40 | 10.1 | 9.0 | 7.2 | 4.4 | 2.2 |
| 470 ▽ | 77 | 114 | 410 | 38 | 36 | 10.5 | 9.3 | 7.5 | 4.5 | 2.3 |
| 560 | 65 | 75 | 320 | 34 | 33 | 11.3 | 10.1 | 8.1 | 4.9 | 2.4 |
| 680 | 54 | 78 | 280 | 27 | 25 | 14.3 | 12.8 | 10.3 | 6.2 | 3.1 |
| 1000 | 38 | 47 | 200 | 21 | 20 | 16.1 | 14.3 | 11.5 | 7.0 | 3.5 |
| 1200 | 32 | 38 | 160 | 17 | 16 | 20.1 | 18.0 | 14.4 | 8.8 | 4.4 |

▽ Variant with different case dimensions




Useful life

depending on ambient temperature T_A under ripple current operating conditions at $V_R^{1)}$




Useful life

depending on case temperature T_C under ripple current operating conditions at $V_R^{1)}$




1) Refer to chapter "General technical information, 5.3 Calculation of useful life" for an explanation on how to interpret the useful life




B41691, B41791

Long useful life – up to 150 °C

Frequency factor of permissible ripple current I_{AC} versus frequency f




Frequency characteristics of ESR
Typical behavior




Equivalent series resistance ESR versus frequency f

Typical behavior for 470 μ F/63 V



Impedance Z versus frequency f


Typical behavior for 470 μ F/63 V





B41691, B41791

Long useful life – up to 150 °C



Cautions and warnings


Personal safety

The electrolytes used by EPCOS have not only been optimized with a view to the intended application, but also with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC).

Furthermore, part of the high-voltage electrolytes used by EPCOS are self-extinguishing. They contain flame-retarding substances which will quickly extinguish any flame that may have been ignited.

As far as possible, EPCOS does not use any dangerous chemicals or compounds to produce operating electrolytes. However, in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no safe substitute materials are currently known. However, the amount of dangerous materials used in our products has been limited to an absolute minimum. Nevertheless, the following rules should be observed when handling Al electrolytic capacitors:

- Any escaping electrolyte should not come into contact with eyes or skin.
- If electrolyte does come into contact with the skin, wash the affected parts immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment.
- Avoid breathing in electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.



B41691, B41791

Long useful life – up to 150 °C

Product safety


The table below summarize the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of chapter "General technical information".

| Topic | Safety information | Reference Chapter "General technical information" |
|--|---|--|
| Polarity | Make sure that polar capacitors are connected with the right polarity. | 1 "Basic construction of aluminum electrolytic capacitors" |
| Reverse voltage | Voltages polarity classes should be prevented by connecting a diode. | 3.1.6 "Reverse voltage" |
| Upper category temperature | Do not exceed the upper category temperatur. | 7.2 "Maximum permissible operating temperature" |
| Maintenance | Make periodic inspections of the capacitors. Before the inspection, make sure that the power supply is turned off and carefully discharge the electricity of the capacitors. Do not apply any mechanical stress to the capacitor terminals. | 10 "Maintenance" |
| Mounting position of screw terminal capacitors | Do not mount the capacitor with the terminals (safety vent) upside down. | 11.1. "Mounting positions of capacitors with screw terminals" |
| Mounting of single-ended capacitors | The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires. Avoid any compressive, tensile or flexural stress. Do not move the capacitor after soldering to PC board. Do not pick up the PC board by the soldered capacitor. Do not insert the capacitor on the PC board with a hole space different to the lead space specified. | 11.4 "Mounting considerations for single-ended capacitors" |
| Robustness of terminals | The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2 Nm M6: 2.5 Nm | 11.3 "Mounting torques" |
| Soldering | Do not exceed the specified time or temperature | 11.5 "Soldering" |



B41691, B41791

Long useful life – up to 150 °C



| Topic | Safety information | Reference Chapter "General technical information" |
|--|---|---|
| Soldering, cleaning agents | Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors. | 11.6 "Cleaning agents" |
| Passive flammability | Avoid external energy, such as fire or electricity. | 8.1 "Passive flammability" |
| Active flammability | Avoid overload of the capacitors. | 8.2 "Active flammability" |
| | | Reference Chapter "Capacitors with screw terminals" |
| Breakdown strength of insulating sleeves | Do not damage the insulating sleeve, especially when ring clips are used for mounting. | "Screw terminals - accessories" |



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, EPCOS-JONES, BAOKE, Alu-X, CeraDiode, CSSP, MLSC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, UltraCap, WindCap are **trademarks registered or pending in Europe and in other countries**. Further information will be found on the Internet at www.epcos.com/trademarks.