

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

HD

High Ripple Low Impedance

series





Smaller



Low Impedance

Anti-Solvent
Feature


- Lower impedance at high frequency range.
- Smaller case size and high ripple current.
- Adapted to the RoHS directive (2002/95/EC).



Specifications

Item	Performance Characteristics							
Category Temperature Range	-40 ~ +105°C							
Rated Voltage Range	6.3 ~ 50V							
Rated Capacitance Range	22 ~ 6800μF							
Capacitance Tolerance	±20% at 120Hz, 20°C							
Leakage Current	After 2 minutes' application of rated voltage, leakage current is not more than 0.01CV or 3 (μA), whichever is greater.							
tan δ	Rated voltage (V)	6.3	10	16	25	35	50	120Hz
	tan δ (MAX.)	0.22	0.19	0.16	0.14	0.12	0.10	20°C
	For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF.							
Stability at Low Temperature	Rated voltage (V)	6.3	10	16	25	35	50	120Hz
	Impedance ratio	Z-25°C / Z+20°C	2	2	2	2	2	
	ZT / Z20 (MAX.)	Z-40°C / Z+20°C	3	3	3	3	3	
Endurance	After an application of D.C. bias voltage plus the rated ripple current for 5000 hours (φD ≤ 6.3 : 2000 hours, φD=8 : 3000 hours, φD=10 : 4000 hours) at 105°C the peak voltage shall not exceed the rated D.C. voltage, capacitors meet the characteristic requirements listed below.							
	Capacitance change	Within ± 25% of initial value						
	tan δ	200% or less of initial specified value						
	Leakage current	Initial specified value or less						
Marking	Printed with white color letter on black sleeve.							


Radial Lead Type



α	(mm)					
	(L < 20)	1.5				
	(L ≥ 20)	2.0				
φD	5	6.3	8	10	12.5	16
P	2.0	2.5	3.5	5.0	5.0	7.5
φd	0.5	0.5	0.6	0.6	0.6	0.8

* In case L > 25 for the φ12.5 dia. unit, lead dia. φd = 0.8mm.

Type numbering system (Example : 10V 3300µF)



※ Configuration

φ D	Pb-free leadwire Pb-free PET sleeve
5	DD
6.3	ED
8 · 10	PD
12.5 · 16	HD

• Please refer to page 21 about the end seal configuration.

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

HD series

Standard ratings

V (Code) Cap. (μF) Item Code		6.3 (0J)				10 (1A)			
		Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz	Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz
			20°C / 100kHz	-10°C / 100kHz			20°C / 100kHz	-10°C / 100kHz	
100	101					5 × 11	0.30	1.0	250
150	151	5 × 11	0.30	1.0	250				
220	221					6.3 × 11	0.13	0.41	405
330	331	6.3 × 11	0.13	0.41	405				
470	471					8 × 11.5	0.072	0.22	760
560	561	8 × 11.5	0.072	0.22	760				
680	681					8 × 15	0.056	0.17	995
820	821	8 × 15	0.056	0.17	995	▲ 10 × 12.5	0.053	0.16	1030
1000	102	10 × 12.5	0.053	0.16	1030				
1200	122	8 × 20	0.041	0.13	1250	8 × 20	0.041	0.13	1250
		▲ 10 × 16	0.038	0.12	1430	▲ 10 × 16	0.038	0.12	1430
1500	152	10 × 20	0.023	0.069	1820				
2200	222	10 × 25	0.022	0.066	2150	12.5 × 20	0.021	0.053	2360
3300	332	12.5 × 20	0.021	0.053	2360	12.5 × 25	0.018	0.045	2770
3900	392	12.5 × 25	0.018	0.045	2770	12.5 × 31.5	0.016	0.041	3290
4700	472	12.5 × 31.5	0.016	0.041	3290	▲ 16 × 20	0.018	0.045	3140
5600	562	12.5 × 35.5	0.015	0.039	3400	12.5 × 35.5	0.015	0.039	3400
		▲ 16 × 20	0.018	0.045	3140	16 × 25	0.016	0.043	3460
6800	682	16 × 25	0.016	0.043	3460				

V (Code) Cap. (μF) Item Code		16 (1C)				25 (1E)			
		Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz	Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz
			20°C / 100kHz	-10°C / 100kHz			20°C / 100kHz	-10°C / 100kHz	
47	470					5 × 11	0.30	1.0	250
56	560	5 × 11	0.30	1.0	250				
100	101					6.3 × 11	0.13	0.41	405
120	121	6.3 × 11	0.13	0.41	405				
220	221					8 × 11.5	0.072	0.22	760
330	331	8 × 11.5	0.072	0.22	760	8 × 15	0.056	0.17	995
						▲ 10 × 12.5	0.053	0.16	1030
470	471	8 × 15	0.056	0.17	995	8 × 20	0.041	0.13	1250
		▲ 10 × 12.5	0.053	0.16	1030	▲ 10 × 16	0.038	0.12	1430
680	681	8 × 20	0.041	0.13	1250				
		▲ 10 × 16	0.038	0.12	1430	10 × 20	0.023	0.069	1820
820	821					10 × 25	0.022	0.066	2150
1000	102	10 × 20	0.023	0.069	1820	12.5 × 20	0.021	0.053	2360
1200	122	10 × 25	0.022	0.066	2150				
1500	152	12.5 × 20	0.021	0.053	2360	12.5 × 25	0.018	0.045	2770
1800	182					12.5 × 31.5	0.016	0.041	3290
						▲ 16 × 20	0.018	0.045	3140
2200	222	12.5 × 25	0.018	0.045	2770	12.5 × 35.5	0.015	0.039	3400
2700	272	12.5 × 31.5	0.016	0.041	3290				
		▲ 16 × 20	0.018	0.045	3140	16 × 25	0.016	0.043	3460
3300	332	12.5 × 35.5	0.015	0.039	3400				
3900	392	16 × 25	0.016	0.043	3460				

▲ : In this case, [6] will be put at 12th digit of type numbering system.

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

HD series

Standard ratings

Cap.(μF)		V (Code)		35 (1V)			50 (1H)		
		Item	Code	Case size φD × L (mm)	Impedance (Ω) MAX.		Case size φD × L (mm)	Impedance (Ω) MAX.	
					20°C / 100kHz	−10°C / 100kHz		20°C / 100kHz	−10°C / 100kHz
22	220						5 × 11	0.34	1.18
33	330			5 × 11	0.30	1.0			
56	560			6.3 × 11	0.13	0.41	6.3 × 11	0.14	0.50
100	101						8 × 11.5	0.074	0.22
120	121						8 × 15	0.061	0.18
150	151			8 × 11.5	0.072	0.22	10 × 12.5	0.061	0.18
180	181						8 × 20	0.046	0.14
220	221			8 × 15	0.056	0.17	10 × 16	0.042	0.12
				▲10 × 12.5	0.053	0.16			
270	271			8 × 20	0.041	0.13	10 × 20	0.030	0.090
330	331			10 × 16	0.038	0.12	10 × 25	0.028	0.085
470	471			10 × 20	0.023	0.069	12.5 × 20	0.027	0.068
560	561			10 × 25	0.022	0.066	12.5 × 25	0.023	0.059
680	681			12.5 × 20	0.021	0.053	12.5 × 31.5	0.021	0.052
820	821						12.5 × 35.5	0.019	0.051
							▲16 × 20	0.023	0.059
1000	102			12.5 × 25	0.018	0.045	16 × 25	0.021	0.056
1200	122			12.5 × 31.5	0.016	0.041			
				▲16 × 20	0.018	0.045			
1500	152			12.5 × 35.5	0.015	0.039			
1800	182			16 × 25	0.016	0.043			

▲ : In this case, [6] will be put at 12th digit of type numbering system.

Frequency coefficient of rated ripple current

Cap.(μF)	50Hz	120Hz	1kHz	10kHz	100kHz
22 ~ 33	0.45	0.55	0.75	0.90	1.00
39 ~ 330	0.60	0.70	0.85	0.95	1.00
390 ~ 1000	0.65	0.75	0.90	0.98	1.00
1200 ~ 6800	0.75	0.80	0.95	1.00	1.00