



New Product

SUP/SUB45N05-20L


Vishay Siliconix

N-Channel 50-V (D-S), 175°C MOSFET, Logic Level

PRODUCT SUMMARY		
$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ (Ω)	I_D (A)
50	0.018 @ $V_{GS} = 10$ V	$\pm 45^a$
	0.020 @ $V_{GS} = 4.5$ V	


175°C Rated
Maximum Junction Temperature
TrenchFET®
Power MOSFETs

TO-220AB

Top View
SUP45N05-20L

DRAIN connected to TAB

TO-263

Top View
SUB45N05-20L

N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	50	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current ($T_J = 175^\circ\text{C}$)	I_D	$\pm 45^a$	A
		± 32	
Pulsed Drain Current	I_{DM}	± 100	
Continuous Source Current (Diode Conduction) ^a	I_S	± 45	
Avalanche Current	I_{AR}	± 45	
Repetitive Avalanche Energy ^b	E_{AR}	100	mJ
Maximum Power Dissipation ^b	P_D	93 ^c	W
		3.75	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Limit	Unit
Junction-to-Ambient	R_{thJA}	40	$^\circ\text{C}/\text{W}$
		8.0	
Junction-to-Case	R_{thJC}	1.6	

Notes

- a. Package limited.
 b. Duty cycle $\leq 1\%$.
 c. See SOA curve for voltage derating.
 d. When mounted on 1" square PCB (FR-4 material).

SUP/SUB45N05-20L

Vishay Siliconix

New Product



SPECIFICATIONS (T _J =25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{DS} = 0 V, I _D = 250 μA	50			V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	1	2		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			± 100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 50 V, V _{GS} = 0 V			1	μA
		V _{DS} = 50 V, V _{GS} = 0 V, T _J = 125 °C			50	
		V _{DS} = 50 V, V _{GS} = 0 V, T _J = 175 °C			150	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 10 V	45			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 10 V, I _D = 30 A			0.018	Ω
		V _{GS} = 10 V, I _D = 30 A, T _J = 125 °C			0.030	
		V _{GS} = 4.5 V, I _D = 45 A			0.020	
Forward Transconductance ^a	g _{fs}	V _{DS} = 15 V, I _D = 45 A	20			S
Dynamic ^e						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = 25 V, f = 1 MHz		1800	3600	pF
Output Capacitance	C _{oss}			370		
Reverse Transfer Capacitance	C _{rss}			130		
Total Gate Charge ^c	Q _g	V _{DS} = 25 V, V _{GS} = 10 V, I _D = 45 A		43	60	nC
Gate-Source Charge ^c	Q _{gs}			7		
Gate-Drain Charge ^c	Q _{gd}			10		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = 25 V, R _L = 0.6 Ω I _D ≅ 45 A, V _{GEN} = 10 V, R _G = 2.5 Ω		10	20	ns
Rise Time ^c	t _r			10	20	
Turn-Off Delay Time ^c	t _{d(off)}			32	60	
Fall Time ^c	t _f			7	15	
Source-drain Diode Ratings and Characteristics (T _c = 25 °C) ^b						
Pulsed Current	I _{SM}				43	A
Forward Voltage ^a	V _{SD}	I _F = 45 A, V _{GS} = 0 V			1.5	V
Reverse Recovery Time	t _{rr}	I _F = 45 A, di/dt = 100 A/μs			49100	ns

Notes

- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- Guaranteed by design, not subject to production testing.
- Independent of operating temperature.









New Product

SUP/SUB45N05-20L

Vishay Siliconix

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





SUP/SUB45N05-20L

Vishay Siliconix

New Product



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



THERMAL RATINGS

