

Low-profile One-way Detector Switch

SPVP Series

The 2mm long stroke made the thin 1.2mm profile possible.

Power

Push

Slide

Rotary

Encoders

Detector

Dual-in-line
Package TypeMulti Control
Devices

TACT

Custom-
Products

Car Use

Features

- Low-profile: only 1.2mm from the print substrate's installation surface.
- Available for reflow soldering.
- The double-sided sliding contact provides high reliability.

Applications

- For detection mechanisms in electronic devices, including DSCs, audio players, and camcorders

Typical Specifications

Items		Specifications
Rating (max.) (Resistive load)		1mA 5V DC
Contact resistance (Initial performance/After lifetime)		5Ω max./10Ω max.
Operating force		0.55N max.
Operating life	Without load	50,000 cycles
	With load	50,000 cycles (1mA 5V DC)

Products Line


Poles	Positions	Terminal style	Location lug	Minimum packing unit (pcs.)	Products No.
1	1	For PC board (Reflow)	With	4,500	SPVP110100
			Without		SPVP120100

Unit:mm

Power
Push
Slide
Rotary
Encoders
Detector
Dual-in-line Package Type
Multi Control Devices
TACT
Custom- Products

Dimensions show only the shape of the print terminal.

■ Circuit Diagram



Products Specifications

Series Items		SPPB	SPVE	SPPW8	SPVM	SPVR	SPVP	SPVN	SPVG	SPVL	SSCM	
		-10℃ to +60℃										
Operating temperature range												
Rating (max.) (Resistive load)		0.1A 30V DC	0.1A 12V DC	0.1A 30V DC	1mA 5V DC				50mA 20V DC	1mA 5V DC		
Electrical performance	Initial contact resistance	1 Ω max.	500m Ω max.	1 Ω max.	2 Ω max.	3 Ω max.	5 Ω max.	2 Ω max.	500m Ω max.	2 Ω max.		
	Insulation resistance	100M Ω min. 100V DC										
	Voltage proof	100V AC for 1 min.										
Mechanical performance	Robustness of terminal	3N for 1 min.	0.5N for 1 min.	3N for 1 min.	1N for 1 min.	0.5N for 1 min.				1N for 1 min.	0.5N for 1 min.	
	Robustness of actuator	10N	5N	10N	5N	2N	5N		10N	5N	0.5N	
	Vibration		10 to 55 to 10Hz/min., the amplitude is 1.5mm for all the frequencies, in the 3 direction of X, Y and Z for 2 hours respectively									
	Resistance to soldering heat	Manual soldering	300±5℃, 5s max.	350±5℃, 3s max.								
		Dip soldering	260±5℃, 5±1s	—	255±5℃, 5±1s	—						
		Reflow soldering	Please see P.306									
Durability	Operating life without load	50,000 cycles 2Ω max.	50,000 cycles 1Ω max.	100,000 cycles 2Ω max.	50,000 cycles 5Ω max.		50,000 cycles 10Ω max.	50,000 cycles 5Ω max.	100,000 cycles 1Ω max.	50,000 cycles 5Ω max.		
	Operating life with load	(0.1A 30V DC) 50,000 cycles 2Ω max.	(0.1A 12V DC) 50,000 cycles 1Ω max.	(0.1A 30V DC) 100,000 cycles 2Ω max.	(1mA 5V DC) 50,000 cycles 5Ω max.		(1mA 5V DC) 50,000 cycles 10Ω max.	(1mA 5V DC) 50,000 cycles 5Ω max.	(50mA 20V DC) 100,000 cycles 1Ω max.	(1mA 5V DC) 50,000 cycles 5Ω max.		
Environmental performance	Cold	-20±2℃ for 96h	-25±2℃ for 96h	-20±2℃ for 96h					-40±2℃ for 96h	-20±2℃ for 96h		
	Dry heat	85±2℃ for 96h										
	Damp heat	40±2℃, 90 to 95%RH for 96h										

Power

Push

Slide

Rotary

Encoders

Detector

Dual-in-line
Package Type

Multi Control
Devices

TACT

Custom-
Products


Soldering Conditions

Example of Reflow Soldering Condition

1. Heating method: Double heating method with infrared heater.

2. Temperature measurement: Thermocouple 0.1 to 0.2 ϕ CA (K) or CC (T) at soldering portion (copper foil surface) . A heat resisting tape should be used for fixed measurement.

3. Temperature profile



Series (Reflow type)	A (°C) 3s max.	B (°C)	C (s)	D (°C)	E (°C)	F (s)
SPPB	250	230	40	180	150	120
SPVE	260					
SPPW8	250	200	20			
SPVM	260	230	40			
SPVR						
SPVP						
SPVN						
SPVG						
SPVL						
SSCM						
SPPY5	240		20	150	Room Temperature	180

Notes

1. The condition mentioned above is the temperature on the mounting surface of a PC board. There are cases where the PC board's temperature greatly differs from that of the switch, depending on the PC board's material, size, thickness, etc. The above-stated conditions shall also apply to switch surface temperatures.


2. As the conditions vary some how depending on the kind of reflow soldering equipment, please make sure you have the right one before use.

Taping Specifications

Taping Packaging

Reel Size

Unit:mm



Series			Number of packages (pcs.)			Reel width W (mm)	Tape width (mm)
			1 reel	1 case／domestic	1 case／export packing		
SPPB	53 (Horizontal)		1,500	3,000	6,000	24.4	24
	53 (Vertical)		600	1,200	2,400		
	63, 64		1,300	2,600	5,200		
SPVE	Standard	h=3.8	2,800	5,600	22,400	12.4	12
		h=4.1					
		h=4.8	2,200	4,400	17,600		
		h=5.2	2,000	4,000	16,000		
		h=5.5					
	Low-profile	h=3.3	2,800	5,600	22,400		
		h=4.75	2,000	4,000	16,000		
	SPPW81	h = 6.1 (Reflow)		1,000	2,000		
h = 6.55 (Reflow)							
h = 7.6 (Reflow)		850	1,700	3,400			
SPVM			3,000	6,000	12,000	16.4	16
SPVR			2,500	5,000	10,000		
SPVP			4,500	9,000	18,000		
SPVN			5,000	10,000	20,000		
SPVG			2,500	5,000	10,000		
SPVL			5,000	10,000	20,000		
SSCM			3,000	6,000	12,000		
SPPY5			550	1,650	3,300	44.4	44

Power

Push

Slide

Rotary

Encoders

Detector

Dual-in-line
Package Type

Multi Control
Devices

TACT

Custom-
Products

Note

Order products in N minimum packing units (1 reel or 1 case).