




- Designed for 802.16 and WIMAX Receiver IF Application
- Low Insertion Loss
- 5.0 X 7.0 mm Surface-Mount Case
- Differential or Single Ended Input and Output
- Complies with Directive 2002/95/EC (RoHS)



SF2073B

456.00 MHz
SAW Filter

SMP-03

Absolute Maximum Ratings

Rating	Value	Units
Maximum Incident Power in Passband	+13	dBm
Max. DC voltage between any 2 terminals	30	VDC
Storage Temperature Range	-40 to +85	°C
Suitable for lead-free soldering - Max Soldering Temperature	260°C for 30 s	

Electrical Characteristics

Characteristic		Sym	Notes	Min	Typ	Max	Units
Nominal Frequency		f _N	1		456.000		MHz
Minimum Insertion Attenuation		α _{min}	1		12.5	14.5	dB
Amplitude Variation	f _N ±5.0 MHz	Δα	1		0.6	1.5	dB p-p
	f _N ±5.2 MHz		1		0.8	2.5	
Absolute Group Delay (at f _N)			1		0.5	0.7	μs
Group Delay Variation (p-p)			1		35	100	ns
Relative Attenuation	256 to 360 MHz		1, 2	35	50		dB
	360 to 416.0 MHz		1, 2	38	64		
	416 to 443 MHz		1, 2	35	40		
	468 to 656 MHz		1, 2	35	40		
	656 to 946 MHz		1, 2	50	60		
Temperature Range	Operating			-40		85	°C
	Storage			-40		85	
Case Style			SMP-03 7 x 5 mm Nominal Footprint				
Lid Symbolization (YY=year, WW=week, S=shift)			RFM SF2073B YYWWS				

I. 200 ohm Matchingpage 2

II. 50 ohm Matchingpage 4

III. SMI 7035 Matchingpage 6

Notes:

1. Unless noted otherwise, all specifications apply over the operating temperature range.
2. Rejection is measured as attenuation below the minimum IL point in the passband. Rejection in final user application is dependent on PCB layout and external impedance matching design. See Application Note No. 42 for details.
3. The design, manufacturing process, and specifications of this filter are subject to change.
4. Tape and Reel Standard ANSI / EIA 481.
5. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
6. US and international patents may apply.
7. RFM, stylized RFM logo, and RF Monolithics, Inc. are registered trademarks of RF Monolithics, Inc.
8. ©Copyright 1999, RF Monolithics Inc.
9. Electrostatic Sensitive Device. Observe precautions for handling.




456.00 MHz

SAW Filter

I. Impedance Matching for Differential 200 Ohm Load: Coilcraft Inductors

(SAW Matched to 200 Ohms Balanced, 4:1 Transformers Account for 2dB of Loss)




0603 coilcraft inductor

456.00 MHz

SAW Filter

I. Impedance Matching for Differential 200 Ohm Load: Coilcraft Inductors



(SAW Matched to 200 Ohms Balanced, 4:1 Transformers Account for 2dB of Loss)



456.00 MHz

SAW Filter


II. Impedance Matching for Single Ended 50 Ohm load.



456.00 MHz

SAW Filter



II. Impedance Matching for Single Ended 50 Ohm load.



456.00 MHz


SAW Filter

III. Impedance Matching on SMI Radio Board: SMI 7035



456.00 MHz

SAW Filter




456.00 MHz


SAW Filter

SMP-03 Case

10-Terminal Ceramic Surface-Mount Case
7 x 5 mm Nominal Footprint




Recommended PCB Footprint



Case Dimensions						
Dimension	mm			Inches		
	Min	Nom	Max	Min	Nom	Max
A	6.80	7.00	7.20	0.268	0.276	0.283
B	4.80	5.00	5.20	0.189	0.197	0.205
C	1.50	1.65	2.00	0.059	0.065	0.079
D	.47	0.60	.73	0.019	0.024	0.029
E	2.41	2.54	2.67	0.095	0.100	0.105
H	0.87	1.0	1.13	0.034	0.039	0.044
J	4.87	5.00	5.13	0.192	0.197	0.202
K	2.87	3.00	3.13	0.113	0.118	0.123
P	1.14	1.27	1.40	0.045	0.050	0.055

Materials	
Solder Pad Termination	Au plating 30 - 60 μinches (76.2-152 μm) over 80-200 μinches (203-508 μm) Ni.
Lid	Fe-Ni-Co Alloy Electroless Nickel Plate (8-11% Phosphorus) 100-200 μinches Thick
Body	Al ₂ O ₃ Ceramic
Pb Free	


Electrical Connections		
Connection		Terminals
Port 1	Input or Return	10
	Return or Input	1
Port 2	Output or Return	5
	Return or Output	6
Ground		All others
Single Ended Operation		Return is ground
Differential Operation		Return is hot



456.00 MHz

SAW Filter

Tape and Reel Specifications



"B "		Quantity Per Reel
Inches	millimeters	
7	178	500
13	330	2000

COMPONENT ORIENTATION and DIMENSIONS

Carrier Tape Dimensions		Tolerance
Ao	5.5 mm	± 0.1mm
Bo	7.5 mm	± 0.1mm
Ko	2.0 mm	± 0.1mm
Pitch	8.0 mm	± 0.1mm
W	16.0 mm	± 0.2mm

