

Tyco/Electronics**Raychem Circuit Protection**

308 Constitution Drive
Menlo Park, CA 94025
800-227-4856
FAX 800-227-4866

Polyswitch® **PTC Devices**

Overcurrent Protection Device

PRODUCT: RHE650

DOCUMENT: SCD 24414

PCN: 715725

REV LETTER: C

REV DATE: OCTOBER 8, 2001

PAGE NO.: 1 OF 1

Specification Status: RELEASED

Electrical Rating

Voltage: 16V MAX

Current: 100A MAX



Insulating Material:

Cured, Flame Retarded Epoxy Polymer
meets UL94 V-0 Requirements

Lead Material:

20 AWG Tin/Lead Plated Copper
(0.8 mm [0.032] nom. Diameter)

Marking:

 Raychem Logo and Voltage
 H6.5 Part Identification
 Lot Identification (can be on back)




TABLE I. DIMENSIONS:

	A		B		C		D		E		F
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	TYP
mm:	--	12.7	--	22.2	4.3	5.8	7.6	--	--	3.0	1.2
in*:	--	(0.50)	--	(0.88)	(0.17)	(0.23)	(0.30)	--	--	(0.12)	(0.05)

*Rounded off approximation

TABLE II. PERFORMANCE RATINGS:

I HOLD	CURRENT RATINGS		TIME TO TRIP	RESISTANCE VALUES		TRIPPED-STATE POWER DISSIPATION
AMPS 25°C HOLD	AMPS AT 25°C HOLD	TRIP	SECONDS AT 25°C, 32.5 A MAX	OHMS AT 25°C MIN	OHMS AT 25°C MAX	WATTS AT 25°C, 16V TYP
6.5	6.5	12.0	5.5	0.011	0.026	4.3

Recognitions:

Reference Documents:

Precedence:

Effectivity:

CAUTION:

UL, TUV, CSA recognized.

PS300

This specification takes precedence over documents referenced herein.

Reference documents shall be the issue in effect on the date of invitation for bid.

Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

