


177-619

April 1983

XB2-B

control and signalling units Ø22

175 451 to 475
178-501 → 509



Contents

General characteristics

General	2
Environment, contact block characteristics	3

Control units

Adaptable sub-assemblies	Operating heads for pushbuttons	4
	Operating heads for selector switches	5
	Double-headed pushbutton operators	6
	Double-headed pushbutton operators with pilot light	7
	Body/contact assemblies	8
	Supplementary contact blocks	8
Complete units	Mechanical overload resets	9

Signalling units

Adaptable sub-assemblies	Bodies and lenses for pilot lights	10
	Body/contact assemblies	11
	Operating heads for pilot lights	12
	Operating heads for illuminated selector switches	12
	Operating heads for "push to test" pilot lights	12

Accessories and spare parts

Bulbs, blanking plugs, tools	13
------------------------------	----

Legends

Legend plates for mounting between operating head and panel	13
ISO legends for mounting within operating heads	14, 15

Small joystick controllers

Complete units	2 and 4 position controllers	16
	Legends	16

Dimensions

Control and signalling units	17
Double-headed pushbutton operators	18
Small joystick controllers	19

Telemecanique in Great Britain



General characteristics

of control and signalling units XB2-B

Ø22.2(fixing)

General

This range of Ø22.2 pushbuttons, selector switches, pilot lights, illuminated pushbuttons, illuminated selector switches and small joystick controllers is designed to meet the requirements of an international market.

Aesthetic

Shape and colours.
Metal bezel, nickel plated and chromed.
Alternatively, metal bezel, matt black anodised.

Ergonomic design

Circular operating surface area greater than that of a Ø30.5mm control unit.

Robust

All the parts whose mechanical function is of prime importance are made of zinc alloy. Insulating parts are made of polyamide reinforced with glass fibre.

Safe

- Fixing method unaffected by excessive vibration, unit will not rotate.
- Positive contact opening.
- Very good flame resistance (class VO in accordance to UL94).
- Protection against electrical shock (unit earthed).

Speed and simplicity of fixing

A screwdriver is all that is required.

Operating heads

The operating heads are functionally interchangeable on the different types of body/contact assemblies.

Body/contact assemblies

For pushbuttons and selector switches:
1-6 contact blocks (N/O or N/C), except for push-pull mushroom heads which are 4 maximum.

For pilot lights, illuminated pushbuttons and illuminated selector switches:
Bodies for direct supply, direct supply through resistor or via integral transformer.

Supply voltage: 6-600V, according to body type.

Bulb: incandescent with type BA9s base.

1 or 2 contacts (N/O or N/C) for illuminated pushbuttons and illuminated selector switches.

The same contact blocks are used throughout the range.
They are slow break and self wiping. Contact tips are made of nickel-silver and the moving bridge of copper. Contact blocks are interchangeable and may be stacked on without additional mounting components. They are protected against the penetration of small objects during assembly and wiring.
Gold flashed contacts are also available.

Fixing

XB2-B manual pilot devices can be fixed in any position on panels of thickness 1 to 6mm.



The operating heads lock on to the base unit using a 1/8th turn bayonet fixing which makes for a simple and fast assembly.

Finally, the complete assembly is locked in to position on the mounting plate by two pointed screws Ø4mm, tightened from the rear. These screws also ensure the earthing of the unit.

Small joystick controllers

- Type XD2-P (compact, contacts non interchangeable).
Fixing centres 30 x 85mm (2 position) or 85 x 85mm (4 position).
2 or 4 position, with or without spring return to the zero position.
1 N/O contact per position.

- Type XD2-G
Fixing centres 90 x 90mm (2 and 4 position).
2 or 4 position, with or without spring return.
1 N/O contact per position.
Additional features:
-variable composition to 2, 3 or 4 position.
-controlling 1, 2 or 4 contacts in each position.
-1 or 2 notches per position, stay-put or spring return.
Details on request.



Environment

Conformity to standards	IEC 337-1, IEC 337-2, NFC 63-140, ASE 0119, ASE 1003, BS 4794, VDE 0660 part 2, UL 506, UL 508, CSA C22-2 No. 14, CSA C22-2 No. 66.
Approvals	Demko, Semko, Nemko, Elektriska Inspektoratet, GL Standard version: CSA 300V (AC) heavy duty, (DC) standard duty; Bureau Veritas; ASE; UL (listed) 300V (AC) heavy duty, (DC) standard duty.
Protective treatment	Standard version: "All climates."
Ambient temperature	Operating: -25 to +70°C. Storage: -40 to +70°C.
Altitude	<3000m
Operating position	All positions.
Resistance to vibration	Ø60mm mushroom head: 8g. Other pushbuttons: 15g. Small joystick controllers: 5g. (from 40 to 500Hz) in accordance with IEC 68-2-6.
Resistance to shock	Pushbuttons: 70g. Mushroom head pushbuttons: 15g. Double headed pushbuttons: 50g. Selector switches: 200g. In accordance with IEC 68-2-6.
Protection against electrical shock	Class 1, in accordance with IEC 536 and NF C20-030.
Degree of protection in accordance with IEC 529 and NF C20-010	IP40: basic double-headed pushbutton. IP65: flush and projecting, illuminated and non-illuminated pushbuttons (mounted). IP66: booted and mushroom head pushbuttons, selector switches, pilot lights, and small joystick controllers (mounted).
Mechanical life	Spring return pushbuttons, selector switches and small joystick controllers: 1 million operations. Latching mushroom head pushbuttons: 300,000 operations.

Contact block characteristics

Nominal thermal current	10A in accordance with IEC 337-1, NF C63-140, UL 508, CSA C22-2 No. 14, VDE 0660.
Nominal insulation voltage	500V in accordance with IEC 158-1, NF C20-040, VDE 0110. 300V in accordance with UL 508, CSA C22-2 No. 14.
Insulation category	Group C in accordance with NF C20-040 and VDE 0110.
Contact operation	Slow break N/O or N/C.
Contact resistance (between terminals)	<25mΩ: Standard <14mΩ: Gold flashed
Operating force	Flush and projecting pushbuttons -with 1N/O contact: 10N -with 1N/C contact: 8N. Additional contacts -N/O: +5N -N/C: +3N.
Terminal referencing	According to CENELEC EN 50013. Numbers indicating the function are marked on the contact block, either: 1-2 for a N/C contact or a 3-4 for a N/O contact. The contact order number is marked on the diecast base, i.e.: First row of contacts: 1 for left hand contact block, 2 for right hand contact block. Second row of contacts: 3 for left hand contact block, 4 for right hand contact block.
Short circuit protection	10A cartridge fuses, g1 or N in accordance with IEC 337-1B.

Making and breaking capacities in accordance with IEC 337-1 and VDE 0660 part 2

Voltage V	AC ~50-60Hz Power broken in kVA For 50 operations							DC --- Power broken in W For 20 operations					
	12	24	48	127	220	380	500	12	24	48	110	220	440
Pushbuttons XB2-B and Small joystick controllers XD2-GA	0.8	1.5	4.4	9.6	15.6	24	32	1000	600	870	240	190	130
Small joystick controllers XD2-PA	0.8	1.5	4	9	15	21	24	650	390	260	165	115	85

Rated power in accordance with IEC 337-1
Duty categories AC11 and DC11

Voltage V	AC ~50-60Hz Power broken in VA							DC --- Power broken in W					
	12	24	48	127	220	380	500	12	24	48	110	220	440
Pushbuttons XB2-B and Small joystick controllers XD2-GA	100	200	400	650	700	600	500	95	65	48	40	30	25
Small joystick controllers XD2-PA	120	240	480	1000	1200	1500	1500	120	240	300	170	110	70
Small joystick controllers XD2-PA	100	200	400	550	600	500	400	58	40	30	23	20	15
	120	240	475	850	1100	1200	1200	120	240	135	110	70	45

For 1 million operations
Operating frequency: 3600 ops./hour
Load factor: 0.5

Secure and positive cable clamp terminals. Capacity: minimum 1 x 0.5mm² maximum 1 x 2.5mm² without cable and

ZB2-B

Control units Ø22.2 (fixing)

circular head, chromium plated metal bezel

Bodies : see page 8
Legends : see pages 13 to 15
Dimensions: see page 17

Operating heads for pushbuttons

Description	Colour	Reference	For ISO legends	Weight kg
Flush	White	ZB2-BA1	-	0.030
	Black	ZB2-BA2	-	0.030
	Green	ZB2-BA3	ZB2-BA38	0.030
	Red	ZB2-BA4	ZB2-BA48	0.030
	Yellow	ZB2-BA5	ZB2-BA58	0.030
	Blue	ZB2-BA6	ZB2-BA68	0.030
	Clear	ZB2-BA7	ZB2-BA78	0.030
Projecting	White	ZB2-BL1	-	0.030
	Black	ZB2-BL2	-	0.030
	Green	ZB2-BL3	ZB2-BW13	0.030
	Red	ZB2-BL4	ZB2-BW14	0.030
	Yellow	ZB2-BL5	ZB2-BW15	0.030
	Blue	ZB2-BL6	ZB2-BW16	0.030
	Clear	-	ZB2-BW17	0.030
Projecting Push and push to release	Black	ZB2-BH2	-	0.032
	Green	-	ZB2-BH3	0.032
	Red	-	ZB2-BH4	0.032
	Yellow	-	ZB2-BH5	0.032
	Blue	-	ZB2-BH6	0.032
	Clear	-	ZB2-BH7	0.032
	Black	ZB2-BP2	-	0.030
Booted	Green	ZB2-BP3	ZB2-BP38	0.030
	Red	ZB2-BP4	ZB2-BP48	0.030
	Yellow	ZB2-BP5	ZB2-BP58	0.030
	Blue	ZB2-BP6	ZB2-BP68	0.030
	Clear	-	ZB2-BP78	0.030

Mushroom operating heads

Spring return	Ø40mm	Black	ZB2-BC2	0.045
		Green	ZB2-BC3	0.045
		Red	ZB2-BC4	0.045
		Yellow	ZB2-BC5	0.045
		Blue	ZB2-BC6	0.045
	Ø60mm	Black	ZB2-BR2	0.055
		Green	ZB2-BR3	0.055
		Red	ZB2-BR4	0.055
		Yellow	ZB2-BR5	0.055
Push-pull stay put	Ø40mm	Black	ZB2-BT2	0.075
		Red	ZB2-BT4	0.075
	Ø60mm	Black	ZB2-BX2	0.080
		Red	ZB2-BX4	0.080
Latching turn to release	Ø30mm	Red	ZB2-BS44	0.045
	Ø40mm	Black	ZB2-BS52	0.055
		Red	ZB2-BS54	0.055
		Yellow	ZB2-BS55	0.055
Latching key release (Ronis key No. 455)	Ø60mm	Red	ZB2-BS64	0.065
	Ø30mm	Red	ZB2-BS74	0.080
	Ø40mm	Red	ZB2-BS14	0.090
	Ø60mm	Red	ZB2-BS24	0.120


✦ Other versions

For colours other than those mentioned above...
For other key numbers...
Details on request.

When ordering



an operating head.
Please state the exact reference.
Example: ZB2-BA2




ZB2-BA•




ZB2-BL•



ZB2-BP•



ZB2-BC•



ZB2-BX•



ZB2-BS54



ZB2-BS24

Control units Ø22.2 (fixing)

ZB2-B

circular head, chromium plated metal bezel

Bodies : see page 8
Legends : see page 13
Dimensions: see page 17

Operating heads for selector switches



ZB2-BD•

Description			Reference	Weight kg
Standard handle (1)	2 position	stay put	ZB2-BD2	0.040
		spring return from right to left	ZB2-BD4	0.040
	3 position	stay put	ZB2-BD3	0.040
		spring return to centre	ZB2-BD5	0.040
		stay put on left, spring return from right to centre	ZB2-BD8	0.040
		stay put on right, spring return from left to centre	ZB2-BD7	0.040
	2 position	stay put	ZB2-BJ2	0.040
		spring return from right to left	ZB2-BJ4	0.040
Long handle (1)	3 position	stay put	ZB2-BJ3	0.040
		spring return to centre	ZB2-BJ5	0.040
		stay put on left, spring return from right to centre	ZB2-BJ8	0.040
		stay put on right, spring return from left to centre	ZB2-BJ7	0.040
		stay put on left, spring return from right to centre	ZB2-BJ8	0.040
		stay put on right, spring return from left to centre	ZB2-BJ7	0.040



ZB2-BJ•

(1) Standard handle black
For white handle add 01 to reference. Example: ZB2-BD201
For red handle add 04 to reference. Example: ZB2-BD204

Operating heads for key switches (Ronis key No. 455)



ZB2-BG•

Description		Key withdrawal	Reference	Weight
2 position	stay put	left hand position	ZB2-BG2	0.070
		left and right hand positions	ZB2-BG4	0.070
	spring return from right to left	left hand position	ZB2-BG6	0.070
		right hand position	ZB2-BG9	0.070
3 position	stay put	all positions	ZB2-BG0	0.070
		centre position	ZB2-BG3	0.070
		left and right hand positions	ZB2-BG5	0.070
		right hand position	ZB2-BG09	0.070
	spring return to centre	centre position	ZB2-BG7	0.070
	stay put on right, spring return from left to centre	right hand position	ZB2-BG1	0.070

+ Other versions

Operating heads are available with mechanical functions other than those shown above.
Other key numbers. Details on request.

When ordering



an operating head.
Please state the exact reference.
Example: ZB2-BD2

ZB2-B

Control units Ø22.2 (fixing)

Double-headed, rectangular pushbutton operators
with chromium plated metal bezel

Bodies : see page 8
Dimensions: see page 18

Double-headed pushbutton operators IP40

Description	Colour of operators	Marking	Reference	Weight kg
2 Flush	Black Red	Unmarked	ZB2-BA8124	0.048
		Marked "I" "O"	ZB2-BA8224	0.048
	Green Red	Unmarked	ZB2-BA8134	0.048
		Marked "I" "O"	ZB2-BA8234	0.048
1 Flush 1 Projecting	Black Red	Unmarked	ZB2-BL8324	0.048
		Marked "I" "O"	ZB2-BL8424	0.048
	Green Red	Unmarked	ZB2-BL8334	0.048
		Marked "I" "O"	ZB2-BL8434	0.048




ZB2-BA8224




ZB2-BL8334

Double-headed pushbutton operators IP65

Description	Colour of operators	Marking	Reference	Weight kg
2 Flush	Black Red	Unmarked	ZB2-BA9124	0.048
		Marked "I" "O"	ZB2-BA9224	0.048
	Green Red	Unmarked	ZB2-BA9134	0.048
		Marked "I" "O"	ZB2-BA9234	0.048
1 Flush 1 Projecting	Black Red	Unmarked	ZB2-BL9324	0.048
		Marked "I" "O"	ZB2-BL9424	0.048
	Green Red	Unmarked	ZB2-BL9334	0.048
		Marked "I" "O"	ZB2-BL9434	0.048



ZB2-BA9234



ZB2-BL9324

When ordering




a double-headed pushbutton operator.
Please state the exact reference.
Example: ZB2-BA8124

Control units Ø22.2 (fixing)

ZB2-B

Double-headed, rectangular pushbutton operators
with chromium plated metal bezel

Bodies : see page 11
Dimensions: see page 18



ZB2-BW81254

Operating heads for pushbuttons, with pilot light incorporating yellow lens

Description	Colour of operators	Marking	Reference	Weight kg
2 Flush 1 Pilot light IP40*	Black Red	Unmarked	ZB2-BW81254	0.043
		Marked "I" "O"	ZB2-BW82254	0.043
	Green Red	Unmarked	ZB2-BW81354	0.043
		Marked "I" "O"	ZB2-BW82354	0.043
1 Flush 1 Projecting 1 Pilot light IP40*	Black Red	Unmarked	ZB2-BW83254	0.043
		Marked "I" "O"	ZB2-BW84254	0.043
	Green Red	Unmarked	ZB2-BW83354	0.043
		Marked "I" "O"	ZB2-BW84354	0.043



ZB2-BW84204

Operating heads for pushbuttons, with pilot light without lens


Description	Colour of operators	Marking	Reference	Weight kg
2 Flush 1 Pilot light IP40*	Black Red	Unmarked	ZB2-BW81204	0.042
		Marked "I" "O"	ZB2-BW82204	0.042
	Green Red	Unmarked	ZB2-BW81304	0.042
		Marked "I" "O"	ZB2-BW82304	0.042
1 Flush 1 Projecting 1 Pilot light IP40*	Black Red	Unmarked	ZB2-BW83204	0.042
		Marked "I" "O"	ZB2-BW84204	0.042
	Green	Unmarked	ZB2-BW83304	0.042
		Marked "I" "O"	ZB2-BW84304	0.042

Lenses for pilot lights




Sold in lots of 10

	Colour	Reference	Weight kg
	Green	ZB2-BW903	0.001
	Red	ZB2-BW904	0.001
	Yellow	ZB2-BW905	0.001
	Blue	ZB2-BW906	0.001
	Clear	ZB2-BW907	0.001



ZB2-BW90



ZB2-BW008

Sealing boot

	Silicone clear	ZB2-BW008	0.004
--	----------------	-----------	-------

*Increased to IP66 by addition of boot ZB2-BW008.

When ordering



a double-headed pushbutton operator.
Please state the exact reference. Example: ZB2-BW81354
a lens and/or a sealing boot.

ZB2-B

Control units Ø22.2 (fixing)

Body/contact assemblies

For use with operating heads shown on pages 4, 5 and 6

Dimensions: see page 17

Complete bodies; screw and captive cable clamp connections



ZB2-BZ10•

Description	Application	Scheme	Reference	Weight kg
With one contact block	Pushbuttons and 2 position selector switches	N/O 	ZB2-BZ101	0.040
		N/C 	ZB2-BZ102	0.040
With two contact blocks	2-way rectangular pushbuttons, pushbuttons and 2 or 3 position selector switches	N/O+N/O 	ZB2-BZ103	0.055
		N/C+N/C 	ZB2-BZ104	0.055
		N/O+N/C 	ZB2-BZ105	0.055
		N/O+N/C 	ZB2-BZ106	0.055
		N/O+N/O 	ZB2-BZ107	0.055
		Make before break 		

Supplementary contact blocks



ZB2-BE10•

Connections	Application	Type	Reference	Weight kg
Screw and captive cable clamp	For converting body/contact assemblies to 3, 4, 5 or 6 contacts maximum or replacing 1st or 2nd contact blocks	N/O Standard	ZB2-BE101	0.015
		Early make	ZB2-BE201	0.015
		N/C Standard	ZB2-BE102	0.015
		Late break	ZB2-BE202	0.015
	For low power switching (<20V, <50mA) gold flashed contacts	N/O	ZB2-BE1016	0.015
		N/C	ZB2-BE1026	0.015

→ Other versions

Body/contact assemblies fitted with "faston" connectors (6.3)
(conforming to NF C20-120).
Details on request.

When ordering



a complete body/contact assembly.
Please state the exact reference. Example: ZB2-BZ101
a supplementary contact block.


Mechanical overload resets Ø22.2 (fixing)

XB2-B


circular head, chromium plated metal bezel

Complete units


Legends: see page 13



XB2-BA8..



XB2-BA9..
30 to 82mm



XB2-BA9..
80 to 257mm

Description	Adjustable length	Colour	Reference	Weight kg
Flush pushbutton 10mm travel For mounting on plate 1 to 3mm thickness Fixing: secured by nut from rear	6 to 16mm	Black	XB2-BA821	0.030
		Red	XB2-BA841	0.030
		Blue	XB2-BA861	0.030
	16 to 26mm	Black	XB2-BA822	0.035
		Red	XB2-BA842	0.035
		Blue	XB2-BA862	0.035
Flush pushbutton 14mm travel For mounting on plate 1 to 6mm thickness Fixing: secured by pointed screws from rear	30 to 57mm	Black	XB2-BA921	0.077
		Red	XB2-BA941	0.077
		Blue	XB2-BA961	0.077
	55 to 82mm	Black	XB2-BA922	0.080
		Red	XB2-BA942	0.080
		Blue	XB2-BA962	0.080
	80 to 107mm	Black	XB2-BA923	0.085
		Red	XB2-BA943	0.085
		Blue	XB2-BA963	0.085
	105 to 132mm	Black	XB2-BA924	0.090
		Red	XB2-BA944	0.090
		Blue	XB2-BA964	0.090
	130 to 157mm	Black	XB2-BA925	0.095
		Red	XB2-BA945	0.095
		Blue	XB2-BA965	0.095
	155 to 182mm	Black	XB2-BA926	0.100
		Red	XB2-BA946	0.100
		Blue	XB2-BA966	0.100
	180 to 207mm	Black	XB2-BA927	0.105
		Red	XB2-BA947	0.105
		Blue	XB2-BA967	0.105
	205 to 232mm	Black	XB2-BA928	0.110
		Red	XB2-BA948	0.110
		Blue	XB2-BA968	0.110
	230 to 257mm	Black	XB2-BA929	0.115
		Red	XB2-BA949	0.115
		Blue	XB2-BA969	0.115

When ordering



a complete unit.
Please state the exact reference.
Example: XB2-BA822

ZB2-B

Signalling units Ø22.2 (fixing)


Bodies and lenses for pilot lights

Legends : see pages 13 to 15
Dimensions: see page 17

Heads (lens + bezel)



ZB2-BV0●




ZB2-BV0●3




ZB2-BV6



ZB2-BV7



ZB2-BV●●



ZB2-BV1●●

	Colour	Reference	Weight kg
Standard lenses suitable for use with ISO legends	Green	ZB2-BV03	0.025
	Red	ZB2-BV04	0.025
	Yellow	ZB2-BV05	0.025
	Blue	ZB2-BV06	0.025
	Clear	ZB2-BV07	0.025
High contrast lenses	Green	ZB2-BV033	0.025
	Red	ZB2-BV043	0.025
	Yellow	ZB2-BV053	0.025
	Blue	ZB2-BV063	0.025
	Clear	ZB2-BV073	0.025


Complete body with screw and captive cable clamp connections

Supply	Typical scheme	Maximum supply voltage	Reference	Weight kg
Direct bulb not supplied to order: see page 13	X1 ⊗ X2	≤ 130V	ZB2-BV6	0.045
Direct through resistor bulb supplied type BA9s, 130V	⊗-X1 X2	220/240V	ZB2-BV7	0.055
Via integral transformer 1.2VA bulb supplied type BA9s, 6V	X1 ⊗ X2	24V:50Hz	ZB2-BV1	0.110
		48V:50Hz	ZB2-BV2	0.110
		110V:50Hz	ZB2-BV3	0.110
		220/240V:50Hz	ZB2-BV4	0.110
		380V:50Hz	ZB2-BV5	0.110
		415V:50Hz	ZB2-BV93	0.110
		440/480:60Hz	ZB2-BV95	0.110
		500V:50Hz	ZB2-BV8	0.110
		500/600:60Hz	ZB2-BV98	0.110

Flashing pilot light body with screw and captive cable clamp connections

Description		Supply voltage	Reference	Weight kg
4 terminal output 3 states, off, flashing light and steady light	Bulb supplied type BA9s, 24V	24V:AC	ZB2-BV181	0.070
		24V:DC	ZB2-BV191	0.070
	Bulb supplied type BA9s, 48V	48V:AC	ZB2-BV183	0.070
		48V:DC	ZB2-BV193	0.070
	Bulb supplied type BA9s, 130V	110/127:AC	ZB2-BV184	0.070
		220/240:AC	ZB2-BV185	0.070

Schemes

DC: U → - X1
+ X2

By the addition of up to 2 ZB2-BE10● contact blocks, these bodies may be used for flashing illuminated pushbutton and illuminated selector switch applications.

When ordering

a head, a complete body or a flashing pilot light body.
Please state the exact reference.
Examples: ZB2-BV03, ZB2-BV6, ZB2-BV181.

Signalling units Ø22.2 (fixing)


ZB2-B

circular head, chromium plated metal bezel


Body/contact assemblies. For use with operator heads shown on pages 4 (ZB2-BH3 to 7 only), 7 and 12

Bulb information: see page 13
Dimensions : see page 17

Complete bodies; screw and captive cable clamp connections



ZB2-BW06•



ZB2-BW07•



ZB2-BW0•••

Supply	Typical scheme	Maximum supply voltage	Contact arrangement	Reference	Weight kg
Direct		≤130V	N/O	ZB2-BW061	0.060
			N/C	ZB2-BW062	0.060
			N/O+N/O	ZB2-BW063	0.070
			N/C+N/C	ZB2-BW064	0.070
			N/O+N/C	ZB2-BW065	0.070
Direct through resistor bulb supplied type BA9s, 130V		220/240	N/O	ZB2-BW071	0.065
			N/C	ZB2-BW072	0.065
			N/O+N/O	ZB2-BW073	0.080
			N/C+N/C	ZB2-BW074	0.080
			N/O+N/C	ZB2-BW075	0.080
Via integral transformer 1.2VA bulb supplied type BA9s, 6V		24V:50Hz	N/O	ZB2-BW011	0.120
			N/C	ZB2-BW012	0.120
			N/O+N/O	ZB2-BW013	0.135
			N/C+N/C	ZB2-BW014	0.135
			N/O+N/C	ZB2-BW015	0.135
		48V:50Hz	N/O	ZB2-BW021	0.120
			N/C	ZB2-BW022	0.120
			N/O+N/O	ZB2-BW023	0.135
			N/C+N/C	ZB2-BW024	0.135
			N/O+N/C	ZB2-BW025	0.135
		110V:50Hz	N/O	ZB2-BW031	0.120
			N/C	ZB2-BW032	0.120
			N/O+N/O	ZB2-BW033	0.135
			N/C+N/C	ZB2-BW034	0.135
			N/O+N/C	ZB2-BW035	0.135
		220/240V:50Hz	N/O	ZB2-BW041	0.120
			N/C	ZB2-BW042	0.120
			N/O+N/O	ZB2-BW043	0.135
			N/C+N/C	ZB2-BW044	0.135
			N/O+N/C	ZB2-BW045	0.135
		380V:50Hz	N/O	ZB2-BW051	0.120
			N/C	ZB2-BW052	0.120
			N/O+N/O	ZB2-BW053	0.135
			N/C+N/C	ZB2-BW054	0.135
			N/O+N/C	ZB2-BW055	0.135
		415V:50Hz	N/O	ZB2-BW0931	0.120
			N/C	ZB2-BW0932	0.120
			N/O+N/O	ZB2-BW0933	0.135
			N/C+N/C	ZB2-BW0934	0.135
			N/O+N/C	ZB2-BW0935	0.135
		440/480V:50Hz	N/O	ZB2-BW0951	0.120
			N/C	ZB2-BW0952	0.120
			N/O+N/O	ZB2-BW0953	0.135
			N/C+N/C	ZB2-BW0954	0.135
			N/O+N/C	ZB2-BW0955	0.135
		500V:50Hz	N/O	ZB2-BW081	0.120
			N/C	ZB2-BW082	0.120
			N/O+N/O	ZB2-BW083	0.135
			N/C+N/C	ZB2-BW084	0.135
			N/O+N/C	ZB2-BW085	0.135
		500/600V:60Hz	N/O	ZB2-BW0981	0.120
			N/C	ZB2-BW0982	0.120
			N/O+N/O	ZB2-BW0983	0.135
			N/C+N/C	ZB2-BW0984	0.135
			N/O+N/C	ZB2-BW0985	0.135

Assemble units of your choice

by using our wide range of adaptable sub-assemblies.
• Bodies and lenses for pilot lights (see previous page).

When ordering



a complete body.
Please state the exact reference. Example: ZB2-BW061
Add the reference of the head, bulb and legend (if required).

ZB2-B

Signalling units Ø22.2 (fixing)

circular head, chromium plated metal bezel



ZB2-BW3•



ZB2-BW1•



ZB2-BK•••



ZB2-BV0••

Operating heads (bezel + lens), suitable for use with ISO legends or separate legend plates

Type of operator	Colour	Reference	Weight kg
Flush	Green	ZB2-BW33	0.025
	Red	ZB2-BW34	0.025
	Yellow	ZB2-BW35	0.025
	Blue	ZB2-BW36	0.025
	Clear	ZB2-BW37	0.025
Projecting	Green	ZB2-BW13	0.030
	Red	ZB2-BW14	0.030
	Yellow	ZB2-BW15	0.030
	Blue	ZB2-BW16	0.030
	Clear	ZB2-BW17	0.030
Flush booted	Green	ZB2-BW53	0.030
	Red	ZB2-BW54	0.030
Mushroom head Spring return	Green	ZB2-BW43	0.030
	Red	ZB2-BW44	0.030
Mushroom head Push-pull stay put	Green	ZB2-BW63	0.030
	Red	ZB2-BW64	0.030

Operating heads for illuminated selector switches

Description		Colour	Reference	Weight kg
Standard handle 2 position	stay put	Green	ZB2-BK123	0.035
		Red	ZB2-BK124	0.035
		Yellow	ZB2-BK125	0.035
		Blue	ZB2-BK126	0.035
		Clear	ZB2-BK127	0.035
	spring return right to left	Green	ZB2-BK143	0.035
		Red	ZB2-BK144	0.035
		Yellow	ZB2-BK145	0.035
		Blue	ZB2-BK146	0.035
		Clear	ZB2-BK147	0.035
Standard handle 3 position	stay put	Green	ZB2-BK133	0.035
		Red	ZB2-BK134	0.035
		Yellow	ZB2-BK135	0.035
		Blue	ZB2-BK136	0.035
		Clear	ZB2-BK137	0.035
	spring return to centre	Green	ZB2-BK153	0.035
		Red	ZB2-BK154	0.035
		Yellow	ZB2-BK155	0.035
		Blue	ZB2-BK156	0.035
		Clear	ZB2-BK157	0.035
	stay put on left, spring return from right to centre	Green	ZB2-BK183	0.035
		Red	ZB2-BK184	0.035
		Yellow	ZB2-BK185	0.035
		Blue	ZB2-BK186	0.035
		Clear	ZB2-BK187	0.035
	stay put on right, spring return from left to centre	Green	ZB2-BK173	0.035
		Red	ZB2-BK174	0.035
		Yellow	ZB2-BK175	0.035
		Blue	ZB2-BK176	0.035
		Clear	ZB2-BK177	0.035

Operating heads for "push to test" pilot lights

Green	ZB2-BV031	0.030
Red	ZB2-BV041	0.030
Yellow	ZB2-BV051	0.030
Blue	ZB2-BV061	0.030
Clear	ZB2-BV071	0.030

When ordering



an operating head.

Please state the exact reference. Example: ZB2-BW63.

Add the reference of the body, bulb and the legend (if required).

Accessories and spare parts

ZB2-B

for XB2-B control and signalling units

Legend plates 30 x 40mm: Not suitable for use with double-headed pushbuttons

"Start" functions: white characters on black. "Stop" functions: white characters on red.

Text	Reference	Weight kg	Text	Reference	Weight kg
------	-----------	--------------	------	-----------	--------------

Without text

Red or black background	ZB2-BY2101	0.001	White or yellow background	ZB2-BY4101	0.001
-------------------------	------------	-------	----------------------------	------------	-------

Standard texts

For pushbuttons

Start	ZB2-BY2303	0.001	Stop	ZB2-BY2304	0.001
Forward	ZB2-BY2305	0.001	Reverse	ZB2-BY2306	0.001
Up	ZB2-BY2307	0.001	Down	ZB2-BY2308	0.001
Right	ZB2-BY2309	0.001	Left	ZB2-BY2310	0.001
On	ZB2-BY2311	0.001	Off	ZB2-BY2312	0.001
Open	ZB2-BY2313	0.001	Close	ZB2-BY2314	0.001
Auto	ZB2-BY2115	0.001	Hand	ZB2-BY2116	0.001
Reset	ZB2-BY2323	0.001	Emergency stop	ZB2-BY2330	0.001
Power	ZB2-BY2326	0.001	Inch	ZB2-BY2321	0.001
Slow	ZB2-BY2337	0.001	Fast	ZB2-BY2328	0.001

For selector switches

Auto-Hand	ZB2-BY2364	0.001	Auto-O-Hand	ZB2-BY2385	0.001
-----------	------------	-------	-------------	------------	-------

Universal symbols

For pushbuttons

O	ZB2-BY2146	0.001	O-I	ZB2-BY2178	0.001
I	ZB2-BY2147	0.001	I-II	ZB2-BY2179	0.001
II	ZB2-BY2148	0.001	I-O-II	ZB2-BY2186	0.001
III	ZB2-BY2149	0.001			

For selector switches

Special texts. Please state the exact wording required when ordering (2 lines max. 11 charas./line).

Black with white charas.	ZB2-BY2002	0.001	Yellow with black charas.	ZB2-BY4005	0.001
Red with white charas.	ZB2-BY2004	0.001	For a number of legends with the same text,		
White with black charas.	ZB2-BY4001	0.001	please consult your regional sales office.		

Large legend plates for use with mushroom heads

Round, Ø60mm. Text: - "Emergency stop", yellow with black charas.	ZB2-BY9330	0.006
Round, Ø90mm. Text: - "Emergency stop", yellow with black charas.	ZB2-BY8330	0.008
Rectangular, 45 x 67.5. Without text, red background.	ZB2-BY5101	0.006

Bulbs

For use in direct supply units: BA9s base fitting. Incandescent bulbs; V ≤ 130V, maximum power 2.6W. Ø11mm maximum, length 28mm maximum.



Sold in lots of 10.

Incandescent bulbs

Voltage	Power	Unit Reference	Weight kg
6V	1.5W	DL1-CB006	0.002
12V	2.6W	DL1-CE012	0.002
24V	2.6W	DL1-CE024	0.002
48V	2.6W	DL1-CE048	0.002
130V	2.6W	DL1-CE130	0.002

Blanking plug for Ø22.2mm hole (sold singly)


Black insulating material	ZB2-SZ3	0.005
Grey insulating material	ZB2-SZ4	0.005

Tools (sold singly)


Bulb extractor for use with types BA9s	XB-F-X13	0.025
Lens tool for ISO legend operators	ZB2-BZ8	0.006
Padlockable guard for flush pushbutton operators	ZB2-BZ6	0.090

♦ Other versions

Legend plates with texts in other languages.
Please consult your regional sales office.



ZB2-BY...



ZB2-BY...330



DL1-C...



ZB2-SZ3

When ordering



a standard legend plate.

Please state the exact reference. Example: ZB2-BY2304


a special legend plate.

Please state the exact reference of the legend plate and the text required

For mounting within the operating heads


- flush pushbuttons
- projecting pushbuttons
- booted pushbuttons
- illuminated pushbuttons
- push to test pilot lights
- and pilot lights

Without text



ZB2-BY1101

Universal symbols




ZB2-BY1146

ZB2-BY1147

ZB2-BY1148

ZB2-BY1149

English texts



ZB2-BY1115

ZB2-BY1316

ZB2-BY1312

ZB2-BY1311

ZB2-BY1303

ZB2-BY1304

Symbols for motions and speeds

	Direction of continuous linear motion to the right		Direction of continuous linear motion to the left		Direction of continuous upward linear motion		Direction of continuous downward linear motion		Linear motion in two directions Left-Right
ZB2-BY1912		ZB2-BY1914		ZB2-BY1913		ZB2-BY1915		ZB2-BY1932	
	Linear motion in two directions Up-Down		Interrupted linear motion		Limited linear motion		Limited linear movement and return		Continuous oscillating linear motion
ZB2-BY1931		ZB2-BY1901		ZB2-BY1902		ZB2-BY1903		ZB2-BY1904	
	Continuous clockwise rotation		Continuous anti-clockwise rotation		Rotation in two directions		Interrupted clockwise rotation		Interrupted anti-clockwise rotation
ZB2-BY1905		ZB2-BY1906		ZB2-BY1907		ZB2-BY1908		ZB2-BY1909	
	Limited clockwise rotation		Limited anti-clockwise rotation		Limited rotary movement and return		Continuous oscillating movement		Direction of spindle rotation
ZB2-BY1910		ZB2-BY1911		ZB2-BY1916		ZB2-BY1917		ZB2-BY1918	
	One revolution irrespective of direction		Number of revolutions per minute		Feed		Feed, mm/revolution		Feed, mm/minute
ZB2-BY1919		ZB2-BY1920		ZB2-BY1921		ZB2-BY1922		ZB2-BY1923	
	Reduced feed		Rapid feed		Normal feed		Longitudinal feed		Transverse feed
ZB2-BY1924		ZB2-BY1925		ZB2-BY1926		ZB2-BY1927		ZB2-BY1928	

Symbols for motions and speeds (continued)

	Vertical feed		Rapid traverse		Threading		Increase of a value		Decrease of a value
ZB2-BY1929		ZB2-BY1930		ZB2-BY1933		ZB2-BY1934		ZB2-BY1935	
	Speed of planing cut		Speed of turning cut		Speed of drilling cut		Speed of milling cut		Conventional milling
ZB2-BY1936		ZB2-BY1937		ZB2-BY1938		ZB2-BY1939		ZB2-BY1940	
	Climb milling								
ZB2-BY1941									

Element symbols

	Electric motor		Rectangular work table or slide element		Round work table or rotating element		Turning spindle		Drilling spindle
ZB2-BY1942		ZB2-BY1943		ZB2-BY1944		ZB2-BY1945		ZB2-BY1946	
	Milling spindle		Grinding spindle		Pump (general symbol)		Coolant pump		Lubricant pump
ZB2-BY1947		ZB2-BY1948		ZB2-BY1949		ZB2-BY1950		ZB2-BY1951	
	Hydraulic pump		Hydraulic motor		Tracer				
ZB2-BY1952		ZB2-BY1953		ZB2-BY1954					

Operational symbols

	Continuous regulation		Adjustable		Lock or tighten		Lock or tighten		Unlock, unclamp
ZB2-BY1955		ZB2-BY1956		ZB2-BY1957		ZB2-BY1958		ZB2-BY1959	
	Unlock, unclamp		Brake on		Brake off		Automatic (or semi-automatic) cycle		Hand control
ZB2-BY1960		ZB2-BY1961		ZB2-BY1962		ZB2-BY1963		ZB2-BY1964	
	ON		OFF		ON-OFF		ON, whilst pushbutton depressed		Engaging
ZB2-BY1965		ZB2-BY1966		ZB2-BY1967		ZB2-BY1968		ZB2-BY1969	
	Disengaging		Locknut closed		Locknut open				
ZB2-BY1970		ZB2-BY1971		ZB2-BY1972					

XD2


Small joystick controllers Ø 22.2 (fixing)


circular head, chromium plated metal bezel

Screw and captive cable clamp connections
(positions A, B, C, D are as viewed from the front of the unit)


Dimensions: see page 19
Schemes : see page 19




Complete units, type XD2-P (compact, contact blocks are not interchangeable)

Description		Reference	Weight kg
2 direction Fixing centres 30x85mm	A — o — B	Without spring return to the zero position	XD2-PA12 0.115
		With spring return to the zero position	XD2-PA22 0.115
4 direction Fixing centres 85x85mm		Without spring return to the zero position	XD2-PA14 0.145
		With spring return to the zero position	XD2-PA24 0.145



Complete units, type XD2-G

2 direction Fixing centres 90x90mm	A — o — B	2 notches with spring return to the zero position	XD2-GA8241 0.500
		2 notches: 1st notch stayput 2nd notch spring return to 1st notch	XD2-GA8251 0.500
4 direction Fixing centres 90x90mm		2 notches with spring return to the zero position	XD2-GA8441 0.555
		2 notches: 1st notch stayput 2nd notch spring return to 1st notch	XD2-GA8451 0.555



Accessories and spare parts

2 direction legend plates For XD2-PA: 30x48mm For XD2-GA: 40x64mm	Without text, black one	30x48	ZD2-GY2201	0.002
	side - red other	40x64	ZD2-GY5201	0.002
	With text*	30x48	ZD2-GY2002	0.002
	black background	40x64	ZD2-GY5002	0.002
	With text*	30x48	ZD2-GY2004	0.002
	red background	40x64	ZD2-GY5004	0.002
4 direction legend plates For XD2-PA: 48x48mm For XD2-GA: 64x64mm	Without text, black one	48x48	ZD2-GY4201	0.003
	side - red other	64x64	ZD2-GY6201	0.003
	With text*	48x48	ZD2-GY4002	0.003
	black background	64x64	ZD2-GY6002	0.003
	With text*	48x48	ZD2-GY4004	0.003
	red background	64x64	ZD2-GY6004	0.003

*State exact text required when ordering: 2 lines of 11 characters per line max.

Spare N/O contact blocks	For controllers XD2-PA XD2-GA	Not interchangeable ZB2-BE101	0.015
---------------------------------	----------------------------------	----------------------------------	-------

♦ Other versions

Variable composition XD2-GA controllers (1 or 2 notches per direction; 1 or 2 contacts per direction).
Contacts for low power switching.
Please consult your local sales office.



When ordering



a small joystick controller
Please state the exact reference. Example: XD2-PA24.
Add the reference of the legend plate and the text required.

Dimensions

of control and signalling units $\varnothing 22.2$ (fixing)




Dimensions


of double-headed pushbutton operators

References: see pages 6,7 and 11

Panel drillings
for double-headed pushbutton
operators, without pilot light




for double-headed pushbutton operators,
with pilot light without boot




Double-headed pushbutton operators without pilot light



ZB2-BZ10● (2)



ZB2-BA● (1)




XB2-BL●●
ZB2-BL● (1)




(1) Operating Head (2) Body/contact assembly

Double-headed pushbutton operators with pilot light



XB2-BW9●●● (direct)
ZB2-BW8●●●● (1)
ZB2-BW065 (2)



XB2-BW9●●● (with resistor)
ZB2-BW8●●●● (1)
ZB2-BW075 (2)



XB2-BW9●●● (with transformer)
ZB2-BW8●●●● (1)
ZB2-BW035, BW045, BW055 (2)




(1) Operating head (2) Body/contact assembly

Sealing boot

for double-headed pushbutton operators with pilot light (supplied fitted)


ZB2-BW008




Dimensions and schemes of small joystick controllers Ø22.2 (fixing)

References: see page 16


Panel drillings for controllers XD2-PA (2 direction)




XD2-PA (4 direction)



XD2-GA (2 and 4 direction)






Controllers XD2-PA••






*typical for each of the 4 directions


XD2-PA12 XD2-PA22



XD2-PA14 XD2-PA24







XD2-GA••







*typical for each of the 4 directions





XD2-GA8241








XD2-GA8251



XD2-GA8441



XD2-GA8451



Notes :








1 X B 2 B 1 2 4 2
FAMILY HEAD CONTACT

HEAD = ZB2-LB4













BODY } = ZB2-BZ102
+CONTACT }

ISO legends


















Symbols for motions and speeds (continued)

	Vertical feed		Rapid traverse		Threading		Increase of a value		Decrease of a value
ZB2-BY1929		ZB2-BY1930		ZB2-BY1933		ZB2-BY1934		ZB2-BY1935	
	Speed of planing cut		Speed of turning cut		Speed of drilling cut		Speed of milling cut		Conventional milling
ZB2-BY1936		ZB2-BY1937		ZB2-BY1938		ZB2-BY1939		ZB2-BY1940	
	Climb milling								
ZB2-BY1941									

Element symbols

	Electric motor		Rectangular work table or slide element		Round work table or rotating element		Turning spindle		Drilling spindle
ZB2-BY1942		ZB2-BY1943		ZB2-BY1944		ZB2-BY1945		ZB2-BY1946	
	Milling spindle		Grinding spindle		Pump (general symbol)		Coolant pump		Lubricant pump
ZB2-BY1947		ZB2-BY1948		ZB2-BY1949		ZB2-BY1950		ZB2-BY1951	
	Hydraulic pump		Hydraulic motor		Tracer				
ZB2-BY1952		ZB2-BY1953		ZB2-BY1954					

Operational symbols

	Continuous regulation		Adjustable		Lock or tighten		Lock or tighten		Unlock, unclamp
ZB2-BY1955		ZB2-BY1956		ZB2-BY1957		ZB2-BY1958		ZB2-BY1959	
	Unlock, unclamp		Brake on		Brake off		Automatic (or semi-automatic) cycle		Hand control
ZB2-BY1960		ZB2-BY1961		ZB2-BY1962		ZB2-BY1963		ZB2-BY1964	
	ON		OFF		ON - OFF		ON, whilst pushbutton depressed		Engaging
ZB2-BY1965		ZB2-BY1966		ZB2-BY1967		ZB2-BY1968		ZB2-BY1969	
	Disengaging		Locknut closed		Locknut open				
ZB2-BY1970		ZB2-BY1971		ZB2-BY1972					


Analogue output joystick controllers Ø 22 mm (fixing)

with circular chromium plated metal bezel


Characteristics :
page 24
Output curves :
page 24
References :
page 25

Dimensions, mounting


Panel cut-out (thickness 1 to 4.5 mm)
Viewed from top of panel




Dimensions
XDA-L11...




XDA-V11...




Minimum distance between 2 controllers




Front plate (48 x 48)




Front plate (48 x 48)




Displacement axes
One 2 direction axis



Mounting
XDA-L11...



XDA-V11...



Two all direction axes

