

W355

CC10

CC21

CC325

WC6

CIRCLIP PLIERS

2195

2295

2105

2205

W355 The scissor action cuts stranded copper and aluminum cable up to 19 strands of 0.064ins diameter without traying. The parrot beak blade holds the cable firmly without distorting its shape. Ideal for cutting domestic cooker cable.

Cat No	Overall Length	Unit/ Pack
--------	----------------	------------

W355/10 10" 250mm

5

CC10 Drop forged steel handles and head joined by a hardened rivet. The head has two cutting stations, hardened and tempered to cut a maximum 9.2mm O/D copper cable

Cat No	Overall Length	Unit/ Pack
--------	----------------	------------

CC10 6½" 164mm

10

CC21 Drop forged steel handles and head joined by a hardened rivet. The head is hardened and tempered to cut a maximum 17mm O/D copper cable

Cat No	Overall Length	Unit/ Pack
--------	----------------	------------

CC21 9½" 238mm

6

CC325 These powerful yet compact cutters feature a ratchet action, which with a series of small following cuts will shear up to a maximum 32mm O/D copper cable

The pressed steel handles are spring loaded for single handed operation with a finger lock to hold them in a closed position

Cat No	Overall Length	Unit/ Pack
--------	----------------	------------

CC325 11" 280mm

1

457-346
WC6 The special cutting action of the head allows materials such as wire strand, electric cable and metal to be cut without distorting the end profile of the material. The pressed aluminium handles are spring loaded for single handed operation with a thumb lock to hold them in the closed position.

Maximum capacities:-

- 6.5mm mild steel strand-85 ton/inch²
- 6.5mm unarmoured electric cable
- 5.0mm high tensile steel rope-115 ton/inch²
- 5.0mm steel wire -21 ton/inch²
- 5.0mm copper and aluminium rod
- 4.0mm steel rod-42 ton/inch²
- 2.5mm spring steel wire-115 ton/inch²

Cat No	Overall Length	Unit/ Pack
--------	----------------	------------

WC6 7½" 195m

6

CIRCLIP PLIERS

A quality range of drop forged circlip pliers with PVC sleeves available for fitting internal and external circlips in capacities as Table 1. Tips are manufactured to close limits and are angled and serrated to ensure retention of the clip when expanded or compressed.

TABLE 1

Cat No	Description	Length MM	Capacity		
			MM	OMM	Point OMM
W2105/5	External Straight Circlip Pliers	5"	125	10-25	1 2-1 4
W2105/7	External Straight Circlip Pliers	7"	175	19-40	1 7-1 9
W2105/9	External Straight Circlip Pliers	9"	230	32-80	2 2-2 4
W2195/5	External Bent Circlip Pliers	5"	125	10-25	1 2-1 4
W2195/7	External Bent Circlip Pliers	7"	175	19-40	1 7-1 9
W2195/9	External Bent Circlip Pliers	9"	230	32-80	2 2-2 4
W2205/5	Internal Straight Circlip Pliers	5"	125	12-25	1 2-1 4
W2205/7	Internal Straight Circlip Pliers	7"	175	19-65	1 7-1 9
W2205/9	Internal Straight Circlip Pliers	9"	230	32-80	2 2-2 4
W2295/5	Internal Bent Circlip Pliers	5"	125	12-25	1 2-1 4
W2295/7	Internal Bent Circlip Pliers	7"	175	19-65	1 7-1 9

PERS

ted ou

his
and

ng edge

ng and

; and
edges a
to safe
1.6mmitside
n to
ed

for

eves

Un

Pac

S

S

S

S

S

S

S

S

affected b

guarantee

practice of

ONAL

spring

e steel

cut with

Un

Pac

ONAL

setting th

le steel

ut with

Un

Pac

CUTTE

ges with

her with

tting the

ton high

meter w

ss relieve

wisting a

r workin

struction

P