


CNS 471

Vishay Sfernice



Decade Divider, Single-In-Line Thin Film Resistor Networks (Standard)



Using these integrated thin film networks instead of discrete resistor sets, designers gain several advantages: smaller size, better overall tracking, greater reliability, and lower cost.

FEATURES

- Low voltage coefficient < 0.02 ppm/V
- Low noise index < - 30 dB
- High stability 0.01 % on ratio (1000 h at Pn at + 70 °C)
- Standard



RoHS
COMPLIANT

TYPICAL PERFORMANCE


	ABS	TRACKING
TCR	< 25 ppm/°C	< 2.5 ppm/°C
	ABS	RATIO
TOL.	0.1 %	0.03 %

SCHEMATIC

5 Decades



6 Decades



STANDARD ELECTRICAL SPECIFICATIONS

TEST	SPECIFICATIONS		CONDITIONS
MATERIAL	PASSIVATED NICHROME		
Resistance range	100 Ω to 10 MΩ		
TCR	Tracking	< 2.5 ppm/°C	Except for 100R (5 ppm/°C)
	Absolute	< 25 ppm/°C	(0 °C to + 70 °C)
Tolerance	Ratio	A = ± 0.05 %, B = ± 0.1 %, C = ± 0.03 %	
	Absolute	± 0.1 %	(0 °C to + 70 °C)
Power rating	Resistor	0.1 W	
	Package	0.6 W	(0 °C to + 70 °C)
Stability	ΔR Ratio	0.01 % typical	1000 h at + 70 °C at Pn
Voltage coefficient	< 0.02 ppm/V		
Working voltage	1200 V		
Operating temperature range	0 °C; + 70 °C		
Storage temperature range	- 55 °C to + 155 °C		
Noise	< - 30 dB typical		
Thermal EMF	0.1 μV/°C		
Shelf life stability (Ratio)	50 ppm		1 year


**CNS 471**

Decade Divider, Single-In-Line
Thin Film Resistor Networks (Standard)

Vishay Sfernice


DIMENSIONS

5 Decades



DIMENSION	INCHES	MILLIMETERS
A	0.100	2.54
B	0.830	21.08
C	0.020	0.51
D	0.275	7 max.
E	0.125	3.17
F	0.100	2.54 max.
G	0.010	0.25

6 Decades






DIMENSION	INCHES	MILLIMETERS
A	0.100	2.54
B	0.830	21.08
C	0.020	0.51
D	0.275	7 max.
E	0.125	3.17
F	0.100	2.54 max.
G	0.010	0.25

MECHANICAL SPECIFICATIONS

Resistive material	Nichrome
Coating	Fluidized epoxy
Terminals	Tin/silver on copper alloy
Substrate material	Alumina
Marking resistance to solvents	Laser marking

GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: CNS471A6



Historical Part Number example: CNS 471 A 6 e2



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.