



JKL PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF22160-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	800 @ 0°C	370	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 METRIC THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION	
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP	
DRAWN BY L. WENGSTROM	APPVD BY DATE FD 10/17/00	SIZE A	FSCM NO. 55335
DIM LINE CORRECT, AND 160+/-5.0 TO 160+/-3.0 LEAD LENGTH TO 17±3 RELEASED	3/14/00 3/14/00 2/29/00	DRAWING NO. BF22160-24B	

