



DG417L/418L/419L

Vishay Siliconix

Precision Monolithic Low-Voltage CMOS Analog Switches

DESCRIPTION

The DG417L/418L/419L are low voltage pin-for-pin compatible companion devices to the industry standard DG417/418/419 with improved performance.

Using BiCMOS wafer fabrication technology allows the DG417L/418L/419L to operate on single and dual supplies. Single supply voltage ranges from 3 to 12 V while dual supply operation is recommended with ± 3 to ± 6 V.

Combining high speed (t_{ON} : 28 ns), flat r_{ON} over the analog signal range (6 Ω), minimal insertion loss (up to 100 MHz), and excellent crosstalk and off-isolation performance (-70 dB at 1 MHz), the DG417L/418L/419L are ideally suited for audio and video signal switching.

The DG417L and DG418L respond to opposite control logic as shown in the Truth Table. The DG419L has an SPDT configuration.

BENEFITS

- Widest Dynamic Range
- Low Signal Errors and Distortion
- Break-Before-Make Switching Action
- Simple Interfacing

FEATURES

- 2.7- thru 12 V Single Supply or ± 3 - thru ± 6 Dual Supply
- On-Resistance - r_{ON} : 14 Ω
- Fast Switching - t_{ON} : 28 ns
- t_{OFF} : 13 ns
- TTL, CMOS Compatible
- Low Leakage: < 100 pA





RoHS*
COMPLIANT

APPLICATIONS

- Precision Automatic Test Equipment
- Precision Data Acquisition
- Communication Systems
- Battery Powered Systems
- Computer Peripherals
- SDSL, DSLAM
- Audio and Video Signal Routing

FUNCTIONAL BLOCK DIAGRAM AND PIN CONFIGURATION



TRUTH TABLE

Logic	DG417L	DG418L
0	ON	OFF
1	OFF	ON

TRUTH TABLE - DG419L

Logic	NC	NO
0	ON	OFF
1	OFF	ON

ORDERING INFORMATION DG417L/418L

Temp Range	Package	Part Number
	8-Pin Narrow SOIC	DG417LDY DG417LDY-E3 DG417LDY-T1 DG417LDY-T1-E3
		DG418LDY DG418LDY-E3 DG418LDY-T1 DG418LDY-T1-E3
		DG417LDQ-T1-E3
		DG418LDQ-T1-E3
	8-Pin MSOP	DG417LDQ-T1-E3
		DG418LDQ-T1-E3

ORDERING INFORMATION DG419L

Temp Range	Package	Part Number
- 40 to 85 °C	8-Pin Narrow SOIC	DG419LDY DG419LDY-E3 DG419LDY-T1 DG419LDY-T1-E3
	8-Pin MSOP	DG419LDQ-T1-E3

DG417L/418L/419L

Vishay Siliconix



ABSOLUTE MAXIMUM RATINGS			
Parameter		Limit	Unit
V+ to V-		- 0.3 to 13	V
GND to V-		7	
V _L		(GND - 0.3) to (V+ + 0.3)	
I _N , COM, NC, NO ^a		- 0.3 to (V+ + 0.3) or 30 mA, whichever occurs first	
Continuous Current (Any Terminal)		30	mA
Peak Current, S or D (Pulsed 1 ms, 10 % Duty Cycle)		100	
Storage Temperature	(AK, DQ, DY Suffix)	- 65 to 150	°C
Power Dissipation (Packages) ^b	8-Pin MSOP ^c	320	mW
	8-Pin SOIC ^c	400	
	8-Pin CerDIP ^d	600	

Notes:

a. Signals on NC, NO, COM, or IN exceeding V+ or V- will be clamped by internal diodes. Limit forward diode current to maximum current ratings.

b. All leads welded or soldered to PC Board.

c. Derate 6.5 mW/°C above 25 °C.

d. Derate 12 mW/°C above 75 °C.

SPECIFICATIONS (SINGLE SUPPLY 12 V)									
Parameter	Symbol	Test Conditions Unless Otherwise Specified V ₊ = 12 V, V ₋ = 0 V V _L = 5 V, V _{IN} = 2.4 V, 0.8 V ^f	Temp ^b	Typ ^c	A Suffix Limits - 55 to 125 °C		D Suffix Limits - 40 to 85 °C		Unit
					Min ^d	Max ^d	Min ^d	Max ^d	
Analog Switch									
Analog Signal Range ^e	V _{ANALOG}		Full		0	12	0	12	V
On-Resistance	r _{ON}	V ₊ = 10.8 V, V ₋ = 0 V I _{NO} , I _{NC} = 5 mA, V _{COM} = 2/9 V	Room Full	13		20 32		20 23.5	Ω
Switch Off Leakage Current	I _{NO(off)} I _{NC(off)}	V _{COM} = 1/11 V V _{NO} , V _{NC} = 11/1 V	Room Full		- 1 - 15	1 15	- 1 - 10	1 10	nA
	I _{COM(off)}		Room Full		- 1 - 15	1 15	- 1 - 10	1 10	
Channel On Leakage Current	I _{COM(on)}	V _{NO} , V _{NC} = V _{COM} = 11/1 V	Room Full		- 1 - 15	1 15	- 1 - 10	1 10	
Digital Control									
Input Current	I _{INL} or I _{INH}		Full	0.01	- 1.5	1.5	- 1	1	μA
Dynamic Characteristics									
Turn-On Time	t _{ON}	R _L = 300 Ω, C _L = 35 pF V _{NO} , V _{NC} = 5 V, See Figure 2	Room Full	28		43 50		43 46	ns
Turn-Off Time	t _{OFF}		Room Full	13		31 35		31 32	
Break-Before-Make Time Delay	t _D	DG419L Only, V _{NC} , V _{NO} = 5 V R _L = 300 Ω, C _L = 35 pF	Room	13					
Charge Injection ^e	Q _{INJ}	V _g = 0 V, R _g = 0 Ω, C _L = 1 nF	Room	1					pC
Off-Isolation ^e	OIRR	R _L = 50 Ω, C _L = 5 pF , f = 1 MHz	Room	- 71					dB
Channel-to-Channel Crosstalk ^e	X _{TALK}		Room	- 71					
Source Off Capacitance ^e	C _{NO(off)} C _{NC(off)}	V _{IN} = 0 or V ₊ , f = 1 MHz	Room	5					pF
Channel-On Capacitance ^e	C _{ON}		Room	15					
Power Supplies									
Positive Supply Current	I ₊	V _{IN} = 0 or V _L	Room Full	0.02		1 7.5		1 5	μA
Negative Supply Current	I ₋		Room Full	- 0.002	- 1 - 7.5		- 1 - 5		
Logic Supply Current	I _L		Room Full	0.002		1 7.5		1 5	
Ground Current	I _{GND}		Room Full	- 0.002	- 1 - 7.5		- 1 - 5		



DG417L/418L/419L

Vishay Siliconix

SPECIFICATIONS (DUAL SUPPLY ± 5 V)									
Parameter	Symbol	Test Conditions Unless Otherwise Specified V+ = 5 V, V- = - 5 V VL = 5 V, VIN = 2.4 V, 0.8 V ^f	Temp ^b	Typ ^c	A Suffix Limits - 55 to 125 °C		D Suffix Limits - 40 to 85 °C		Unit
					Min ^d	Max ^d	Min ^d	Max ^d	
Analog Switch									
Analog Signal Range ^e	VANALOG		Full		- 5	5	- 5	5	V
On-Resistance	rON	V+ = 5 V, V- = - 5 V INO, INc = 5 mA, VCOM = ± 3.5 V	Room Full	14		18.5 30		18.5 21	Ω
Switch Off Leakage Current ^a	INO(off) INc(off)	V+ = 5.5 , V- = - 5.5 V VCOM = ± 4.5 V VNO, VNC = ± 4.5 V	Room Full		- 1 - 15	1 15	- 1 - 10	1 10	nA
	ICOM(off)		Room Full		- 1 - 15	1 15	- 1 - 10	1 10	
Channel On Leakage Current ^a	ICOM(on)	V+ = 5.5 V, V- = - 5.5 V VNO, VNC = VCOM = ± 4.5 V	Room Full		- 1 - 15	1 15	- 1 - 10	1 10	
Digital Control									
Input Current ^a	IINL or IINH		Full	0.05	- 1.5	1.5	- 1	1	μA
Dynamic Characteristics									
Turn-On Time ^e	tON	RL = 300 Ω, CL = 35 pF VNO, VNC = ± 3.5 V, See Figure 2	Room Full	30		41 50		41 44	ns
Turn-Off Time ^e	tOFF		Room Full	16		32 36		32 33	
Break-Before-Make Time Delay ^e	tD	DG419L Only, VNO, VNC = 3.5 V RL = 300 Ω, CL = 35 pF	Room	10					
TransitionTime	tTRANS	RL = 300 Ω, CL = 35 pF VS1 = ± 3.5 V, VS2 = ± 3.5 V	Room	33		47		47	
Charge Injection ^e	QINJ	Vg = 0 V, Rg = 0 Ω, CL = 1 nF	Room	3					pC
Off-Isolation ^e	OIRR	RL = 50 Ω, CL = 5 pF , f = 1 MHz	Room	- 71					dB
Channel-to-Channel Crosstalk ^e	XTALK		Room	- 76					
Source Off Capacitance ^e	CNO(off) CNC(off)	f = 1 MHz	Room	5.2					pF
Channel-On Capacitance ^e	CON		Room	15					
Power Supplies									
Positive Supply Current ^e	I+	VIN = 0 or VL	Room Full	0.03		1 7.5		1 5	μA
Negative Supply Current ^e	I-		Room Full	- 0.002	- 1 - 7.5		- 1 - 5		
Logic Supply Current ^e	IL		Room Full	0.002		1 7.5		1 5	
Ground Current ^e	IGND		Room Full	- 0.002	- 1 - 7.5		- 1 - 5		

DG417L/418L/419L

Vishay Siliconix



SPECIFICATIONS (SINGLE SUPPLY 5 V)									
Parameter	Symbol	Test Conditions Unless Otherwise Specified V+ = 5 V, V- = 0 V VL = 5 V, VIN = 2.4 V, 0.8 V ^f	Temp ^b	Typ ^c	A Suffix Limits - 55 to 125 °C		D Suffix Limits - 40 to 85 °C		Unit
					Min ^d	Max ^d	Min ^d	Max ^d	
Analog Switch									
Analog Signal Range ^e	VANALOG		Full			5		5	V
On-Resistance ^e	rON	V+ = 4.5 V, I _{NO} , I _{NC} = 5 mA V _{COM} = 1 V, 3.5 V	Room Full	26		36.5 50		36.5 40.5	Ω
Dynamic Characteristics									
Turn-On Time ^e	t _{ON}	RL = 300 Ω, CL = 35 pF V _{NO} , V _{NC} = 3.5 V, See Figure 2	Room Full	37		49 60		49 54	ns
Turn-Off Time ^e	t _{OFF}		Room Full	16		31 35		31 32	
Break-Before-Make Time Delay ^e	t _D	DG419L Only, V _{NO} , V _{NC} = 3.5 V RL = 300 Ω, CL = 35 pF	Room	19					
Charge Injection ^e	Q _{INJ}	V _g = 0 V, R _g = 0 Ω, CL = 1 nF	Room	0.4					pC
Power Supplies									
Positive Supply Current ^e	I+	VIN = 0 or VL	Room Full	0.02		1 7.5		1 5	μA
Negative Supply Current ^e	I-		Room Full	- 0.002	- 1 - 7.5		- 1 - 5		
Logic Supply Current ^e	IL		Room Full	0.002		1 7.5		1 5	
Ground Current ^e	IGND		Room Full	- 0.002	- 1 - 7.5		- 1 - 5		



DG417L/418L/419L

Vishay Siliconix

SPECIFICATIONS (SINGLE SUPPLY 3 V)									
Parameter	Symbol	Test Conditions Unless Otherwise Specified V+ = 3 V, V- = 0 V VL = 3 V, VIN = 2.0 V, 0.4 V ^f	Temp ^b	Typ ^c	A Suffix Limits - 55 to 125 °C		D Suffix Limits - 40 to 85 °C		Unit
					Min ^d	Max ^d	Min ^d	Max ^d	
Analog Switch									
Analog Signal Range ^e	V _{ANALOG}		Full		0	3	0	3	V
On-Resistance	r _{ON}	V+ = 2.7 V, V- = 0 V I _{NO} , I _{NC} = 5 mA, V _{COM} = 0.5, 2.2 V	Room Full	47		70 80		70 75	Ω
Switch Off Leakage Current ^a	I _{NO(off)} I _{NC(off)}	V+ = 3.3 , V- = 0 V V _{COM} = 1, 2 V, V _{NO} , V _{NC} = 2, 1 V	Room Full		- 1 - 15	1 15	- 1 - 10	1 10	nA
	I _{COM(off)}		Room Full		- 1 - 15	1 15	- 1 - 10	1 10	
Channel On Leakage Current ^a	I _{COM(on)}	V+ = 3.3 V, V- = 0 V V _{NO} , V _{NC} = V _{COM} = 1, 2 V	Room Full		- 1 - 15	1 15	- 1 - 10	1 10	
Digital Control									
Input Current ^a	I _{INL} or I _{INH}		Full	0.005	- 1.5	1.5	- 1	1	μA
Dynamic Characteristics									
Turn-On Time	t _{ON}	RL = 300 Ω, CL = 35 pF V _{NO} , V _{NC} = 1.5 V, See Figure 2	Room Full	65		75 95		75 85	ns
Turn-Off Time	t _{OFF}		Room Full	26		41 45		41 43	
Break-Before-Make Time Delay	t _D	DG419L Only, V _{NO} , V _{NC} = 1.5 V RL = 300 Ω, CL = 35 pF	Room	33					
Charge Injection ^e	Q _{INJ}	V _g = 0 V, R _g = 0 Ω, CL = 10 nF	Room	1					pC
Off-Isolation ^e	OIRR	RL = 50 Ω, CL = 5 pF , f = 1 MHz	Room	- 71					dB
Channel-to-Channel Crosstalk ^e	X _{TALK}		Room	- 77					
Source Off Capacitance ^e	C _{NO(off)} C _{NC(off)}	f = 1 MHz	Room	5.6					pF
Channel On Capacitance ^e	CD(on)		Room	16					

Notes:

- Leakage parameters are guaranteed by worst case test condition and not subject to production test.
- Room = 25 °C, Full = as determined by the operating temperature suffix.
- Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.
- The algebraic convention whereby the most negative value is a minimum and the most positive a maximum, is used in this data sheet.
- Guaranteed by design, not subject to production test.
- V_{IN} = input voltage to perform proper function.







Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

DG417L/418L/419L

Vishay Siliconix









TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted





TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



DG417L/418L/419L

Vishay Siliconix



SCHEMATIC DIAGRAM (TYPICAL CHANNEL)






Figure 1.

TEST CIRCUITS




C_L (includes fixture and stray capacitance)

$$V_{OUT} = V_{IN} \frac{R_L}{R_L + r_{ON}}$$



Note: Logic input waveform is inverted for switches that have the opposite logic sense control

Figure 2. Switching Time



C_L (includes fixture and stray capacitance)





Figure 3. Break-Before-Make (DG419L)



TEST CIRCUITS



C_L (includes fixture and stray capacitance)

$$V_O = V_S \frac{R_L}{R_L + r_{ON}}$$






Figure 4. Transition Time (DG419L)



$$V_{IN} = 0 - V_+$$



IN dependent on switch configuration Input polarity determined by sense of switch.

Figure 5. Charge Injection




Figure 6. Crosstalk (DG419L)

DG417L/418L/419L

Vishay Siliconix



TEST CIRCUITS




Figure 7. Off Isolation




Figure 8. Source/Drain Capacitances



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.