

Series DSD, DLD

Time Delay Relay • 10-50 Amp

- DC Control, AC Output
- External Adjustment
- Industry Standard Package
- Zero Voltage Turn-On
- Panel Mount

These “on-operate” (pull-in) time-delay solid state relays are housed in a single industry standard package. AC output is controlled by a DC input and has an externally adjustable time delay. Choices include models with two time-delay ranges.

Manufactured in Crydom's ISO 9001 Certified facility for optimum product performance and reliability.

CRYDOM

Control over power

MODEL NUMBERS	DSD2410	DSD2425	DSD2450	DLD2410	DLD2425	DLD2450
OUTPUT SPECIFICATIONS^①						
Operating Voltage Range (47-63 Hz) [Vrms]	48-280	48-280	48-280	48-280	48-280	48-280
Load Current Range ^③ [Arms]	.04-10	.04-25	.04-50	.04-10	.04-25	.04-50
Transient Overvoltage [Vpk]	600	600	600	600	600	600
Max. Surge Current, (16.6ms) [Apk]	120	250	625	120	250	625
Max. On-State Voltage Drop @ Rated Current [Vpk]	1.6	1.6	1.6	1.6	1.6	1.6
Thermal Resistance Junction to Case [$R_{\theta JC}$]	1.48	1.02	0.63	1.48	1.02	0.63
Maximum $I^2 t$ for Fusing, (8.3 msec.) [$A^2 sec$]	60	260	1620	60	260	1620
Max. Off-State Leakage Current @ Rated Voltage [mArms]	10	10	10	10	10	10
Min. Off-State dv/dt @ Max. Rated Voltage [V/ μsec] ^②	500	500	500	500	500	500
Max. Turn-On Time ^④	Adjustable, See Table					
Max. Turn-Off Time	1/2 cycle	1/2 cycle	1/2 cycle	1/2 cycle	1/2 cycle	1/2 cycle
Max. Reset Time [μsec] ^⑤	100	100	100	100	100	100
Power Factor (Min.) with Max. Load	0.5	0.5	0.5	0.5	0.5	0.5

INPUT SPECIFICATIONS ^① DC CONTROL

Control Voltage Range	3.5-15Vdc
Max. Turn-On Voltage	3.5 Vdc
Min. Turn-Off Voltage	1.0 Vdc
Min. Input Impedance	1500 Ohms
Typical Input Current	3.4mA @ 5 Vdc, 11.4mA @ 15Vdc

GENERAL NOTES

- ① All parameters at 25°C unless otherwise specified.
- ② Off-State dv/dt test method per EIA/NARM standard RS-443, paragraph 13.11.1
- ③ Heat sinking required, for derating curves see page 2.
- ④ Timing Resistor may be as high as 10M Ohm with performance dependent on resistor quality.
- ⑤ Before and after time-out.

TYPICAL TURN-ON DELAY ^①

RESISTOR	TIME (DSD)	TIME (DLD)
0 (Short)	0.10 sec	1.6 sec
10K Ω	0.19 sec	3.1 sec
100K Ω	0.94 sec	15 sec
470K Ω	4.0 sec	64 sec
1.0M Ω ^④	8.3 sec	133 sec

© 2002 CRYDOM CORP, Specifications subject to change without notice.

For recommended applications and more information contact:

USA: Sales Support (877) 502-5500 Tech Support (877) 702-7700 FAX (619) 710-8540

Crydom Corp, 2320 Paseo de las Americas, Ste. 201, San Diego, CA 92154

Email: sales@crydom.com WEB SITE: http://www.crydom.com

UK: +44 (0)1202 365070 • FAX +44 (0)1202 365090 Crydom International Ltd., 7 Cobham Road, Ferndown Industrial Estate, Ferndown, Dorset BH21 7PE, Email: intsales@crydom.com.

GERMANY: +49 (0)180 3000 506



Series DSD, DLD

Time Delay Relay • 10-50 Amp

GENERAL SPECIFICATIONS

Dielectric Strength, Input section/output/base 4000 Vrms

Insulation Resistance @ 500Vdc 10^{10}

Ambient Operating Temperature Range -30 to 80°C

Ambient Storage Temperature Range -40 to 125°C



MECHANICAL SPECIFICATIONS

Weight: (typical) 3.0 oz. (43g)

Encapsulation: Thermally Conductive Epoxy




Terminals: Screws and Saddle Clamps Furnished, Unmounted

WIRING DIAGRAM



All dimensions are in inches (millimeters)

CURRENT DERATING CURVES



© 2002 CRYDOM CORP, Specifications subject to change without notice.

APPROVALS

UL E116949