


# PNP SILICON PLANAR MEDIUM POWER TRANSISTOR

## FXT557

ISSUE 1 – MARCH 94

### FEATURES

- \* 300 Volt  $V_{CE0}$
- \* 0.5 Amp continuous current
- \*  $P_{tot} = 1$  Watt



E-Line  
TO92 Compatible

REFER TO ZTX557 FOR GRAPHS

### ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	$V_{CBO}$	-300	V
Collector-Emitter Voltage	$V_{CEO}$	-300	V
Emitter-Base Voltage	$V_{EBO}$	-5	V
Peak Pulse Current	$I_{CM}$	-1	A
Continuous Collector Current	$I_C$	-0.5	A
Power Dissipation at $T_{amb}=25^{\circ}C$	$P_{tot}$	1	W
Operating and Storage Temperature Range	$T_j, T_{stg}$	-55 to +200	$^{\circ}C$

### ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ )

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-300			V	$I_C = -100\mu A, I_E = 0$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-300			V	$I_C = -10mA, I_B = 0^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5			V	$I_E = -100\mu A, I_C = 0$
Collector Cut-Off Current	$I_{CBO}$			-0.1	$\mu A$	$V_{CE} = -200V, I_E = 0$
Emitter Cut-Off Current	$I_{EBO}$			-0.1	$\mu A$	$V_{EB} = -4V, I_C = 0$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			-0.3	V	$I_C = -50mA, I_B = -5mA^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$			-1	V	$I_C = -50mA, I_B = -5mA^*$
Base-Emitter Turn-on Voltage	$V_{BE(on)}$			-1	V	$I_C = -50mA, V_{CE} = -10V^*$
Static Forward Current Transfer Ratio	$h_{FE}$	50		300		$I_C = -10mA, V_{CE} = -10V^*$ $I_C = -50mA, V_{CE} = -10V^*$
Transition Frequency	$f_T$	75			MHz	$I_C = -50mA, V_{CE} = -10V$ $f = 100MHz$
Output Capacitance	$C_{obo}$			10	pF	$V_{CE} = -10V, f = 1MHz$

\*Measured under pulsed conditions. Pulse width=300 $\mu s$ . Duty cycle  $\leq 2\%$

查询FXT557供应商

捷多邦, 专业PCB打样工厂, 24小时加急出货