


SANYO

Cadnica

Cell Type KR-1100AAU


Specifications




Nominal Capacity		1100mAh	
Nominal Voltage		1.2V	
Charging Current	Standard	110mA	
	Quick	220mA	
	Fast	1600mA	
Charging Time	Standard	14 to 16Hrs.	
	Quick	7 to 8Hrs.	
	Fast	about 1Hr.	
Ambient Temperature	Charge	Standard	0°C to +45°C [+32°F to 113°F]
		Quick	0°C to +45°C [+32°F to 113°F]
		Fast	0°C to +45°C [+32°F to 113°F]
	Discharge		-20°C to +60°C [-4°F to 140°F]
	Storage		-30°C to +50°C [-22°F to 122°F]
Internal Impedance (Av.) (at 50% discharge)		19.0mΩ (at 1000Hz)	
Weight		24g/0.85oz	
Dimensions(D)×(H) (with tube)		14.3 ⁰ _{-0.5} × 50.3 ⁰ ₋₁	mm
		0.56 ⁰ _{-0.02} × 1.98 ⁰ _{-0.04}	inch

Typical Characteristics


Charge




Discharge (at high rate)




Charge



Discharge (at high rate)



Discharge (at low rate)



Temperature (Charge & Discharge)

