



## SMP50 / SMTPA / TPA

### TRISIL™ FOR TELECOM EQUIPMENT PROTECTION

#### FEATURES

- Bidirectional crowbar protection
- Voltage range from 62V to 270V
- Low capacitance from 12pF to 20pF @ 50V
- Low leakage current :  $I_R = 2\mu A$  max
- Holding current:  $I_H = 150$  mA min
- Repetitive peak pulse current :  
 $I_{PP} = 50$  A (10/1000 $\mu s$ )

#### MAIN APPLICATIONS

Telecommunication equipment such as:

- Analog and digital line cards (xDSL, T1/E1, ISDN, ...)
- Terminals (phone, fax, modem, ...) and central office equipment

#### DESCRIPTION

These Trisil series have been designed to protect telecommunication equipment against lightning and transient induced by AC power lines.

They are available in SMA, SMB and DO-15 packages.

#### BENEFITS

Trisils are not subject to ageing and provide a fail safe mode in short circuit for a better protection. They are used to help equipment to meet various standards such as UL1950, IEC950 / CSA C22.2, UL1459 and FCC part 68.

Trisils have UL94 V0 approved resin.

SMA and SMB packages are JEDEC registered (DO-214AC and DO-214AA).

Trisils are UL497B approved (file: E136224).





Table 1: Order Codes

| Part Number | Marking    |
|-------------|------------|
| SMP50-xxx   | See page 9 |
| TPAxxx      |            |
| SMTPAxxx    |            |

Figure 1: Schematic Diagram



## SMP50 / SMTPA / TPA

**Table 2: In compliances with the following standards**

| STANDARD                                   | Peak Surge Voltage (V) | Waveform Voltage                 | Required peak current (A)                  | Current waveform                 | Minimum serial resistor to meet standard ( $\Omega$ ) |
|--------------------------------------------|------------------------|----------------------------------|--------------------------------------------|----------------------------------|-------------------------------------------------------|
| <b>GR-1089 Core First level</b>            | 2500<br>1000           | 2/10 $\mu$ s<br>10/1000 $\mu$ s  | 500<br>100                                 | 2/10 $\mu$ s<br>10/1000 $\mu$ s  | 20<br>10                                              |
| <b>GR-1089 Core Second level</b>           | 5000                   | 2/10 $\mu$ s                     | 500                                        | 2/10 $\mu$ s                     | 40                                                    |
| <b>GR-1089 Core Intra-building</b>         | 1500                   | 2/10 $\mu$ s                     | 100                                        | 2/10 $\mu$ s                     | 0                                                     |
| <b>ITU-T-K20/K21</b>                       | 6000<br>1500           | 10/700 $\mu$ s                   | 150<br>37.5                                | 5/310 $\mu$ s                    | 53<br>0                                               |
| <b>ITU-T-K20 (IEC61000-4-2)</b>            | 8000<br>15000          | 1/60 ns                          | ESD contact discharge<br>ESD air discharge |                                  | 0<br>0                                                |
| <b>VDE0433</b>                             | 4000<br>2000           | 10/700 $\mu$ s                   | 100<br>50                                  | 5/310 $\mu$ s                    | 21.5<br>0                                             |
| <b>VDE0878</b>                             | 4000<br>2000           | 1.2/50 $\mu$ s                   | 100<br>50                                  | 1/20 $\mu$ s                     | 0<br>0                                                |
| <b>IEC61000-4-5</b>                        | 4000<br>4000           | 10/700 $\mu$ s<br>1.2/50 $\mu$ s | 100<br>100                                 | 5/310 $\mu$ s<br>8/20 $\mu$ s    | 21.5<br>0                                             |
| <b>FCC Part 68, lightning surge type A</b> | 1500<br>800            | 10/160 $\mu$ s<br>10/560 $\mu$ s | 200<br>100                                 | 10/160 $\mu$ s<br>10/560 $\mu$ s | 12.5<br>6.5                                           |
| <b>FCC Part 68, lightning surge type B</b> | 1000                   | 9/720 $\mu$ s                    | 25                                         | 5/320 $\mu$ s                    | 0                                                     |

**Table 3: Absolute Ratings** ( $T_{amb} = 25^{\circ}\text{C}$ )

| Symbol             | Parameter                                                 |                                                                                                                      | Value                                     | Unit               |
|--------------------|-----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------------|--------------------|
| $I_{PP}$           | Repetitive peak pulse current (see figure 2)              | 10/1000 $\mu$ s<br>8/20 $\mu$ s<br>10/560 $\mu$ s<br>5/310 $\mu$ s<br>10/160 $\mu$ s<br>1/20 $\mu$ s<br>2/10 $\mu$ s | 50<br>100<br>55<br>65<br>75<br>100<br>100 | A                  |
| $I_{FS}$           | Fail-safe mode : maximum current (note 1)                 | 8/20 $\mu$ s                                                                                                         | 2.5                                       | kA                 |
| $I_{TSM}$          | Non repetitive surge peak on-state current (sinusoidal)   | t = 0.2 s<br>t = 1 s<br>t = 2 s<br>t = 15 mn                                                                         | 16<br>11.5<br>10<br>3.5                   | A                  |
| $I^2t$             | $I^2t$ value for fusing                                   | t = 16.6 ms<br>t = 20 ms                                                                                             | 6.2<br>6.5                                | A <sup>2</sup> s   |
| $T_{stg}$<br>$T_j$ | Storage temperature range<br>Maximum junction temperature |                                                                                                                      | -55 to 150<br>150                         | $^{\circ}\text{C}$ |
| $T_L$              | Maximum lead temperature for soldering during 10 s.       |                                                                                                                      | 260                                       | $^{\circ}\text{C}$ |


**Note 1:** in fail safe mode, the device acts as a short circuit

Table 4: Thermal Resistances

| Symbol        | Parameter                                                                                   | Value |     |     | Unit                 |
|---------------|---------------------------------------------------------------------------------------------|-------|-----|-----|----------------------|
|               |                                                                                             | DO-15 | SMA | SMB |                      |
| $R_{th(j-a)}$ | Junction to ambient (with recommended footprint or with $L_{lead} = 10\text{mm}$ for DO-15) | 100   | 120 | 100 | $^{\circ}\text{C/W}$ |
| $R_{th(j-l)}$ | Junction to leads ( $L_{lead} = 10\text{mm}$ for DO-15)                                     | 60    | 30  | 20  | $^{\circ}\text{C/W}$ |

Table 5: Electrical Characteristics ( $T_{amb} = 25^{\circ}\text{C}$ )

| Symbol   | Parameter                  |
|----------|----------------------------|
| $V_{RM}$ | Stand-off voltage          |
| $V_{BR}$ | Breakdown voltage          |
| $V_{BO}$ | Breakover voltage          |
| $I_{RM}$ | Leakage current            |
| $I_{PP}$ | Peak pulse current         |
| $I_{BO}$ | Breakover current          |
| $I_H$    | Holding current            |
| $V_R$    | Continuous reverse voltage |
| $I_R$    | Leakage current at $V_R$   |
| C        | Capacitance                |



| Types                          | $I_{RM} @ V_{RM}$ |     | $I_R @ V_R$   |     | Dynamic $V_{BO}$ | Static $V_{BO} @ I_{BO}$ |      | $I_H$ | C    | C    |
|--------------------------------|-------------------|-----|---------------|-----|------------------|--------------------------|------|-------|------|------|
|                                | max.              |     | max.          |     | max.             | max.                     | max. | min.  | typ. | typ. |
|                                | $\mu\text{A}$     | V   | $\mu\text{A}$ | V   | V                | V                        | mA   | mA    | pF   | pF   |
| SMP50-62 / TPA62<br>SMTPA62    | 2                 | 56  | 5             | 62  | 85               | 82                       | 800  | 150   | 20   | 40   |
| SMP50-68 / TPA68<br>SMTPA68    |                   | 61  |               | 68  | 93               | 90                       |      |       | 20   | 40   |
| SMP50-100 / TPA100<br>SMTPA100 |                   | 90  |               | 100 | 135              | 133                      |      |       | 16   | 35   |
| SMP50-120 / TPA120<br>SMTPA120 |                   | 108 |               | 120 | 160              | 160                      |      |       | 16   | 30   |
| SMP50-130 / TPA130<br>SMTPA130 |                   | 117 |               | 130 | 173              | 173                      |      |       | 14   | 30   |
| SMP50-180 / TPA180<br>SMTPA180 |                   | 162 |               | 180 | 235              | 240                      |      |       | 14   | 25   |
| SMP50-200 / TPA200<br>SMTPA200 |                   | 180 |               | 200 | 262              | 267                      |      |       | 12   | 25   |
| SMP50-220 / TPA220<br>SMTPA220 |                   | 198 |               | 220 | 285              | 293                      |      |       | 12   | 25   |
| SMP50-240 / TPA240<br>SMTPA240 |                   | 216 |               | 240 | 300              | 320                      |      |       | 12   | 25   |
| SMP50-270 / TPA270<br>SMTPA270 |                   | 243 |               | 270 | 350              | 360                      |      |       | 12   | 25   |

**Note 1:**  $I_R$  measured at  $V_R$  guarantee  $V_{BR} \min \geq V_R$

**Note 2:** see functional test circuit 1

**Note 3:** see test circuit 2

**Note 4:** see functional holding current test circuit 3

**Note 5:**  $V_R = 50\text{V}$  bias,  $V_{RMS}=1\text{V}$ ,  $F=1\text{MHz}$

**Note 6:**  $V_R = 2\text{V}$  bias,  $V_{RMS}=1\text{V}$ ,  $F=1\text{MHz}$

Figure 2: Pulse waveform (10/1000μs)




Figure 3: Non repetitive surge peak on-state current versus overload duration




Figure 4: On-state voltage versus on-state current (typical values)




Figure 5: Relative variation of holding current versus junction temperature




Figure 6: Relative variation of breakover voltage versus junction temperature







Figure 7: Relative variation of leakage current versus reverse voltage applied (typical values)



**Figure 8: Variation of thermal impedance junction to ambient versus pulse duration (Printed circuit board FR4, SCu=35μm, recommended pad layout)**



**Figure 9: Relative variation of junction capacitance versus reverse voltage applied (typical values)**



**Figure 10: Test circuit 1 for Dynamic  $I_{BO}$  and  $V_{BO}$  parameters**




Figure 11: Test circuit 2 for  $I_{BO}$  and  $V_{BO}$  parameters




Figure 12: Test circuit 3 for dynamic  $I_H$  parameters




Figure 13: Ordering Information Scheme




Figure 14: SMA Package Mechanical Data






Figure 15: Foot Print Dimensions (in millimeters)




**SMP50 / SMTPA / TPA**

**Figure 16: SMB Package Mechanical Data**



**Figure 17: Foot Print Dimensions (in millimeters)**



**Figure 18: DO-15 Package Mechanical data**






Table 6: Ordering Information

| Part Number | Marking | Package | Weight  | Base qty | Delivery mode |
|-------------|---------|---------|---------|----------|---------------|
| SMP50-62    | V06     | SMA     | 0.068 g | 5000     | Tape & reel   |
| SMP50-68    | V07     |         |         |          |               |
| SMP50-100   | V10     |         |         |          |               |
| SMP50-120   | V12     |         |         |          |               |
| SMP50-130   | V13     |         |         |          |               |
| SMP50-180   | V18     |         |         |          |               |
| SMP50-200   | V20     |         |         |          |               |
| SMP50-220   | V22     |         |         |          |               |
| SMP50-240   | V24     |         |         |          |               |
| SMP50-270   | V27     |         |         |          |               |
| SMTPA62     | U01     | SMB     | 0.11 g  | 2500     | Tape & reel   |
| SMTPA68     | U05     |         |         |          |               |
| SMTPA100    | U13     |         |         |          |               |
| SMTPA120    | U17     |         |         |          |               |
| SMTPA130    | U19     |         |         |          |               |
| SMTPA180    | U25     |         |         |          |               |
| SMTPA200    | U27     |         |         |          |               |
| SMTPA220    | U31     |         |         |          |               |
| SMTPA240    | U35     |         |         |          |               |
| SMTPA270    | U39     |         |         |          |               |
| TPA62       | TPA62   | DO-15   | 0.40 g  | 1000     | Ammopack      |
| TPA62RL     |         |         |         | 6000     | Tape & reel   |
| TPA68       | TPA68   |         |         | 1000     | Ammopack      |
| TPA68RL     |         |         |         | 6000     | Tape & reel   |
| TPA100      | TPA100  |         |         | 1000     | Ammopack      |
| TPA100RL    |         |         |         | 6000     | Tape & reel   |
| TPA120      | TPA120  |         |         | 1000     | Ammopack      |
| TPA130      | TPA130  |         |         | 1000     | Ammopack      |
| TPA130RL    |         |         |         | 6000     | Tape & reel   |
| TPA180      | TPA180  |         |         | 1000     | Ammopack      |
| TPA180RL    |         |         |         | 6000     | Tape & reel   |
| TPA200      | TPA200  |         |         | 1000     | Ammopack      |
| TPA200RL    |         |         |         | 6000     | Tape & reel   |
| TPA220      | TPA220  |         |         | 1000     | Ammopack      |
| TPA220RL    |         |         |         | 6000     | Tape & reel   |
| TPA240      | TPA240  |         |         | 1000     | Ammopack      |
| TPA240RL    |         |         |         | 6000     | Tape & reel   |
| TPA270      | TPA270  |         |         | 1000     | Ammopack      |
| TPA270RL    |         |         |         | 6000     | Tape & reel   |

Table 7: Revision History

| Date        | Revision | Description of Changes                 |
|-------------|----------|----------------------------------------|
| 16-Nov-2004 | 1        | SMP50, SMTPA and TPA datasheets merge. |

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.  
All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

**STMicroelectronics group of companies**

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America  
**[www.st.com](http://www.st.com)**