



A Unit of Teledyne Electronics and Communications

Series TS

Output to 2.5A, 275 Vac
AC/DC Control

Part Number	Description
TS24D2G	2A, 275 Vac
TS3R2G	2.5A, 30 Vdc
TS3R1G	1A, 30 Vac/Vdc


Part Number Explanation

TS	24	D	2	G
Series	Line Voltage ¹	Switch Type ²	Output Current - Amps	Control Range ³

NOTES

- 1) Line Voltage (nominal): 24 = 240 Vac;
3 = 30 Vdc (3–30 Vdc/Vac for TS3R1G)
- 2) Switch Type: D = Zero-cross turn-on; R = Random turn-on
- 3) Control Range: G = 12–30 Vdc/Vac (TS242G, TS3R1G)
G = 12–30 Vdc (TS3R2G)

MECHANICAL SPECIFICATION



WEIGHT: .39 oz. (11g) Hole Ø .04 (1.1)

Figure 1 — TS relays; dimensions in inches (mm)

INPUT (CONTROL) SPECIFICATION

	Min	Max	Units
Control Range			
TS242G, TS3R1G	12	30	Vac/Vdc
TS3R2G	12	30	Vdc
Input Current Range	4.1	13	mA
(See Figure 2)			
Must Turn-Off Voltage		2.5	V
Input Resistance (Typical)		2100	Ohms



FEATURES/BENEFITS

- Pin-to-pin compatible with electromechanical relays
- AC and DC control
- AC and DC output
- Random and zero-cross turn-on
- Compact size
- High inrush capabilities
- Integrated clamping voltage

DESCRIPTION

The Series TS relays provide AC/DC switching in a compact size. The TS relays also provide an AC/DC control. These relays can withstand high surge currents. The TS relays are pin-to-pin compatible with electromechanical relays and may be used as replacements.

APPLICATIONS

- Interface applications
- Vending machines
- Light/lamp control
- Contactor driver
- Fan speed control

APPROVALS

All models are UL recognized.
UL File Number E128555.

CONTROL CHARACTERISTIC




Figure 2 — TS Relays

BLOCK DIAGRAM




Figure 3a — TS24D2G




Figure 3b — TS3R1G




Figure 3c — TS3R2G

GRID DIAGRAM




Figure 4a — TS24D2G




Figure 4b — TS3R1G




Figure 4c — TS3R2G

OUTPUT (LOAD) SPECIFICATION

	Min	Max	Unit
Operating Range			
TS24D2G	12	275	Vrms
TS3R2G	0	30	Vdc
TS3R1G	0	30	Vac/Vdc

Peak Voltage

TS24D2G	600	V
TS3R2G	60	V
TS3R1G	60	V

Load Current Range

TS24D2G	.05	2	Arms
TS3R2G	.001	2.5	Arms
TS3R1G	.001	1	Arms

Maximum Surge Current Rating (Non-Repetitive)

(See Figure 6)

TS24D2G	100	A
TS3R2G	12	A
TS3R1G	2.4	A

OUTPUT (LOAD) SPECIFICATION (Continued)

	Min	Max	Unit
On-State Voltage Drop			
TS24D2G		1.0	V
TS3R2G		0.5	V
TS3R1G		0.9	V

Zero-Cross Window (Typical)

TS24D2G	±10	V
TS3R2G	NA	
TS3R1G	NA	

Off-State Leakage Current (60Hz)

All relays	1	mA
------------	---	----

Operating Frequency Range

TS24D2G	1	440	Hz
TS3R1G	0	50	KHz

Turn-On Time (60Hz)

TS24D2G	10	ms
TS3R2G	50	µs
TS3R1G	5	ms

OUTPUT (LOAD) SPECIFICATION (Continued)

	Min	Max	Unit
Turn-Off Time (60Hz)			
TS24D2G		17	ms
TS3R2G		600	μs
TS3R1G		10	ms
Off-State dv/dt			
TS24D2G		500	V/μs
Switching Frequency			
TS3R2G		100	Hz
TS3R1G		10	Hz
I ² t for Match Fusing (<8.3ms)			
TS24D2G		50	A ² S

ENVIRONMENTAL SPECIFICATION

	Min	Max	Unit
Maximum Junction Temperature		125	°C
Operating Temperature			
TS24D2G	-40	100	°C
TS3R2G	-40	100	°C
TS3R1G	-40	90	°C
Input-Output Isolation			
TS24D2G	4000		V
TS3R2G	2500		V
TS3R1G	4000		V
Junction-Case Thermal Resistance			
TS24D2G	12		°C/W
TS3R2G	12		°C/W
TS3R1G	44		°C/W
Junction-Ambient Thermal Resistance			
TS24D2G	44		°C/W
TS3R2G	44		°C/W
TS3R1G	88		°C/W
Maximum Soldering Heat (1mm case)	260		°C

THERMAL CURVE




Figure 5a — TS24D2G




Figure 5b — TS3R2G




Figure 5c — TS3R1G

NON-REPETITIVE SURGE CURRENT




Figure 6a — TS24D2G




Figure 6b — TS3R2G




Figure 6c — TS3R1G

NOTES:

1. On inductive loads, a free-wheeling diode (or clamp) is recommended.
2. Electrical specifications at 25°C unless otherwise specified.
3. TS3R2G no polarity on the control pins.
4. For additional/custom options, contact factory.