

Common Mode Chokes & Coupled Inductors

For use in xDSL Applications and all General Signal Applications

- Reduce Common Mode Noise
- Operating Temp -40°C to +85°C
- Multiple Lines Per Part
- IR Reflow Capable Product

Call Tamura Sales Engineering for detailed specifications or for new products not listed below.

Part #	Size	Mounting	Turns Ratio WDG:WDG	Inductance @ 10KHz, 0.1V	DC Current (mA)	WDG DCR (Ω)	Package Fig.	Schematic Fig.
TTC-4072	EP13	THT	---	95μH	100	0.2	B	1
TTC-4078	EE5	SMD	1:1	348.5μH	0	5.45	A	2
TTC-4079	EE5	SMD	1:1	205μH	0	3.5	A	2
TTC-4090	EP13	THT	1:1	3.0mH	150	2.5	B	4
TTC-4091	EP13	THT	1:1	5.0mH	150	5.5	B	4
TTC-4095	EP13	THT	1:1	7.0mH	100	7.5	B	4
TTC-4096	EP10	THT	1:1	5.0mH	100	7.5	D	7
TTC-4104	EE5	SMD	1:1	300μH	0	5.2	A	2
TTC-4106	EP7	EP7	1:1	90μH	100	1.0	F	3
TTC-4110	EP13	SMD	1:1	4.0mH	100	4.5	C	5
TTC-4111	EP13	SMD	1:1	5.0mH	100	5.0	C	5

Application	Part #	OCL (mH) Min	DCR (Ω) Max	HiPot (Vrms)	CM Attenuation (dB) Typ.			Mounting	Package Fig.	Schematic Fig.
					0.1MHz	1MHz	10MHz			
ADSL	TTC-314	6.3	1	1500	-30	-45	-25	8 Pin SMD	E	6

Mechanical Dimensions mm (inches)

All dimensions are typical, please contact Tamura for tolerances and suggested layout information.

Fig. A




Fig. B




Fig. C




Fig. D




Fig. E





Fig. F



Common Mode Chokes & Coupled Inductors


Schematics




1




2



3



4



5



6



7