

## DUAL NON-INVERTING POWER DRIVER

### FEATURES

- 3.0A Peak Current Totem Pole Output
- 5 to 35V Operation
- 25ns Rise and Fall Times
- 25ns Propagation Delays
- Thermal Shutdown and Under-Voltage Protection
- High-Speed, Power MOSFET Compatible
- Efficient High Frequency Operation
- Low Cross-Conduction Current Spike
- Enable and Shutdown Functions
- Wide Input Voltage Range
- ESD Protection to 2kV


### DESCRIPTION

The UC1708 family of power drivers is made with a high-speed, high-voltage, Schottky process to interface control functions and high-power switching devices – particularly power MOSFETs. Operating over a 5 V to 35 V supply range, these devices contain two independent channels. The A and B inputs are compatible with TTL and CMOS logic families, but can withstand input voltages as high as  $V_{IN}$ . Each output can source or sink up to 3 A as long as power dissipation limits are not exceeded.

Although each output can be activated independently with its own inputs, they can be forced low in common through the action of either a digital high signal at the Shutdown terminal or by forcing the Enable terminal low. The Shutdown terminal will only force the outputs low, it will not effect the behavior of the rest of the device. The Enable terminal effectively places the device in under-voltage lockout, reducing power consumption by as much as 90%. During under-voltage and disable (Enable terminal forced low) conditions, the outputs are held in a self-biasing, low-voltage, state.

The UC3708 and UC2708 are available in plastic 8-pin MINI DIP and 16-pin *bat-wing* DIP packages for commercial operation over a 0°C to 70°C temperature range and industrial temperature range of -25°C to 85°C respectively. For operation over a -55°C to 125°C temperature range, the UC1708 is available in hermetically sealed 8-pin MINI CDIP, 16 pin CDIP and 20 pin CLCC packages. Surface mount devices are also available.

### BLOCK DIAGRAM




NOTE: Shutdown feature is not available in J or N packages only.


Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

**CONNECTION DIAGRAMS**


**DIL-8 (Top View)**  
 J Or N Package



**SOIC-16 (Top View)**  
 DW Package




**DIL-16 (Top View)**  
 JE Or NE Package



Note: In JE package, Pin 4 is Logic Ground. Pins 5, 12, and 13 are no connect.

**CLCC-20 (Top View)**  
 L Package



**ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>**

|   |                | VALUE                      | UNIT |
|---|----------------|----------------------------|------|
| Supply Voltage, $V_{IN}$                      |                | 35                         | V    |
| Output Current (Each Output, Source or Sink)  | Steady-State   | 0.5                        | A    |
|   | Peak Transient | 3                          | A    |
| Output Voltage                                |                | -0.3 to ( $V_{IN} + 0.3$ ) | V    |
| Enable and Shutdown Inputs                    |                | -0.3 to 6.2                | V    |
| A and B Inputs                                |                | -0.3 to ( $V_{IN} + 0.3$ ) | V    |
| Operating Junction Temperature <sup>(2)</sup> |                | 150                        | °C   |
| Storage Temperature Range                     |                | -65 to 150                 | °C   |
| Lead Temperature (Soldering, 10 Seconds)      |                | 300                        | °C   |

(1) All voltages are with respect to Logic Gnd pin. All currents are positive into, negative out of, device terminals.

(2) Consult Unirode Integrated Circuits databook for information regarding thermal specifications and limitations of packages.

**ELECTRICAL CHARACTERISTICS**

Unless otherwise stated,  $V_{IN}=10V$  to  $35V$ , and these specifications apply for:  $-55^{\circ}C < T_A < 125^{\circ}C$  for the UC1708,  $-25^{\circ}C < T_A < 85^{\circ}C$  for the UC2708, and  $0^{\circ}C < T_A < 70^{\circ}C$  for the UC3708,  $T_A = T_J$

| PARAMETER                           |                        | TEST CONDITIONS       | MIN  | TYP  | MAX | UNIT |
|-------------------------------------|------------------------|-----------------------|------|------|-----|------|
| $V_{IN}$                            | Supply current         | Outputs low           |      | 18   | 26  | mA   |
|                                     |                        | Outputs high          |      | 14   | 18  |      |
|                                     |                        | Enable = 0 V          |      | 1    | 4   |      |
| A, B and shutdown inputs low level  |                        |                       |      |      | 0.8 | V    |
| A, B and shutdown inputs high level |                        |                       | 2.0  |      |     | V    |
| A, B Input current low              |                        | $V_{A,B} = 0.4V$      | -1   | -0.6 |     | mA   |
| A, B Input current high             |                        | $V_{A,B} = 2.4V$      | -200 |      | 50  | A    |
| A, B Input leakage current high     |                        | $V_{A,B} = 35.3V$     |      |      | 200 | A    |
| Shutdown input current low          |                        | $V_{SHUTDOWN} = 0.4V$ |      | 20   | 100 | A    |
| Shutdown input current high         |                        | $V_{SHUTDOWN} = 2.4V$ |      | 170  | 500 | A    |
|                                     |                        | $V_{SHUTDOWN} = 6.2V$ |      | 0.6  | 1.5 | mA   |
| Enable input current low            |                        | $V_{ENABLE} = 0V$     | -600 | -460 | 200 | A    |
| Enable input current high           |                        | $V_{ENABLE} = 6.2V$   |      |      | 200 | A    |
| Enable threshold rising             |                        |                       |      | 2.8  | 3.6 | V    |
| Enable threshold falling            |                        |                       | 1.0  | 2.4  | 3.4 | V    |
| $V_{IN} - V_{OUT}$                  | Output High Saturation | $I_{OUT} = -50mA$     |      |      | 2.0 | V    |
|                                     |                        | $I_{OUT} = -500mA$    |      |      | 2.5 | V    |
| $V_{OUT}$                           | Output Low Saturation  | $I_{OUT} = 50mA$      |      |      | 0.5 | V    |
|                                     |                        | $I_{OUT} = 500mA$     |      |      | 2.5 | V    |
| Thermal Shutdown                    |                        |                       |      | 155  |     | °C   |

**SWITCHING CHARACTERISTICS (see Figure 1)**

(VIN = 20V, delays measured to 10% output change.)

| PARAMETER                        | TEST CONDITIONS            |               | MIN | TYP | MAX | UNIT |
|----------------------------------|----------------------------|---------------|-----|-----|-----|------|
| <b>FROM A,B INPUT TO OUTPUT:</b> |                            |               |     |     |     |      |
| Rise Time Delay (TPLH)           | CL = 0pF                   |               |     | 25  | 40  | ns   |
|                                  | CL = 1000pF                | UC1708        |     | 25  | 45  | ns   |
|                                  |                            | UC2708/UC3708 |     | 25  | 40  |      |
|                                  | CL = 2200pF                | UC1708        |     | 25  | 50  | ns   |
|                                  |                            | UC2708/UC3708 |     | 25  | 45  |      |
|                                  | 10% to 90% Rise (TTLH)     | CL = 0pF      |     |     | 55  | 75   |
| CL = 1000pF <sup>(1)</sup>       |                            | UC1708        |     | 25  | 80  | ns   |
|                                  |                            | UC2708/UC3708 |     | 25  | 50  |      |
| CL = 2200pF                      |                            | UC1708        |     | 40  | 85  | ns   |
|                                  |                            | UC2708/UC3708 |     | 40  | 55  |      |
| Fall Time Delay (TPHL)           |                            | CL = 0pF      |     |     | 25  | 40   |
|                                  | CL = 1000pF <sup>(1)</sup> |               |     | 25  | 45  |      |
|                                  | CL = 2200pF                |               |     | 35  | 50  |      |
| 90% to 10% Fall (TTHL)           | CL = 0pF                   |               |     | 15  | 20  | ns   |
|                                  | CL = 1000pF <sup>(1)</sup> |               |     | 25  | 45  |      |
|                                  | CL = 2200pF                |               |     | 40  | 55  |      |


(1) These parameters, specified at 1000pF, although ensured over recommended operating conditions, are not tested in production.

**SWITCHING CHARACTERISTICS (see Figure 1)**


(VIN = 20V, delays measured to 10% output change.)

| PARAMETER                             | TEST CONDITIONS  |               | MIN | TYP | MAX | UNIT |
|---------------------------------------|--|---------------|-----|-----|-----|------|
| <b>FROM SHUTDOWN INPUT TO OUTPUT:</b> |  |               |     |     |     |      |
| Rise Time Delay (TPLH)                | CL = 0pF   |               |     | 25  | 75  | ns   |
|                                       | CL = 1000pF <sup>(1)</sup>                             | UC1708        |     | 30  | 80  | ns   |
|                                       |  | UC2708/UC3708 |     | 30  | 75  |      |
|                                       | CL = 2200pF  | UC1708        |     | 35  | 85  | ns   |
|                                       |  | UC2708/UC3708 |     | 35  | 75  |      |
|                                       | 10% to 90% Rise (TTLH)                                 | CL = 0pF      |     |     | 50  | 75   |
| CL = 1000pF <sup>(1)</sup>            |  | UC1708        |     | 25  | 80  | ns   |
|                                       |  | UC2708/UC3708 |     | 25  | 50  |      |
| CL = 2200pF                           |  | UC1708        |     | 40  | 85  | ns   |
|                                       |  | UC2708/UC3708 |     | 40  | 55  |      |
| Fall Time Delay (TPHL)                |  | CL = 0pF      |     |     | 25  | 45   |
|                                       | CL = 1000pF <sup>(1)</sup>                             |               |     | 30  | 50  |      |
|                                       | CL = 2200pF  |               |     | 35  | 55  |      |
| 90% to 10% Fall (TTHL)                | CL = 0pF   |               |     | 25  | 20  | ns   |
|                                       | CL = 1000pF <sup>(1)</sup>                             |               |     | 25  | 45  |      |
|                                       | CL = 2200pF  |               |     | 40  | 55  |      |
| Total Supply Current                  | F = 200kHz, 50% duty cycle, both channels; CL = 0pF    |               |     | 23  | 25  | mA   |
|                                       | F = 200kHz, 50% duty cycle, both channels; CL = 2200pF |               |     | 38  | 45  |      |

(1) These parameters, specified at 1000pF, although ensured over recommended operating conditions, are not tested in production.



**Figure 1. AC Test Circuit and Switching Time Waveforms**



NOTE: Shutdown feature available only in JE, NE or DW Packages.

**Figure 2. Equivalent Input Circuits**

**PACKAGING INFORMATION**

| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| 5962-0051401Q2A  | ACTIVE                | LCCC         | FK              | 20   | 1           | TBD                     | POST-PLATE       | N / A for Pkg Type           |
| 5962-0051401QEA  | ACTIVE                | CDIP         | J               | 16   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| 5962-0051401QPA  | ACTIVE                | CDIP         | JG              | 8    | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| 5962-0051401V2A  | ACTIVE                | LCCC         | FK              | 20   | 1           | TBD                     | POST-PLATE       | N / A for Pkg Type           |
| 5962-0051401VEA  | ACTIVE                | CDIP         | J               | 16   | 1           | TBD                     | A42              | N / A for Pkg Type           |
| 5962-0051401VPA  | ACTIVE                | CDIP         | JG              | 8    | 1           | TBD                     | A42              | N / A for Pkg Type           |
| UC1708J          | ACTIVE                | CDIP         | JG              | 8    | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| UC1708J883B      | ACTIVE                | CDIP         | JG              | 8    | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| UC1708JE         | ACTIVE                | CDIP         | J               | 16   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| UC1708JE883B     | ACTIVE                | CDIP         | J               | 16   | 1           | TBD                     | A42 SNPB         | N / A for Pkg Type           |
| UC1708L883B      | ACTIVE                | LCCC         | FK              | 20   | 1           | TBD                     | POST-PLATE       | N / A for Pkg Type           |
| UC2708D          | OBSOLETE              |              | UTR             |      |             | TBD                     | Call TI          | Call TI                      |
| UC2708DW         | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC2708DWG4       | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC2708DWTR       | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC2708DWTRG4     | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC2708J          | OBSOLETE              |              | UTR             |      |             | TBD                     | Call TI          | Call TI                      |
| UC2708JE         | OBSOLETE              |              | UTR             |      |             | TBD                     | Call TI          | Call TI                      |
| UC2708N          | ACTIVE                | PDIP         | P               | 8    | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |
| UC2708NE         | ACTIVE                | PDIP         | N               | 16   | 25          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |
| UC2708NEG4       | ACTIVE                | PDIP         | N               | 16   | 25          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |
| UC2708NG4        | ACTIVE                | PDIP         | P               | 8    | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |
| UC2708Q          | OBSOLETE              |              | UTR             |      |             | TBD                     | Call TI          | Call TI                      |
| UC3708DW         | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC3708DWG4       | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC3708DWTR       | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC3708DWTRG4     | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR          |
| UC3708N          | ACTIVE                | PDIP         | P               | 8    | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |
| UC3708NE         | ACTIVE                | PDIP         | N               | 16   | 25          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |
| UC3708NEG4       | ACTIVE                | PDIP         | N               | 16   | 25          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |
| UC3708NG4        | ACTIVE                | PDIP         | P               | 8    | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | N / A for Pkg Type           |

| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| UC3708Q          | OBSOLETE              |              | UTR             |      |             | TBD                     | Call TI          | Call TI                      |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.


**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**




**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**



\*All dimensions are nominal

| Device     | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| UC2708DWTR | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.85   | 10.8    | 2.7     | 12.0    | 16.0   | Q1            |
| UC3708DWTR | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.85   | 10.8    | 2.7     | 12.0    | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

| Device     | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------|--------------|-----------------|------|------|-------------|------------|-------------|
| UC2708DWTR | SOIC         | DW              | 16   | 2000 | 346.0       | 346.0      | 33.0        |
| UC3708DWTR | SOIC         | DW              | 16   | 2000 | 346.0       | 346.0      | 33.0        |


J (R-GDIP-T\*\*)

14 LEADS SHOWN

CERAMIC DUAL IN-LINE PACKAGE



| DIM \ PINS ** | 14                     | 16                     | 18                     | 20                     |
|---------------|------------------------|------------------------|------------------------|------------------------|
| A             | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX         | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN         | —                      | —                      | —                      | —                      |
| C MAX         | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN         | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |



4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.


# MECHANICAL DATA

MLCC006B – OCTOBER 1996

## FK (S-CQCC-N\*\*)

## LEADLESS CERAMIC CHIP CARRIER


28 TERMINAL SHOWN



- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a metal lid.
  - The terminals are gold plated.
  - Falls within JEDEC MS-004

DW (R-PDSO-G16)

PLASTIC SMALL-OUTLINE PACKAGE




- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
  - D. Falls within JEDEC MS-013 variation AA.

# MECHANICAL DATA

MPDI001A – JANUARY 1995 – REVISED JUNE 1999

## P (R-PDIP-T8)

## PLASTIC DUAL-IN-LINE




- NOTES: A. All linear dimensions are in inches (millimeters).  
 B. This drawing is subject to change without notice.  
 C. Falls within JEDEC MS-001

# MECHANICAL DATA

MCER001A – JANUARY 1995 – REVISED JANUARY 1997

JG (R-GDIP-T8)

CERAMIC DUAL-IN-LINE




- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a ceramic lid using glass frit.
  - Index point is provided on cap for terminal identification.
  - Falls within MIL STD 1835 GDIP1-T8

# MECHANICAL DATA

## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| <b>Products</b>             |  | <b>Applications</b> |  |
|-----------------------------|--|---------------------|--|
| Amplifiers                  | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             | Audio               | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Data Converters             | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     | Automotive          | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| DSP                         | <a href="http://dsp.ti.com">dsp.ti.com</a>                         | Broadband           | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Clocks and Timers           | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>           | Digital Control     | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Interface                   | <a href="http://interface.ti.com">interface.ti.com</a>             | Medical             | <a href="http://www.ti.com/medical">www.ti.com/medical</a>               |
| Logic                       | <a href="http://logic.ti.com">logic.ti.com</a>                     | Military            | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Power Mgmt                  | <a href="http://power.ti.com">power.ti.com</a>                     | Optical Networking  | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Microcontrollers            | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> | Security            | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
| RFID                        | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>               | Telephony           | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
| RF/IF and ZigBee® Solutions | <a href="http://www.ti.com/lprf">www.ti.com/lprf</a>               | Video & Imaging     | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
|                             |  | Wireless            | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2008, Texas Instruments Incorporated