



[查询WP12供应商](#)[捷多邦，专业PCB打样工厂，24小时加急出货](#)

WP12

12 Watt Single Output Regulated Power Supplies



Features:

N.A. AC input
Fully enclosed plastic case
Fully regulated output
High Efficiency
Warranty: 5 years

Environmental

Operating temperature.....0° C to 40° C
Storage temperature.....-55° C to 85° C
Weight: 0.5 lbs

EMI

Meets FCC class B

Safety

UL 1950
cUL Listed to CSA 22.2 No. 950

Polarity: COM  +V

Electrical specifications

Input

Voltage.....90-132VAC
Current.....0.75A
Frequency.....47-63 Hz
Input connector.....2 Pin NEMA 5/15 plug

Output

Line regulation.....TYP 1%
Load regulation.....5% Max
Set point.....5% of rated output
Hold up time.....12 ms min. at full load 115 V

Over voltage protection.....Built-in
Over current protection.....Built-in
Short circuit protection.....Pulsing Mode, auto recovery
Ripple/noise(Vp-p).....1%
Output connector.....barrel type(5.5 x 2.5 x 9.5mm)

Output Electrical Specifications

Model No.	Voltage	Power	Current
WP1205-760	5	12	2.4A
WP1212-760	12	12	1A
WP1215-760	15	12	0.8A
WP1218-760	18	12	0.67A
WP1224-760	24	12	0.5A

[Quality Power Supplies](#) | [Agency Certifications](#) | [Output Connectors](#) | [Custom Requests](#) | [About Us](#) | [Quality Management Team](#) | [Job Opportunities](#) | [Elpac News](#) | [Sales Representatives](#) | [Distributors](#) | [Catalog Request](#)
[Power Supplies](#) | [External Power Supplies](#) | [Open Frame Power Supplies](#) | [Medical Power Supplies](#) | [Custom](#)