


1 Amp Schottky Rectifier

1N5817G, 1N5818G, 1N5819G



Dim.	Inches		Millimeter		Notes
	Minimum	Maximum	Minimum	Maximum	
A	.081	.107	2.057	2.718	Dia.
B	1.10	---	27.94	---	
C	.160	.205	4.064	5.207	
D	.028	.034	.711	.864	Dia.

GLASS HERMETIC DO41

- Schottky Barrier Rectifier
- Guard Ring Protection
- Low Forward Voltage
- High Reliability
- High Current Capability

Microsemi Catalog Number	Working Peak Reverse Voltage	Repetitive Peak Reverse Voltage
1N5817G	20V	20V
1N5818G	30V	30V
1N5819G	40V	40V

Electrical Characteristics

		5817G	5818G	5819G	
Average forward current	I _{F(AV)}	1A	1A	1A	R _{θJL} = 15°C/W, L = 1/4"
Ambient Temperature		135°C	130°C	130°C	8.3ms, half sine, T _J = 150°C
	I _{FSM}	50A	50A	50A	I _{FM} = 0.1A: T _J = 25°C*
Maximum surge current	V _{FM}	.36V	.39V	.39V	I _{FM} = 1.0A: T _J = 25°C*
Max peak forward voltage	V _{FM}	.45V	.55V	.55V	I _{FM} = 3.0A: T _J = 25°C*
Max peak forward voltage	V _{FM}	.65V	.85V	.85V	V _{RRM} , T _J = 25°C
Max peak forward voltage	I _{RM}	1mA	1mA	1mA	V _R = 5.0V, T _J = 25°C
Max peak reverse current	C _J	105pF	50pF	50pF	
Typical junction capacitance					

*Pulse test: Pulse width 300 μsec, Duty cycle 2%

Thermal and Mechanical Characteristics

Storage temperature range	T _{STG}	-65°C to 150°C
Operating junction temp range	T _J	-65°C to 150°C
Maximum thermal resistance	L = 1/4" R _{θJL}	15°C/W Junction to Lead
Weight		.012 ounces (0.38 grams) typical

1N5818G & 1N5819G

Figure 1
Typical Forward Characteristics




Figure 3
Typical Junction Capacitance





Figure 2
Typical Reverse Characteristics



1N5817G

Figure 1
Typical Forward Characteristics




Figure 3
Typical Junction Capacitance




Figure 2
Typical Reverse Characteristics

