


查询1N708A供应商

捷多邦 专业PCB打样工厂 24小时加急出货

Central Semiconductor Corp.
 Central Semiconductor Corp.
 Central Semiconductor Corp.
Central™ Semiconductor Corp.
 145 Adams Avenue
 Hauppauge, New York 11788



145 Adams Avenue, Hauppauge, NY 11788 USA
 Tel: (631) 435-1110 • Fax: (631) 435-1824

1N708A THRU 1N745A

400mW ZENER DIODE
 5% TOLERANCE

JEDEC DO-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N708A series types are Hermetically Sealed Axial Lead Silicon Zener Diodes.

MAXIMUM RATINGS (T_A=25°C)

	SYMBOL	UNIT
Power Dissipation	P _D	400 mW
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 TO +200 °C

TYPE	ZENER VOLTAGE V _Z @ I _{ZT} (VOLTS)	TEST CURRENT		ZENER IMPEDANCE Z _Z @ I _{ZT} (Ω)
		I _{ZT} (mA)		
1N708A	5.6	25		3.6
1N709A	6.2	25		4.1
1N710A	6.8	25		4.7
1N711A	7.5	25		5.3
1N712A	8.2	25		6.0
1N713A	9.1	12		7.0
1N714A	10	12		8.0
1N715A	11	12		9.0
1N716A	12	12		10
1N717A	13	12		11
1N718A	15	12		13
1N719A	16	12		15
1N720A	18	12		17
1N721A	20	4.0		20
1N722A	22	4.0		24
1N723A	24	4.0		28
1N724A	27	4.0		35
1N725A	30	4.0		42
1N726A	33	4.0		50
1N727A	36	4.0		60
1N728A	39	4.0		70
1N729A	43	4.0		84
1N730A	47	4.0		98
1N731A	51	4.0		115
1N732A	56	4.0		140
1N733A	62	2.0		170
1N734A	68	2.0		200
1N735A	75	2.0		240
1N736A	82	2.0		280
1N737A	91	1.0		340
1N738A	100	1.0		400
1N739A	110	1.0		490
1N740A	120	1.0		570
1N741A	130	1.0		650
1N742A	150	1.0		860
1N743A	160	1.0		970

