

查询6778供应商

捷多邦, 专业

6778 PCB打样上

, 24小时加急出货

HDSL


Line Transformer

6778 FILTRAN


- Complaint with Globespan chip sets
- Designed to reflect 135 Ω line side, 8.4 Ω IC side
- Extended temperature range -40°C to +85°C




MECHANICAL (All dimensions in inches)




SUGGESTED PAD LAYOUT



SCHEMATIC



.0935X.094



ELECTRICAL SPECIFICATION @ 25°C

Part Number	L	L	L _L	DCR $\pm 10\%$			Turns Ratio $\pm 1\%$	Hipot	C _{ww}	Return Loss	Insertion Loss	Frequency Response	Longitudinal Balance
	@ 10kHz, 00°C (mH)	@ 10kHz, 100mADC (mH)	@ 100 KHz (μ H)	1-4 (Ω)	2-5 (Ω)	9-7 (Ω)	10kHz	VAC	100kHz (pF MAX)	40kHz-500kHz (dB MIN)	@ 100kHz (dB MAX)	40kHz-1MHz (dB MAX)	40kHz-500kHz (dB MAX)
6778	2.07	2.07	15.00	1.45	1.45	0.45	4 : 1	1,875	65.00	15.00	0.50	± 1.00	55.00

