

查询8630供应商

捷多邦 专业

T3/DS3/E3/STS-1


Dual Input Transformers

8630-8632

PCB打样工


, 24小时加急出货

- Models matched to leading transceiver ICs
- Return Loss requirements of G.703 exceed
- 1500 Vrms isolation per UL1459 and UL1950
- Extended operating temperature range of -40°C to +85°C




Mechanical and Schematic (All dimensions in inches)



SUGGESTED PAD LAYOUT



SCHEMATIC 1



SCHEMATIC 2



SCHEMATIC 3

ELECTRICAL SPECIFICATION @ 25°C

Part Number	Turns Ratio (±2%)		OCL Primary @ 25°C (μH MIN)		OCL Primary @ -40°C (μH MIN)		L _L (μH MAX)		C _{WV} (pF MAX)		Isolation Voltage (Vrms MIN)	Schematic	Primary Pins	
	TX	RX	TX	RX	TX	RX	TX	RX	TX	RX			TX	RX
8630	1:2CT	1:1	40	100	19	40	.100	.110	10	10	1500	1	16-14	6-8
8631	1:2CT	1:1	40	100	40	40	.110	.110	10	10	1500	2	6-8	16-15
8632	1:2CT	1:1	40	100	40	40	.110	.110	10	10	1500	3	7-8	16-15

