


## Rail Mounted Terminal Blocks

### 0456360000

ASK 1

When good enough just isn't good enough

**Weidmüller**[Email to a Friend](#)[View Catalog Page](#)

Representative Photo

#### Technical Information

Clamping Type	Screw Clamp
Series	W Series
Rail Type	TS 35
Function	Disconnect
Configuration	Lever
Wire Size	#22...12 AWG
Current	15 A
Voltage	300 V
Color/Material	Beige PA

#### Technical Data

	UL	CSA	VDE
Rated Voltage	300 V	300 V	500 V
Rated Current	15 A	10.0 A	6.3 A
Wire Size	#22...12 AWG	#26...12 AWG	4 mm <sup>2</sup>

#### Additional Data

Width/Length/Height mm (in.)	8/58/44 (.31"/2.28"/1.73")
Insulation Stripping Length mm (in.)	9 (.35")
Torque Nm (lb. in)	0.9 (8.0)
Clamping Screw	M 3
Flammability Class	UL 94 (V2)

#### Suggested Accessories

DIN-rail  
Ferrules  
Markers (SchT)  
Marking pens  
Marking system (WS/ZS)  
Marking tags (DEK)

Mounting brackets

Tools

找PDF  
维库一下  
pdf.dzsc.com

**Product Liability** The above information describes our products. It does not constitute guaranteed properties and is not intended to a the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot be completely ruled out. Techni data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from

Weidmüller - North America  
United States 001 (800) 849-9343  
Canada 001 (800) 268-4080

or

Weidmüller - Germany  
Telephone operator 0049 (-5252) 960-0