




FLIR LEPTON[®]

Longwave Infrared (LWIR) Camera Module

The FLIR Lepton is an LWIR camera solution that is smaller than a dime, can fit inside a cell phone, and is ten times less expensive than a traditional IR camera. Using a focal plane array (FPA) of 80 × 60 active pixel, Lepton easily integrates into native mobile-devices and other electronics as an IR sensor or thermal imager.

ENHANCED IR SENSOR

Greater sensitivity than common thermopile arrays

- Thermal sensitivity <50 mK
- Optional temperature-stable output to support radiometric processing
- Low operating power, 150mW
- Low power standby mode

MICRO THERMAL IMAGER

Uncooled thermal imaging for small electronics

- Integrated digital thermal image processing
- Multiple lens options: 50° / 25° FOV
- Shutter option available
- Fast time to image (<0.5 seconds)





EASE OF INTEGRATION

Simplifies development and manufacturing of thermal-enabled devices

- 8.5 x 8.5 x 5.6 mm package
- Export Compliant (<9Hz)
- MIPI and SPI video interfaces
- Uses standard cell phone-compatible power supplies
- Two-wire serial control interface
- 32-pin socket interface to connector

Specifications

Overview	LEPTON 50° shutterless	LEPTON 25°	LEPTON 50° w/shutter
Sensor technology	Uncooled VOx microbolometer		
Spectral range	Longwave infrared, 8 μm to 14 μm		
Array format	80 × 60, progressive scan		
Pixel size	17 μm		
Effective frame rate	8.6 Hz (exportable)		
Thermal sensitivity	<50 mK (0.050° C)		
Temperature compensation	Automatic. Output image independent of camera temperature.		
Non-uniformity corrections	Shutterless, automatic (with scene motion)		Automatic with shutter
Image optimization	Factory configured and fully automated		
FOV - horizontal	51°	25°	51°
FOV - diagonal	63.5°	31.3°	63.5°
Output format	User-selectable 14-bit, 8-bit (AGC applied), or 24-bit RGB (AGC and colorization applied)		
Solar protection	Integral		
Electrical			
Input clock	25-MHz nominal, CMOS IO Voltage Levels		
Video data interface	Video over SPI		
Control port	CCI (I2C-like), CMOS IO Voltage Levels		
Input supply voltage (nominal)	2.8 V, 1.2 V, 2.5 V to 3.1 V IO		
Power dissipation	Nominally 150 mW at room temperature (operating), 4 mW (standby)		
Mechanical			
Package dimensions – socket version	8.5 × 8.5 × 5.6 mm (w × l × h)		
Weight	0.55 grams (typ)	0.55 grams (typ)	0.55 grams (typ)
Environmental			
Optimum operating temperature range	-10 °C to +65 °C		
Non-operating temperature range	-40 °C to +80 °C		
Shock	1500 G @ 0.4 ms		



SANTA BARBARA

FLIR Systems, Inc.
70 Castilian Drive
Goleta, CA 93117
USA
PH: +1 805.964.9797

PORTLAND

Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

EUROPE

FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

CHINA – SHANGHAI

FLIR Systems, Co., Ltd.
K301-302, No.26 Lane
168, Daduhe Road,
Putuo District, Shanghai
200062, P.R.China
PH: +86-21-5169 7628

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2014 FLIR Systems, Inc. All rights reserved. (Updated 061215)