


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00028	Connector, dc plug, 4.75x1.7xL20 mm, EIAJ-3, molding style, spring contacts	1	
2	30-00003	Wire, 2C BC, 24 AWG, UL2468, 300V, 80C, 3.6 mm, VW-1, PVC, 76A	1	
3	24-00001	Overmold, PVC, black	1	



Wiring diagram	
50-00028	Wire Color
Center	Black with stripe
Sleeve	Black

REVISION	DATE	DESCRIPTION	PREPARED:	NOTES RoHS and REACH compliant Function test: no open, no reversed polarity, no short circuit, no INT 4 A, 12 Vdc Functionally equivalent components may be used	TENSILITY 20802 Sockeye Place #130 Bend, OR 97701 USA tel 541.323.3228 fax 541.323.4202 800 877.670.7118 www.tensility.com			
A	6/27/2012	Initial release	VERIFIED:					
			DIMENSIONS ARE IN MILLIMETERS	DESCRIPTION: Cable, 1830 mm, 4.75x1.7x9.5 mm 50-00028 dc plug to stripped tinned, 24 AWG, 30-00003 wire	SIZE	PART NUMBER		
			TOLERANCES: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm		A	10-01078		
					SCALE: 1:1	WEIGHT:	SHEET 1 OF 1	