

Protect It! 6-Outlet Industrial Safety Surge Protector, 6-ft. Cord, 900 Joules, Outlet Covers

MODEL NUMBER: TLM626SA



Highlights

- 6 outlets (including transformer outlets and 4 safety covers)
- 6 ft. cord
- 900 joule rating
- Rugged metal case
- \$10,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Package Includes

- TLM626SA SAfety Surge Suppressor
- 4 safety covers
- Owner's manual

Description

This Tripp Lite surge suppressor is designed to provide safe, reliable surge protection in harsh environments. A 900 joule rating can protect connected equipment against even the strongest surges. 6 outlets protect connected equipment against damaging surges, spikes and line noise. Convenient transformer outlets accommodate multiple transformers without blocking other outlets. A 6 ft. grounded cord reaches distant outlets. A lighted on/off switch with integrated circuit breaker provides power control over connected equipment. Breaker protects against dangerous system overload. Protected LED confirms that connected equipment is being protected. 4 safety covers shield unused outlets from debris and accidental contact. A rugged metal case stands up to the harshest environments. Integrated keyhole slots on bottom panel provide convenient wall/desk mounting. Tripp Lite will repair or replace any connected equipment damaged by surges, including direct lightning strikes, up to \$10,000 and for life! As an added safety feature, the surge suppressor's bright yellow color alerts you and others that power cords and tools are in use.

Features

- 6 outlets protect connected equipment against damaging surges, spikes and line noise
- . 6-ft. grounded cord reaches distant outlets
- Lighted ON/OFF switch with integrated circuit breaker provides power control over connected equipment. Breaker protects against dangerous system overload.
- Protected LED If this green LED ever goes out, Tripp Lite will replace your surge suppressor under warranty at no charge!
- · Convenient transformer outlets accommodate multiple transformers without blocking other outlets.
- 4 safety covers shield unused outlets from debris and accidental contact.
- · Rugged metal case stands up to the harshest environments.
- Integrated keyhole slots on bottom panel provide convenient wall/desk mounting.
- 900 joules of surge protection
- OSHA color guidelines, outlined in Document 1910.145, alert users to hazardous situations, which may cause minor or moderate injury. This Tripp Lite
 product complies with those guidelines.
- \$10,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised



Specifications

Output Receptacles (6) Circuit Breaker (amps) 15 Overload Protection Co Transformer Accommodation Yes Outlet Safety Covers Yes	ombo power switch and circuit breaker es (2) es (4) single row of 6	
Output Receptacles (6) Circuit Breaker (amps) 15 Overload Protection Co Transformer Accommodation Yes Outlet Safety Covers Yes	5) 5-15R 5 combo power switch and circuit breaker es (2) es (4) single row of 6	
Circuit Breaker (amps) 15 Overload Protection Co Transformer Accommodation Yes Outlet Safety Covers Yes	ombo power switch and circuit breaker es (2) es (4) single row of 6	
Overload Protection Co Transformer Accommodation Yes Outlet Safety Covers Yes	ombo power switch and circuit breaker es (2) es (4) single row of 6	
Transformer Accommodation Yes Outlet Safety Covers Yes	es (2) es (4) single row of 6	
Outlet Safety Covers Ye	es (4) single row of 6	
	single row of 6	
Outlet Orientation 1 s		
	es	
Right-Angle Outlets Yes		
INPUT		
Nominal Input Voltage(s) Supported 120	20V AC	
Recommended Electrical Service 120	20V (110-125V)	
Input Connection Type NE	EMA 5-15P	
Input Cord Length (ft.) 6		
Input Cord Length (m) 1.8	83	
Input Cord Gauge Type 14	4 gauge, SJT	
Voltage Compatibility (VAC) 120	20	
Maximum Surge Amps 450	5000	
Right-Angle Plug No	0	
USER INTERFACE, ALERTS & CONTROLS		
Switches Lig	ighted on/off power switch	
Diagnostic LED Details 1 g	green "protected" LED confirms surge suppression is present	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating 900	00	
AC Suppression Response Time < 1	1 ns	
Protection Modes Inc	ncludes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression	
Clamping Voltage (RMS) 150	50V	
EMI / RFI Filtering Up	p to 20 dB	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection No	0	





Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Shipping Dimensions (hwd / in.)	13.61 x 4.97 x 2.01
Shipping Dimensions (hwd / cm)	34.57 x 12.62 x 5.11
Shipping Weight (lbs.)	1.70
Shipping Weight (kg)	0.77
Unit Dimensions (hwd / in.)	12.23 x 2.30 x 1.28
Unit Dimensions (hwd / cm)	31.06 x 5.84 x 3.25
Unit Weight (lbs.)	1.46
Unit Weight (kg)	0.66
Material of Construction	Metal
Integrated Keyhole Mounting Tabs	Yes
Receptacle Color	black
Color (AC Line Cord)	yellow
Outlets Measurement (Center to Center)	Distance between standard outlets = 30.40mm; Distance between transformer and standard outlets = 45mm
Keyhole Slot Mounting Measurement (Center to Center)	155mm
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
cUL / CSA (Canada)	cUL
Approvals	cULus, RoHS
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies