

## Wirewound Resistor, Open Style, Current Shunts, Very Low Value



### FEATURES

- Extremely low resistance values for current sensing applications
- Low temperature coefficients (down to 100 ppm/°C)
- Complete welded construction
- Material categorization:  
For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



### STANDARD ELECTRICAL SPECIFICATIONS

| GLOBAL MODEL <sup>(1)</sup> | HISTORICAL MODEL | TOLERANCE <sup>(2)</sup><br>% | RESISTANCE RANGE<br>Ω |
|-----------------------------|------------------|-------------------------------|-----------------------|
| MRS-1298...xx               | MRS1298xx        | 1, 5, 10                      | 0.001 to 0.050        |
| MRS-1367...xx               | MRS1367xx        | 1, 5, 10                      | 0.001 to 0.100        |
| MRS-1375...xx               | MRS1375xx        | 1, 5, 10                      | 0.001 to 0.010        |
| MRS-1510...xx               | MRS1510xx        | 1, 5, 10                      | 0.001 to 0.500        |

#### Notes

<sup>(1)</sup> The xx is for the two digit "special" number as described in Dimensions tables MRS-1298, MRS-1367, MRS-1375, and MRS-1510.

<sup>(2)</sup> Other tolerances may be available, contact factory.

### TECHNICAL SPECIFICATIONS

| PARAMETER                   | UNIT   | MRS RESISTOR CHARACTERISTICS                                                                   |
|-----------------------------|--------|------------------------------------------------------------------------------------------------|
| Temperature Coefficient     | ppm/°C | Typical is ± 100 (- 10 °C to + 80 °C) consult factory if application is TC sensitive           |
| Maximum Current Rating      | A      | Dependent upon configuration, see Dimensions tables MRS-1298, MRS-1367, MRS-1375, and MRS-1510 |
| Operating Temperature Range | °C     | - 55 to + 275                                                                                  |


### GLOBAL PART NUMBER INFORMATION

Global Part Numbering example: MRS-1298R010JE1401 (visit [www.vishay.net](http://www.vishay.net) Vishay Dale parts numbering manual for all options)


|                                                                          |   |   |   |                                                                            |   |   |   |                                      |   |                              |   |   |                                                 |   |   |   |   |
|--------------------------------------------------------------------------|---|---|---|----------------------------------------------------------------------------|---|---|---|--------------------------------------|---|------------------------------|---|---|-------------------------------------------------|---|---|---|---|
| M                                                                        | R | S | - | 1                                                                          | 2 | 9 | 8 | R                                    | 0 | 1                            | 0 | J | E                                               | 1 | 4 | 0 | 1 |
| GLOBAL MODEL<br>(8 digits)                                               |   |   |   | VALUE<br>(4 digits)                                                        |   |   |   | TOLERANCE<br>(1 digit)               |   | PACKAGING CODE<br>(3 digits) |   |   | SPECIAL<br>(2 digits)                           |   |   |   |   |
| (See Standard Electrical Specifications Global Model column for options) |   |   |   | L = mΩ<br>(below 0.01 Ω)<br>R = Decimal<br>5L00 = 0.005 Ω<br>R010 = 0.01 Ω |   |   |   | F = ± 1 %<br>J = ± 5 %<br>K = ± 10 % |   | E14 = Bulk pack              |   |   | (Dash Number)<br>From 01 to 99<br>as applicable |   |   |   |   |

Historical Part Number example: MRS129801J


|                  |           |            |
|------------------|-----------|------------|
| <b>MRS1298</b>   | <b>01</b> | <b>5 %</b> |
| HISTORICAL MODEL | SIZE      | TOLERANCE  |

**DIMENSIONS** in inches [millimeters]

**MRS-1298**

| GLOBAL MODEL SPECIAL | RESISTANCE $\Omega$ | CURRENT RATING (MAXIMUM) A | DIMENSION H   |
|----------------------|---------------------|----------------------------|---------------|
| 01                   | 0.010               | 25                         | 0.750 [19.05] |
| 02                   | 0.005               | 25                         | 0.750 [19.05] |
| 03                   | 0.003               | 25                         | 0.580 [14.73] |
| 04                   | 0.001               | 25                         | 0.400 [10.16] |
| 05                   | 0.050               | 10                         | 0.700 [17.78] |
| 06                   | 0.010               | 15                         | 0.350 [9.89]  |
| 07                   | 0.005               | 15                         | 0.350 [9.89]  |
| 08                   | 0.002               | 15                         | 0.400 [10.16] |
| 09                   | 0.00382             | 15                         | 0.350 [9.89]  |
| 10                   | 0.013               | 15                         | 1.000 [25.40] |
| 11                   | 0.033               | 15                         | 0.600 [15.24] |
| 12                   | 0.025               | 15                         | 0.400 [10.16] |
| 13                   | 0.033               | 15                         | 0.875 [22.22] |
| 14                   | 0.008               | 15                         | 0.685 [17.40] |
| 15                   | 0.020               | 10                         | 0.300 [7.62]  |
| 16                   | 0.050               | 15                         | 0.600 [15.24] |
| 17                   | 0.004               | 25                         | 0.500 [12.70] |
| 18                   | 0.010               | 15                         | 0.350 [9.89]  |


**MRS-1367**

| GLOBAL MODEL SPECIAL | RESISTANCE $\Omega$ | CURRENT RATING (MAXIMUM) A | DIMENSION H TYPICAL | DIMENSION CC  | DIMENSION H <sub>1</sub> TYPICAL |
|----------------------|---------------------|----------------------------|---------------------|---------------|----------------------------------|
| 03                   | 0.050               | 10                         | 0.750 [19.05]       | 1.500 [38.10] | 0.500 [12.70]                    |
| 04                   | 0.010               | 15                         | 0.750 [19.05]       | 0.900 [22.86] | 0.625 [15.88]                    |
| 05                   | 0.020               | 10                         | 0.500 [12.70]       | 0.750 [19.05] | 0.375 [9.53]                     |
| 06                   | 0.025               | 10                         | 0.625 [15.88]       | 0.750 [19.05] | 0.500 [12.70]                    |
| 07                   | 0.040               | 10                         | 0.800 [20.32]       | 0.812 [20.62] | 0.675 [17.15]                    |
| 08                   | 0.050               | 8                          | 0.500 [12.70]       | 0.960 [24.38] | 0.375 [9.53]                     |
| 09                   | 0.070               | 8                          | 0.650 [16.51]       | 1.300 [33.02] | 0.525 [13.34]                    |
| 10                   | 0.070               | 10                         | 0.800 [20.32]       | 1.600 [40.64] | 0.675 [17.15]                    |
| 11                   | 0.005               | 15                         | 0.750 [19.05]       | 0.750 [19.05] | 0.550 [13.97]                    |
| 12                   | 0.033               | 8                          | 0.500 [12.70]       | 0.400 [10.16] | 0.325 [8.26]                     |
| 13                   | 0.025               | 10                         | 0.475 [12.07]       | 0.960 [24.38] | 0.350 [9.89]                     |
| 14                   | 0.015               | 10                         | 0.750 [19.05]       | 1.500 [38.10] | 0.625 [15.88]                    |
| 15                   | 0.050               | 10                         | 0.625 [15.88]       | 1.080 [27.43] | 0.500 [12.70]                    |
| 16                   | 0.100               | 6.5                        | 0.620 [15.75]       | 0.625 [15.88] | 0.400 [10.16]                    |
| 17                   | 0.020               | 12.5                       | 0.500 [12.70]       | 0.600 [15.24] | 0.375 [9.53]                     |
| 18                   | 0.025               | 15                         | 0.540 [13.72]       | 0.800 [20.32] | 0.415 [10.54]                    |
| 21                   | 0.030               | 10                         | 0.725 [18.42]       | 0.750 [19.05] | 0.525 [13.34]                    |
| 25                   | 0.022               | 10                         | 0.710 [18.03]       | 0.620 [15.75] | 0.510 [12.95]                    |

**DIMENSIONS** in inches [millimeters]


| <b>MRS-1375</b>      |                     |                            |               |               |               |              |
|----------------------|---------------------|----------------------------|---------------|---------------|---------------|--------------|
| GLOBAL MODEL SPECIAL | RESISTANCE $\Omega$ | CURRENT RATING (MAXIMUM) A | DIMENSION L   | DIMENSION H   | DIMENSION CC  | DIMENSION LD |
| 01                   | 0.001               | 30                         | 0.750 [19.05] | 0.500 [12.70] | 0.500 [12.70] | 0.080 [2.03] |
| 02                   | 0.002               | 40                         | 1.700 [43.18] | 0.500 [12.70] | 0.500 [12.70] | 0.080 [2.03] |
| 03                   | 0.003               | 40                         | 1.700 [43.18] | 0.500 [12.70] | 0.500 [12.70] | 0.080 [2.03] |
| 04                   | 0.001               | 40                         | 1.700 [43.18] | 0.500 [12.70] | 0.500 [12.70] | 0.080 [2.03] |
| 05                   | 0.002               | 30                         | 1.250 [31.75] | 0.750 [19.05] | 0.500 [12.70] | 0.080 [2.03] |
| 06                   | 0.004               | 30                         | 1.250 [31.75] | 0.750 [19.05] | 0.500 [12.70] | 0.080 [2.03] |
| 07                   | 0.00166             | 35                         | 1.600 [40.64] | 0.500 [12.70] | 0.500 [12.70] | 0.080 [2.03] |
| 09                   | 0.005               | 40                         | 2.865 [72.77] | 0.750 [19.05] | 0.500 [12.70] | 0.080 [2.03] |
| 10                   | 0.010               | 20                         | 1.400 [35.56] | 0.750 [19.05] | 0.500 [12.70] | 0.080 [2.03] |
| 11                   | 0.004               | 30                         | 1.200 [30.48] | 0.400 [10.16] | 0.500 [12.70] | 0.080 [2.03] |
| 13                   | 0.001               | 40                         | 1.250 [31.75] | 0.750 [19.05] | 0.500 [12.70] | 0.080 [2.03] |

| <b>MRS-1510</b>      |                     |                            |              |               |               |              |
|----------------------|---------------------|----------------------------|--------------|---------------|---------------|--------------|
| GLOBAL MODEL SPECIAL | RESISTANCE $\Omega$ | CURRENT RATING (MAXIMUM) A | DIMENSION L  | DIMENSION H   | DIMENSION CC  | DIMENSION LD |
| 01                   | 0.050               | 15                         | 1.00 [25.40] | 0.400 [10.16] | 0.215 [5.46]  | 0.057 [1.45] |
| 02                   | 0.003               | 25                         | 1.10 [27.94] | 0.355 [9.02]  | 0.200 [5.08]  | 0.040 [1.02] |
| 03                   | 0.0015              | 40                         | 1.10 [27.94] | 0.380 [9.65]  | 0.270 [6.86]  | 0.081 [2.06] |
| 04                   | 0.001               | 40                         | 1.00 [25.40] | 0.500 [12.70] | 0.300 [7.62]  | 0.081 [2.06] |
| 05                   | 0.002               | 30                         | 1.25 [31.75] | 0.750 [19.05] | 0.375 [9.53]  | 0.080 [2.03] |
| 06                   | 0.001               | 80                         | 2.19 [55.63] | 0.625 [15.87] | 0.625 [15.87] | 0.128 [3.25] |

**MATERIAL SPECIFICATIONS**

**Element:** Copper-nickel alloy or nickel-chrome alloy, depending on resistance value


**Coating:** Silicone, when requested

**Standard Terminals:** Tinned copper

**Part Marking:** None

**AMBIENT TEMPERATURE DERATING**

Derating is required for ambient temperatures above 25 °C per the following graph:

**DERATING**




## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.