



**Is Now Part of**



**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)**

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.



June 2016



## FSA850

### Audio 3-Pole / 4-Pole MIC-GND Switch

#### Features

|                                 |                         |
|---------------------------------|-------------------------|
| Switch Type                     | 3-Pole/4-Pole MIC - GND |
| V <sub>CC</sub>                 | 2.3 to 4.5 V            |
| THD (MIC)                       | 0.001% Typical          |
| ESD                             |                         |
| IEC 61000-4-2 (Air Gap)         | 15 kV                   |
| IEC 61000-4-2 (Contact)         | 8 kV                    |
| HBM (All Pins)                  | 3 kV                    |
| GNDnA/GNDnB to GND              | 8 kV                    |
| Power to GND                    | 10 kV                   |
| CDM                             | 2 kV                    |
| Operating Temperature           | -40°C to 85°C           |
| R <sub>ON</sub> Maximum (GND1n) | 0.08 Ω                  |
| R <sub>ON</sub> Maximum (SENSE) | 1 Ω                     |

#### Applications

- 3.5 mm and 2.5 mm Audio Jacks
- Cellular Phones, Smart Phones
- MP3 and PMP (Portable Media Player)

#### Description

The FSA850 is a 3-pole or 4-pole audio jack microphone GND switch for accessories with General-Purpose Input / Output (GPIO) control signals. The FSA850 also has the ability to perform 4-pole cross-point switching to support Open Mobile Terminal Platform (OMTP) 4-pole headset plugs. The architecture is designed to replace discrete MOSFET solutions and allow common third-party headphones to be used for listening to music or playing video from mobile handsets, personal media players, and portable peripheral devices.

- Supports 4-Pole OMTP Cross Point Switching for GND Connection
- Integrates a MIC switch for 3- or 4-Pole Configuration Headset Plugs
- Reduces “Pop and Click” Caused by Microphone Bias

#### Ordering Information

| Part Number | Operating Temperature Range | Top Mark | Package                                                                              | Packing Method            |
|-------------|-----------------------------|----------|--------------------------------------------------------------------------------------|---------------------------|
| FSA850UCX   | -40 to +85°C                | M5       | 12-Ball, Wafer-Level Chip-Scale Package (WLCSP), 3x4 Array, 0.4mm Pitch, 250 μm Ball | 3000 units on Tape & Reel |

## Typical Application




Figure 1. Typical Mobile Application

## Analog Symbol




Figure 2. Analog Symbol

Table 1. Functional Truth Table

| S0 | S1 | GND                   | SENSE                 | MIC       |
|----|----|-----------------------|-----------------------|-----------|
| 0  | 0  | MIC/GND1A             | MIC/GND2A             | MIC/GND2B |
| 0  | 1  | HIGH-Z                | HIGH-Z                | HIGH-Z    |
| 1  | 0  | MIC/GND1A & MIC/GND1B | MIC/GND2A & MIC/GND2B | HIGH-Z    |
| 1  | 1  | MIC/GND1B             | MIC/GND2B             | MIC/GND2A |

## Pin Assignments




Figure 3. Pin Assignments (Top Through View, Top Mark Side)

## Pin Descriptions

| Name            | Ball #   | Type   | Description                                      |
|-----------------|----------|--------|--------------------------------------------------|
| MIC             | A2       | Switch | Microphone, connects to microphone pre-amplifier |
| SENSE           | A3       | Switch | Sense pin to detect GND offset                   |
| S0, S1          | B3, B1   | Input  | MIC, SENSE, and MIC/GNDn switch-select pin       |
| MIC/GND1A       | D3       | Switch | GND switch, connects to pole 3 of audio jack     |
| MIC/GND2A       | C3       | Switch | GND switch, connects to pole 3 of audio jack     |
| MIC/GND1B       | D1       | Switch | GND switch, connects to pole 4 of audio jack     |
| MIC/GND2B       | C1       | Switch | GND switch, connects to pole 4 of audio jack     |
| V <sub>CC</sub> | A1       | Power  | Supply voltage                                   |
| GND             | B2,C2,D2 | Ground | Ground for both the audio jack and PCB           |

## Absolute Maximum Ratings

Stresses exceeding the Absolute Maximum Ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol             | Parameter                                                                         |                                                         | Min. | Max.         | Unit |
|--------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------|------|--------------|------|
| $V_{CC}$           | Supply Voltage from Battery                                                       |                                                         | -0.5 | +5.5         | V    |
| $V_{CNTRL}$        | Control Input Voltage (S0, S1)                                                    |                                                         | -0.5 | $V_{CC}$     | V    |
| $V_{SWM}, V_{SWG}$ | Switch I/O Voltage (SENSE, MIC, MIC/GND1A, MIC/GND2A, MIC/GND1B, MIC/GND2B)       |                                                         | -0.5 | $V_{CC}+0.5$ | V    |
| $I_{IK}$           | Input Clamp Diode Current <sup>(1)</sup>                                          |                                                         | -50  |              | mA   |
| $I_{SW}$           | Switch I/O Current (Continuous) <sup>(1)</sup> (SENSE, MIC, MIC/GND2A, MIC/GND2B) |                                                         |      | 50           | mA   |
| $I_D$              | GND Switch I/O Current (Continuous) <sup>(1)</sup> (MIC/GND1A, MIC/GND1B)         |                                                         |      | 300          | mA   |
| $T_{STG}$          | Storage Temperature Range                                                         |                                                         | -65  | +150         | °C   |
| $T_J$              | Maximum Junction Temperature                                                      |                                                         |      | +150         | °C   |
| $T_L$              | Lead Temperature (Soldering, 10 Seconds)                                          |                                                         |      | +260         | °C   |
| ESD                | IEC 61000-4-2 System ESD                                                          | Air Gap                                                 |      | 15           | kV   |
|                    |                                                                                   | Contact                                                 |      | 8            |      |
|                    | Human Body Model, JEDEC JESD22-A114                                               | All Other Pins (S0,S1, SENSE, MIC)                      |      | 3            |      |
|                    |                                                                                   | I/O to GND (MIC/GND1A, MIC/GND2A, MIC/GND1B, MIC/GND2B) |      | 8            |      |
|                    |                                                                                   | Power to GND                                            |      | 10           |      |
|                    | Charged Device Model, JEDEC JESD22-C101                                           | All Pins                                                |      | 2            |      |

### Note:

1. The input and output negative ratings may be exceeded if the input and output diode current ratings are observed.

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

| Symbol      | Parameter                                                              | Min. | Max.     | Unit |
|-------------|------------------------------------------------------------------------|------|----------|------|
| $V_{CC}$    | Battery Supply Voltage                                                 | 2.3  | 4.5      | V    |
| $V_{CNTRL}$ | Control Input Voltage (S0, S1)                                         | 0    | $V_{CC}$ | V    |
| $V_{SWM}$   | Switch I/O Voltage (MIC)                                               | 0    | $V_{CC}$ | V    |
| $V_{SWG}$   | Switch I/O Voltage (SENSE, MIC/GND1A, MIC/GND2A, MIC/GND1B, MIC/GND2B) | 0    | 1.0      | V    |
| $T_A$       | Operating Temperature                                                  | -40  | +85      | °C   |

## DC Electrical Characteristics

All typical values are at  $T_A = 25^\circ\text{C}$  and  $V_{CC} = 3.3\text{V}$  unless otherwise specified.

| Symbol            | Parameter                                                           | Condition                                                                                               | $V_{CC}$ (V) | $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$ |      |          | Unit          |
|-------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|--------------|--------------------------------------------------|------|----------|---------------|
|                   |                                                                     |                                                                                                         |              | Min.                                             | Typ. | Max.     |               |
| $V_{IK}$          | Clamp Diode Voltage                                                 | $I_{IN} = -18\text{ mA}$                                                                                | 2.8          |                                                  |      | -1.2     | V             |
| $V_{IH}$          | Input Voltage High                                                  | $V_{CNTRL} = 0$ to $V_{CC}$                                                                             | 2.3 to 4.5   | 1.0                                              |      |          | V             |
| $V_{IL}$          | Input Voltage Low                                                   | $V_{CNTRL} = 0$ to $V_{CC}$                                                                             | 2.3 to 4.5   |                                                  |      | 0.5      | V             |
| $I_{IN}$          | Control Input Leakage (S0,S1)                                       | $V_{CNTRL} = 0$ to $V_{CC}$                                                                             | 4.5          | -1                                               |      | 1        | $\mu\text{A}$ |
| $I_{OZ}$          | Off Leakage Current of Ports – Sense, MIC, MIC/GNDnA, and MIC/GNDnB | $S[0:1]=01$ ; SENSE=MIC=0.3 V; $V_{CC}=0.3\text{ V}$ ; MIC/GNDnA or MIC/GNDnB=1V0.3V or Floating        | 2.3 to 4.5   | -1.00                                            | 0.05 | 1.00     | $\mu\text{A}$ |
| $I_{AON}$         | On Leakage Current of Ports – Sense, MIC, MIC/GNDnA, and MIC/GNDnB  | $S[0:1]=00, 10, 11$ ; SENSE=MIC=0.3V; $V_{CC}=0.3\text{ V}$ ; MIC/GNDnA or MIC/GNDnB=1V0.3V or Floating | 2.3 to 4.5   | -1.00                                            | 0.05 | 1.00     | $\mu\text{A}$ |
| $I_{CC}$          | Quiescent Supply Current                                            | $V_{SWG}=0$ or $1\text{ V}$ ; $V_{SWM}=0$ or $V_{CC}$ ; $I_{OUT}=0$                                     | 4.5          |                                                  | 15   | 20       | $\mu\text{A}$ |
| $I_{CCZ}$         | Quiescent Supply Current – Hi-Z                                     | $S[0:1]=01$ ; $V_{SWG}=0$ or $1\text{ V}$ ; $V_{SWM}=0$ or $V_{CC}$ ; $I_{OUT}=0$                       | 4.5          |                                                  | 0.2  | 1.0      | $\mu\text{A}$ |
| $I_{CCT}$         | Increase in $I_{CC}$ Current Per Control Voltage and $V_{CC}$       | S0, S1=1.65 V                                                                                           | 4.5          |                                                  |      | 3        | $\mu\text{A}$ |
| $R_{ON\_SEN}$     | Switch On Resistance for SENSE Switch Paths                         | $I_{ON} = -24\text{ mA}$ , $S[0:1]=00$ or $11$ MIC/GND2A or MIC/GND2B=1.0 V                             | 2.3          |                                                  | 0.6  | 1.0      | $\Omega$      |
| $R_{ONFLAT\_SEN}$ | On Resistance Flatness for SENSE Switch Paths                       | $I_{ON} = -24\text{ mA}$ , $S[0:1]=00$ or $11$ MIC/GND2A or MIC/GND2B=0 to 1.0 V                        | 2.3          |                                                  | 0.05 | 0.20     | $\Omega$      |
| $R_{ON\_MIC}$     | Switch On Resistance for MIC Switch Paths                           | $I_{ON} = -24\text{ mA}$ , $S[0:1]=00$ or $11$ MIC/GND2A or MIC/GND2B=1.0V                              | 2.3          |                                                  | 0.6  | 1.0      | $\Omega$      |
| $R_{ONFLAT\_MIC}$ | On Resistance Flatness for MIC Switch Path                          | $I_{ON} = -24\text{ mA}$ , $S[0:1]=00$ or $11$ MIC/GND2A or MIC/GND2B=0.5 to $V_{CC}$                   | 2.3          |                                                  | .08  | 0.5      | $\Omega$      |
| $V_{MIC}$         | MIC Input Signal Range                                              |                                                                                                         | 2.3 to 4.5   | 0                                                |      | $V_{CC}$ | V             |
| $R_{DSON(GND)}$   | GND Switch On Resistance                                            | $I_{ON} = -200\text{ mA}$ , $S[0:1]=00$ or $11$ MIC/GND1A or MIC/GND1B                                  | 2.3          |                                                  | 40   | 80       | m $\Omega$    |
| $V_{SENSE}$       | SENSE Input Signal Range                                            |                                                                                                         | 2.3 to 4.5   | 0                                                |      | 1        | V             |

## AC Electrical Characteristics

All typical values are at  $T_A = 25^\circ\text{C}$  and  $V_{CC} = 3.3\text{V}$  unless otherwise specified.

| Symbol         | Parameter                                  | Condition                                                                   | $V_{CC}$ (V) | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ |      |      | Unit          |
|----------------|--------------------------------------------|-----------------------------------------------------------------------------|--------------|-------------------------------------------------|------|------|---------------|
|                |                                            |                                                                             |              | Min.                                            | Typ. | Max. |               |
| $t_{ON\_MIC}$  | Turn-On Time (MIC, SENSE) S0, S1 to Output | $R_L=10\text{ k}\Omega$ , $C_L=10\text{ pF}$                                | 2.3 to 4.5   |                                                 |      | 1    | $\mu\text{s}$ |
| $t_{OFF\_MIC}$ | Turn-Off Time (MIC, SENSE) S0,S1 to Output | $R_L=10\text{ k}\Omega$ , $C_L=10\text{ pF}$                                | 2.3 to 4.5   |                                                 |      | 1    | $\mu\text{s}$ |
| $t_{ENABLE}$   | Enable Time (MIC, SENSE) S0,S1 to Output   | $S[0:1]=01$ to $00,10,11$ ,<br>$R_L=10\text{ k}\Omega$ , $C_L=10\text{ pF}$ | 2.3 to 4.5   |                                                 | 1    |      | $\mu\text{s}$ |
| $t_{DISABLE}$  | Turn-Off Time (MIC, SENSE) S0,S1 to Output | $S[0:1]=00,10,11$ to $01$ ,<br>$R_L=10\text{ k}\Omega$ , $C_L=10\text{ pF}$ | 2.3 to 4.5   |                                                 | 1    |      | $\mu\text{s}$ |

## MIC and SENSE Switch

| Symbol                   | Parameter                              | Condition                                                                                                          | $V_{CC}$ (V) | $T_A = -40$ to $+85^\circ\text{C}$ |       |      | Unit |
|--------------------------|----------------------------------------|--------------------------------------------------------------------------------------------------------------------|--------------|------------------------------------|-------|------|------|
|                          |                                        |                                                                                                                    |              | Min.                               | Typ.  | Max. |      |
| THD                      | Total Harmonic Distortion - MIC        | $R_T=600\ \Omega$ , $V_{SW}=0.5\text{ V}_{PP}$ ,<br>$f=20\text{ Hz}$ to $20\text{ kHz}$ ,<br>$V_{IN}=1.8\text{ V}$ | 2.8          |                                    | 0.001 |      | %    |
| $O_{IRRM}$               | Off Isolation – MIC/SENSE              | $f=20\text{ kHz}$ , $R_S=600\ \Omega$ ,<br>$C_L=0\text{ pF}$ , $R_T=600\ \Omega$ ,<br>$V_{SW}=0.2\text{ V}_{PP}$   | 2.8          |                                    | - 88  |      | dB   |
| $X_{TALKM}$              | Crosstalk from MIC to SENSE            | $f=1\text{ MHz}$ , $R_L=100\ \Omega$                                                                               | 2.8          |                                    | -80   |      | dB   |
| $X\text{-Talk}_{System}$ | X-Talk Between Left and Right Speakers | $f=2\text{ kHz}$ , $R_L=32\ \Omega$ ,<br>$C_L=0\text{ pF}$ , $V_{IN}=100\text{ mV}_{RMS}$                          | 2.8          |                                    | -54   |      | dB   |

## Capacitance

| Symbol     | Parameter                              |       | Condition                                                    | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ |      |      | Unit |
|------------|----------------------------------------|-------|--------------------------------------------------------------|-------------------------------------------------|------|------|------|
|            |                                        |       |                                                              | Min.                                            | Typ. | Max. |      |
| $C_{IN}$   | Control Pin Input Capacitance (S0, S1) |       | $V_{CC}=0\text{ V}$ , $f=1\text{ MHz}$                       |                                                 | 1.7  |      | pF   |
| $C_{ONM}$  | On Capacitance                         | SENSE | $V_{CC}=2.8\text{ V}$ , $EN=V_{CC}$ , $f=1\text{ MHz}$ ,     |                                                 | 65   |      |      |
|            |                                        | MIC   |                                                              |                                                 | 75   |      |      |
| $C_{OFFM}$ | Off Capacitance                        | SENSE | $V_{CC}=2.8\text{ V}$ , $EN=0\text{ V}$ , $f=1\text{ MHz}$ , |                                                 | 25   |      |      |
|            |                                        | MIC   |                                                              |                                                 | 30   |      |      |

## Power


| Symbol | Parameter                                             | Conditions                                                                                                        | $V_{CC}$ (V) | $T_A = -40$ to $+85^\circ\text{C}$ |      |      | Unit |
|--------|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|--------------|------------------------------------|------|------|------|
|        |                                                       |                                                                                                                   |              | Min.                               | Typ. | Max. |      |
| PSRR   | Power Supply Rejection Ratio                          | Power Supply Noise at $300\text{ mV}_{PP}$ ,<br>Measured 10/90%,<br>$f=217\text{ Hz}$                             | 2.8          | -80                                |      |      | dB   |
| IL     | Insertion Loss through Switch<br>( $V_{OUT}/V_{IN}$ ) | SENSE/MIC: $V_{IN}=400\text{ mV}_{pk-pk}$ ,<br>$f=20\text{ kHz}$ , DC Bias= $0.3\text{ V}$ ,<br>$R_L=600\ \Omega$ | 2.8          |                                    | -0.4 |      | dB   |
|        |                                                       | SENSE/MIC: $V_{IN}=400\text{ mV}_{pk-pk}$ ,<br>$f=20\text{ kHz}$ , DC Bias= $2.5\text{ V}$ ,<br>$R_L=600\ \Omega$ | 2.8          |                                    | -0.4 |      |      |

The following information applies to the WL-CSP package dimensions on the next page:


**Product Specific Dimensions**

| D       | E       | X       | Y       |
|---------|---------|---------|---------|
| 1.56 mm | 1.16 mm | 0.18 mm | 0.18 mm |



| REVISIONS |                          |         |                   |
|-----------|--------------------------|---------|-------------------|
| REV       | DESCRIPTION              | DATE    | APP'D / SITE      |
| 1         | Initial drawing release. | 8-19-09 | L. England / FSME |




TOP VIEW



RECOMMENDED LAND PATTERN  
(NSMD PAD TYPE)



SIDE VIEWS



BOTTOM VIEW

## NOTES:

A. NO JEDEC REGISTRATION APPLIES.

B. DIMENSIONS ARE IN MILLIMETERS.


C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.

D. DATUM C IS DEFINED BY THE SPHERICAL CROWNS OF THE BALLS.

E. PACKAGE NOMINAL HEIGHT IS 586 MICRONS ±39 MICRONS (547-625 MICRONS).

F. FOR DIMENSIONS D, E, X, AND Y SEE PRODUCT DATASHEET.

G. DRAWING FILENAME: MKT-UC012ACrev1.

| APPROVALS                                                                                                           |            | DATE    | <div>FAIRCHILD</div> <div>SEMICONDUCTOR™</div> <div>12BALL WLCSP, 3X4 ARRAY</div> <div>0.4MM PITCH, 250UM BALL</div> |      |                |     |
|---------------------------------------------------------------------------------------------------------------------|------------|---------|----------------------------------------------------------------------------------------------------------------------|------|----------------|-----|
| DRAWN                                                                                                               | L. England | 8-19-09 |                                                                                                                      |      |                |     |
| DFTG. CHK.                                                                                                          | S. Martin  | 8-19-09 |                                                                                                                      |      |                |     |
| ENGR. CHK.                                                                                                          |            |         |                                                                                                                      |      |                |     |
|                                                                                                                     |            |         |                                                                                                                      |      |                |     |
| <div></div> <div>INCH [MM]</div> |            |         | SCALE                                                                                                                | SIZE | DRAWING NUMBER | REV |
|                                                                                                                     |            |         | N/A                                                                                                                  | N/A  | MKT-UC012AC    | 1   |
| DO NOT SCALE DRAWING                                                                                                |            |         |                                                                                                                      |      | SHEET 1 of 1   |     |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative