

► General data



Round cable set, with two 50-pos. socket strips (1:1 connection), for connecting 32 channels, cable length: 2.5 m

Order number	2289104
Type	FLK 50/EZ-DR/ 250/KONFEK

Barcode number	4017918057497
Unit pack	1 Piece
Customs tariff	85444190000

► Technical data

General

Nominal voltage U_N	60 V AC/DC
Max. current carrying capacity per path	1 A
Max. conductor resistance	0.16 Ohm/m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 50 °C
Number of positions	50
Fixed cable length	2.5 m
Single wire, cross section	0.14 mm ²
Single wire, number	7
Single wire, material	Cu tin-plated
External diameter	10.4 mm
Cable, preassembly	Insulation displacement technique, IEC 352-4/ DIN EN 60352-4

► Certificates

UL

Nominal voltage U_N	125 V
-----------------------	-------

CUL

Nominal voltage U_N	125 V
-----------------------	-------

► Drawings

Approval logo



► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved