

CORDS



3-conductor & Custom Power Cords



International Power Cords & Connectors

Shielded & Unshielded

Hospital Grade



Custom Fan Assemblies & Connectors

2 & 3-conductor

Molded Plugs



Example: 3-conductor, unshielded, SJT cord with a 5-15P plug and a C-13 connector. 6'7" long, black



No. of Conductors	Wire Gauge	Cord Type	Plug	Connector	Length	Color Code
2	4	1	3	1	67	01
1 = 2 Conductor	2 = 12AWG	1 = SJT	0 = None	0 = None	18 = 1'8"	01 = Black
2 = 3 Conductor	4 = 14AWG	2 = SVT	1 = 1-15 Standard	1 = C-13 Straight	33 = 3'3"	02 = Brown
(unshielded)	6 = 16AWG	3 = SPT-1	2 = 1-15P Polarized	2 = C-13 Right Angle	50 = 5'0"	03 = Gray
3 = 3 Conductor	8 = 18AWG	4 = SJO	3 = 5-15P Straight	3 = C-14	60 = 6'0"	05 = White
(shielded)	A = 0.75mm	6 = H03VV-F	4 = 5-15P Right Angle	4 = C-15	67 = 6'7"	
	B = 1.0mm	7 = H03VVH2-F	5 = 5-15P Hospital	5 = C-19	76 = 7'6"	
	C = 1.5mm	8 = H05VV-F	Grade Clear	6 = C-17	80 = 8'0"	
			6 = 5-15P Hospital	7 = 022A	910 = 9'10"	
			Grade Gray	8 = 002-2	100 = 10'0"	
			7 = C-14		160 = 16'0"	
			8 = 5-20P			
			9 = 6-15P			
			A = 003A Europe			
			B = 006B Europe			
			C = 010 Europe			
			D = 010A Europe			
			E = 012A UK			
			F = 015 Australia			
			G = 019 Europe			

LET US QUOTE ON
YOUR CUSTOM CORD
REQUIREMENTS

COMPLETE TURNKEY
ASSEMBLIES DELIVERED
JIT WORLDWIDE

STOCKED CORDS				
Part No.	Wire Gauge (AWG)	Cord Type	Plug	Connector
24130-67-01	14	SJT	5-15P	wire leads
24130-910-01				
26130-67-01				
26130-910-01				
28130-67-01	16	SVT		C-13
28130-910-01				
28230-67-01				
28230-910-01	18	SVT		
24131-67-01				
24131-910-01				
26131-67-01				
26131-910-01	16	SJT	none	
28131-67-01				
28131-910-01				
28231-76-01				
26171-33-01	18	SVT		C-14
28171-33-01				
28271-33-01				
26101-67-01	16	SJT		
26101-910-01				
28101-67-01				
28101-910-01				
28201-76-01	18	SVT	C-14	
28201-910-01				
28201-76-01				

CORDAGE	DESCRIPTION
SPT-1	Service Parallel Thermoplastic, 1/32" Insulation, 2 or 3 conductor
SPT-2	Service Parallel Thermoplastic, 3/64" Insulation, 2 or 3 conductor
SPT-3	Service Parallel Thermoplastic, 1/16" Insulation, 2 or 3 conductor
SJT	Service Junior Thermoplastic, 3 conductor
SVT	Service Vacuum Thermoplastic, 3 conductor
SJO	Service Junior Oil Resistant, 3 conductor
SJTW-A	Service Junior Thermoplastic, Outdoor use, 3 conductor
HPN	Heater Parallel Neoprene, 2 or 3 conductor
H03VV-F	Harmonized, 300V, PVC jacket and conductor insulation, flexible cable
H03VVH2-F	Harmonized, 300V, PVC jacket and conductor insulation, flat, non-separable
H05VV-F	Harmonized, 500V, PVC jacket and conductor insulation, flexible cable

