



## Product Information

# Contact Cleaner HFP

High Flash Contact Cleaner  
**3005**

## Introduction

Contact Cleaner HFP is a heavy duty contact cleaner with a flash point greater than 140°F. Non-ozone depleting, Contact Cleaner HFP is ideal for penetrating and dissolving soils such as oil, grease, wax, tar, adhesive and rosin. Contact Cleaner HFP is an excellent cleaning product for electronic and electrical equipment, machinery and metal parts. Contact Cleaner HFP has a low odor and does not contain CFCs, HCFC, 1,1,1-trichloroethane, methylene chloride, perchloroethylene or other chlorinated solvents.

### Features / Benefits

Flash Point Above 140°F  
Rapidly Penetrating  
Residue Free  
Non-Ozone Depleting  
Non-Corrosive  
Controlled Evaporation  
Displaces Moisture

### Physical Properties

<b>Boiling Point</b>	35°C / 95°F
<b>Flash Point (TCC)</b>	60°C/140°F
<b>Evaporation Rate</b>	NIF
<b>Surface Tension</b>	21.5
<b>Kauri-Butanol (KB Value)</b>	39

## Chemical Components

Dipropylene glycol monomethyl ether.....	(34590-94-8)	10-16%
Hydrotreated heavy naphtha.....	(64742-48-9)	70-80%
Dipropylene Glycol Methyl Ether Acetate.....	(88917-22-0)	5-10%
Carbon Dioxide (Aerosol Propellant).....	(124-38-9)	1-5%

## Plastic Compatibility

Material	Compatibility	Material	Compatibility
<b>ABS</b>	Excellent	<b>PMMA</b>	Not Compatible
<b>Nylon 6</b>	Excellent	<b>POM</b>	Excellent
<b>Lexan</b>	Not Compatible	<b>PP</b>	Excellent
<b>HDPE</b>	Excellent	<b>PS</b>	Not Compatible
<b>LDPE</b>	Excellent	<b>PTFE</b>	Excellent
<b>Phenolic</b>	Excellent	<b>PVC</b>	Excellent

## Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

## Packaging and Availability

---

Contact Cleaner HFP is available in the following sizes:

3005-15S	15 Ounce Aerosol
3005-G	1 Gallon in Plastic

## Resources

---

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

North America  
Tech Spray L.P.  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

Europe  
Techspray International  
UNIT 4, 44/46 Bunyan Road, Kempston  
Bedford MK42 8HL United Kingdom  
+44 (0) 1234 855443  
email: [tseurope@techspray.com](mailto:tseurope@techspray.com)

Countries Outside US  
Call to locate a distributor  
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.  
P.O. Box 949  
Amarillo, TX 79105  
[www.techspray.com](http://www.techspray.com)

Aerosol MSDS

[English](#)  
[French](#)  
[German](#)  
[Italian](#)  
[Spanish](#)

Bulk MSDS

[English](#)  
[French](#)  
[German](#)  
[Italian](#)  
[Spanish](#)

