



# **Contact Cleaner NF225**

## Non-Flammable Non-141B Contact Cleaner 3015

Introduction

Contact Cleaner NF225 is designed for general cleaning and degreasing. Nonflammable and safe on most plastics, Contact Cleaner NF225 is the standard for precision cleaning of polar and non-polar soils, including hand oils, solder oils, greases, silicones, fluxes and similar soils. Excellent for tape head cleaning and

general degreasing.

Features / Benefits Non-Flammable Safe on Most Plastics Rapidly Evaporating Residue Free Rapidly Penetrating Non-Corrosive

Physical Properties		
Boiling Point	58°C / 136°F	
Flash Point (TCC)	None	
Evaporation Rate	>1	
Surface Tension		
Kauri-Butanol (KB Value)		

#### **Chemical Components**

3,3-Dichloro-1,1,1,2,2-pentafluoropropane(HCFC-225ca) (422-56-0)	32-37%-Aerosol 40-45%-Bulk
1,3-Dichloro-1,1,2,2,3-pentafluoropropane(HCFC-225cb) (507-55-1)	37-45%-Aerosol 48-55%-Bulk
Methanol(67-56-1)	.5-2%-Aerosol 1-2%-Bulk
Ethanol(64-17-5)	5-7%-Aerosol 7-8%-Bulk
Nitromethane(75-52-5)	<.5%
1,1,1,2-Tetrafluoroethane (Aerosol)(811-97-2)	18-22%
Carbon Dioxide (Aerosol Propellant)(124-38-9)	1-3%

### Plastic Compatibility

Material	Compatibility	Material	Compatibility
ABS	Excellent	PMMA	Excellent
Nylon	Excellent	POM	Excellent
Lexan	Excellent	PP	Excellent
HDPE	Excellent	PS	Excellent
LDPE	Excellent	PTFE	Excellent
C. E. Phenolic	Excellent	PVC	Excellent

#### **Environmental Policy**

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

#### Packaging and Availability

Contact Cleaner NF225 is available in the following sizes:

3015-18S 18 Ounce Aerosol 3015-5G 50 Pounds in Metal

#### Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: <a href="https://www.techspray.com">www.techspray.com</a>.

North America Tech Spray L.P. P.O. Box 949 Amarillo, TX 79105 800-858-4043 email: tsales@techspra

UNIT 4, 44/46 Bunyan Road, Kempston Bedford MK42 8HL United Kingdom +44 (0) 1234 855443

Europe

Countries Outside US Call to locate a distributor in your country.

email: tsales@techspray.com

email: tseurope@techspray.com

**Techspray International** 

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P. P.O. Box 949 Amarillo, TX 79105 www.techspray.com Aerosol MSDS
English
French
German
Italian
Spanish

Bulk MSDS English French German Italian Spanish

