

Product Information

C/D Solv™ HFP

High Flash Cleaner/Degreaser 3035

Introduction

C/D-Solv™ HFP is a high flash point, non-chlorinated solvent. The non-ozone depleting formula does not contain CFCs, 1,1,1-trichloroethane, or other chlorinated solvents. Rapidly penetrating, the high flash point allows the solvent to be used in areas where flammability is a concern without sacrificing cleaning efficiency.

Features / Benefits Flash Point Above 140°F Non-Ozone Depleting Controlled Evaporation Residue Free Safe on Most Plastics Rapidly Penetrating Non-Corrosive

Physical Properties		
Boiling Point	149°C / 300°F	
Flash Point (TCC)	64°C / 147°F	
Evaporation Rate	NIF	
Surface Tension	26	
Kauri-Butanol (KB Value)	39	

Chemical Components

Aliphatic Hydrocarbon	(64742-47-8)	85-95%
Propylene glycol phenyl ether	(770-35-4)	1-10%
Dipropylene glycol phenyl ether	(51730-94-0)	<1%
Carbon Dioxide (Aerosol Propellant)	(124-38-9)	1-5%

Plastic Compatibility

Material	Compatibility	Material	Compatibility
ABS	Excellent	PMMA	Not Compatible
Nylon 6	Excellent	POM	Excellent
Lexan	Not Compatible	PP	Excellent
HDPE	Excellent	PS	Not Compatible
LDPE	Excellent	PTFE	Excellent
Phenolic	Excellent	PVC	Excellent

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

C/D Solv™ HFP is available in the following sizes:

3035-15S 15 Ounce Aerosol 3035-G 1 Gallon in Plastic 3035-55G 331 Pounds in Metal

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America Tech Spray L.P. P.O. Box 949 Amarillo, TX 79105 800-858-4043

email: tsales@techspray.com

Europe Techspray International UNIT 4, 44/46 Bunyan Road, Kempston Bedford MK42 8HL United Kingdom +44 (0) 1234 855443

email: tseurope@techspray.com

Countries Outside US Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P. P.O. Box 949 Amarillo, TX 79105 www.techspray.com Aerosol MSDS **English French** German Italian Spanish

Bulk MSDS English French German Italian **Spanish**



Copyright 2004 Tech Spray, L. P. For Commercial Use Only