



T-3/4 Subminiature Lamps

Line No.	Part No. Wire Lead	Part No. Miniature Flanged	Part No. Bi-Pin	Volts	Amps	M.S.C.P.	Filament Type	Life Hours
1	7100	3810	7810	1.5	0.010	0.002	C-2R	10,000
2	7101	3811	7811	1.5	0.015	0.003	C-2R	5,000
3	8534	7121	7111	2.5	0.110	0.060	C-2R	10,000
4	3102	—	—	4.5	0.022	0.018	C-2R	5,000
5	30	—	—	4.5	0.021	0.017	C-2R	5,000
6	8537	8538	7538	5.0	0.015	0.02	C-2R	1,000
7	6803	8587	7113	5.0	0.060	0.03	C-2R	100,000
8	6833	8913	7114	5.0	0.060	0.05	C-2R	100,000
9	6153	6183	7115	5.0	0.060	0.15	C-2R	3,000
10	7133	8828	7116	5.0	0.075	0.09	C-2R	25,000
11	8666	8383	7117	5.0	0.080	0.15	C-2R	15,000
12	7153	8270	7118	5.0	0.115	0.15	C-2R	40,000
13	7102	7123	7119	5.0	0.115	0.20	C-2R	5,000
14	L51	L52	L53	12.0	0.060	0.15	C-2F	16,000
15	L54	L55	L56	14.0	0.050	0.13	C-2F	16,000
16	*L57	*L58	*L59	28.0	0.024	0.10	CC-2F	16,000


*Add 1.4 to MOL



T-3/4 Wire Lead



T-3/4 Miniature Flanged



T-3/4 Bi-Pin