



Advanex™ 30 - DISCONTINUED

Industrial Lubricant
3110

Introduction

Advanex™ 30 is an industrial strength lubricant designed for harsh environments, perfect for indoor or outdoor applications. Advanex™ 30 cleans and protects by depositing a thin protective coating. Advanex™ 30 penetrates rapidly to quickly loosen corroded parts while displacing surface moisture. It is safe on most plastics and does not contain CFCs.

Features / Benefits

Industrial Strength
Displaces Moisture
Penetrates Rapidly
Loosens Corroded Parts
Prevents Corrosion
Safe on Plastics

Chemical Components

Aliphatic hydrocarbon.....	(64742-47-8)	80-90%
Hydrotreated Heavy Naphtha.....	(64742-48-9)	1-5%
Oxygenated Hydrocarbon		1-5%
Petrolatum USP.....	(8009-03-8)	1-5%
Carbon Dioxide (Aerosol Propellant).....	(124-38-9)	1-5%

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Advanex™ 30 is available in the following sizes:

3110-8S	8 Ounce Aerosol
3110-15S	15 Ounce Aerosol
3110-QT	1 Quart Trigger Sprayer
3110-G	1 Gallon in Plastic
3110-5G	33 Pounds in Metal
3110-55G	331 Pounds in Metal

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America
Tech Spray L.P.
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe
Techspray International
UNIT 4, 44/46 Bunyan Road, Kempston
Bedford MK42 8HL United Kingdom
+44 (0) 1234 855443
email: tseurope@techspray.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.
P.O. Box 949
Amarillo, TX 79105
www.techspray.com

Aerosol MSDS
[English](#)
[French](#)
[German](#)
[Italian](#)
[Spanish](#)

Bulk MSDS
[English](#)
[French](#)
[German](#)
[Italian](#)
[Spanish](#)

