



Proshield™ - DISCONTINUED

Corrosion Inhibitor 3200

Introduction

Proshield™ is a long lasting corrosion inhibitor, which forms a thick, waxy coating to protect metal parts in storage for up to two years. The indoor/outdoor coating shields parts from moisture, air, corrosive fumes, dust and particulates. Proshield™ protects aluminum and stops exfoliation or filiform corrosion. As an industrial lubricant, Proshield™ is ideally suited for gears, chains, wire rope and other moving parts requiring lubrication and a high level of corrosion resistance. This product does not contain CFCs, 1,1,1-trichloroethane or other ozone depleting solvents.

Features / Benefits

- Long Lasting Corrosion Inhibitor
- High Salt Resistance
- Forms Waxy Film
- Safe on Plastics
- Non-Ozone Depleting
- Non-Corrosive

Chemical Components

| | | |
|--|--------------|-------------------------------|
| Aliphatic Hydrocarbon..... | (64742-47-8) | 20-23%-Aerosol 45-65%-Bulk |
| Oil Soluble Sodium Sulfonate | Proprietary | 26-32%-Aerosol 6-10%-Bulk |
| Oxygenated Hydrocarbons | | 1-5%-Aerosol 6-10% |
| Naphthenic Oil | (64742-52-5) | 9-15% |
| Petrolatum USP..... | (8009-03-8) | 12-20% |
| n-Hexane..... | (64742-49-0) | 20-25% |
| Carbon Dioxide (Aerosol Propellant)..... | (124-38-9) | <3% |

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Proshield™ is available in the following sizes:

| | |
|----------|---------------------|
| 3200-10S | 10 Ounce Aerosol |
| 3200-16S | 16 Ounce Aerosol |
| 3200-G | 1 Gallon in Plastic |
| 3200-5G | 35 Pounds in Metal |

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America
Tech Spray L.P.
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe
Techspray International
UNIT 4, 44/46 Bunyan Road, Kempston
Bedford MK42 8HL United Kingdom
+44 (0) 1234 855443
email: tseurope@techspray.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.
P.O. Box 949
Amarillo, TX 79105
www.techspray.com

[English MSDS](#)
[French MSDS](#)
[German MSDS](#)
[Italian MSDS](#)
[Spanish MSDS](#)

