

35618 Hook-up/Lead - UL AWM Style 3173 - XL-DUR®

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---

Description:

The insulation is cross-linked polyethylene applied in a single extrusion. This construction has excellent thermal aging characteristics, moisture resistance, and solvent resistance. The 356-series of XL-DUR is recommended for class 130(B) as motor leads

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	18
Stranding	16x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	XLPE - Cross Linked Polyethylene
Insulation Thickness	.030 in.

OVERALL:

Overall Nominal Diameter	.109 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	3173
UL Rating	600 V, 125°C
CSA Type	CL1251
CSA Rating	600 V, 125°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2004

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
35618 0015000	#18STR XLPE 125C 600VBRN	5000	50	BROWN	C I U Z

35618 Hook-up/Lead - UL AWM Style 3173 - XL-DUR®

35618 002500	#18 STR XLPE 125C 600V	500	5.5	RED	F
35618 0025000	#18STR XLPE 125C 600VRED	5000	50	RED	C I U Z
35618 0035000	#18STR XLPE 125C 600VORG	5000	50	ORANGE	C I U Z
35618 004500	#18 STR XLPE 125C 600V	500	5.5	YELLOW	F
35618 0045000	#18STR XLPE 125C 600VYEL	5000	50	YELLOW	C I U Z
35618 005500	#18 STR XLPE 125C 600V	500	5.5	GREEN, DARK	F
35618 0055000	#18STRXLPE 125C 600VDGRN	5000	50	GREEN, DARK	C I U Z
35618 0065000	#18STRXLPE 125C 600VLBLU	5000	50	BLUE, LIGHT	C I U Z
35618 0075000	#18STR XLPE 125C 600VVIO	5000	50	VIOLET	C I U Z
35618 0085000	#18STR XLPE 125C 600VGRY	5000	50	GRAY	C I U Z
35618 0095000	#18STR XLPE 125C 600VWHT	5000	50	WHITE	C I U Z
35618 010500	#18 STR XLPE 125C 600V	500	5.5	BLACK	F
35618 0105000	#18STR XLPE 125C 600VBLK	5000	50	BLACK	C I U Z
35618 0125000	#18STR XLPE 125C 600VPNK	5000	50	PINK	C I U Z
35618 013500	#18 STR XLPE 125C 600V	500	5.5	BLUE, DARK	F
35618 0135000	#18STRXLPE 125C 600VDBLU	5000	50	BLUE, DARK	C I U Z

C = CRATE REEL PUT-UP.

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

I = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'

U = TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10 000' PER COLOR COMBINATION. (SEE TOPCOAT ADDER TABLE)

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1

Revision Date: 04-26-2005

35618 Hook-up/Lead - UL AWM Style 3173 - XL-DUR®

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.