


[→ Honeywell.com](#) [→ Automation & Control Solutions](#)
[HOME](#)
[ABOUT US](#)
[KEY INDUSTRIES SERVED](#)
[PRODUCTS & INFORMATION](#)
[NEWS & EVENTS](#)
[SALES &](#)

Honeywell Sensing and Control

[Search](#)


narrow your search

Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1727)
- Sensors (5899)
- Switches (9774)
- Wireless (39)

Technology

- Control and Instrumentation (1052)
- Electromechanical (9300)
- Microstructure (1492)
- Optical/Infrared (1042)
- Thick Film (1409)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPMM
XYR6000™

[find out more](#)

white papers

Wireless Switches Offer
Unlimited Benefit
Basic Switches Are Not Created
Equal
Applying Precision Switches
Sensors for Medical Devices
New Ways to Measure Torque
Choosing Safety Switches
Specifying Hour Meters

Need help?

[Click here to contact us](#)

380C310K

(Home : Products » Sensors » Rotary Position Sensors » Conductive Plastic Potentiometers » 380)



Actual product
appearance may vary.

380 Series Industrial Potentiometer, Conductive Plastic Element,
Solder lug Terminals, 2 W Power Rating, 10 kOhm Resistance
Value

[Sales & Service](#)
[Distributor Inventory](#)
[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

Description

The 380 Series is a robust 2 watt potentiometer that offers the advantages of a conductive plastic element and a 100,000 cycle rotational life. Special tapers and element designs available on a special order.

Features

Features

- Robust nickel-plated brass shaft and bushings
- Conductive plastic element
- Linear taper
- 100,000 cycle rotational life

Potential Applications

Potential Applications

- Manual controls (throttle, joystick)
- Electric vehicles
- Personal mobility
- Off-road vehicles
- Welding and heating
- Telecommunications

contacts

Customer Service
Technical Support
Global Sales & Service
View Site Demo
Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



my links

[Login to iCOM](#)
[Login to Rep/AD Portal](#)
[Login to Digital University](#)

News Center

HONEYWELL ANNOUNCES
ADDITION TO RELIALIGN™
RESIDENTIAL DOOR
INTERLOCK SWITCHES THAT
FEATURE RUGGED, PLASTIC
HOUSING

HONEYWELL RELEASES
UNLIMITED POTENTIAL WITH
NEW LIMITLESS™ WIRELESS
SWITCHES

HONEYWELL'S XYR6000
WIRELESS POSITION SENSOR
ENABLES MONITORING IN
HAZARDOUS AREAS AND
REMOTE LOCATIONS

**MICRO SWITCH
Anniversary site**

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)


[→ Honeywell.com](#) [→ Automation & Control Solutions](#)
[HOME](#)[ABOUT US](#)[KEY INDUSTRIES SERVED](#)[PRODUCTS & INFORMATION](#)[NEWS & EVENTS](#)[SALES &](#)

Honeywell Sensing and Control

Search



narrow your search

Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1727)
- Sensors (5899)
- Switches (9774)
- Wireless (39)

Technology

- Control and Instrumentation (1052)
- Electromechanical (9300)
- Microstructure (1492)
- Optical/Infrared (1042)
- Thick Film (1409)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPMM
XYR6000™

[find out more](#)

white papers

Wireless Switches Offer
Unlimited Benefit
Basic Switches Are Not Created
Equal
Applying Precision Switches
Sensors for Medical Devices
New Ways to Measure Torque
Choosing Safety Switches
Specifying Hour Meters

Need help?

[Click here to contact us](#)

380C310K

(Home : Products : Sensors » Rotary Position Sensors » Conductive Plastic Potentiometers » 380)



Actual product
appearance may vary.

380 Series Industrial Potentiometer, Conductive Plastic Element,
Solder lug Terminals, 2 W Power Rating, 10 kOhm Resistance
Value

[Sales & Service](#)
[Distributor Inventory](#)
[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

Product Specifications

Potentiometer Type	Industrial
Element Type	Conductive Plastic
Terminal	Solder lug
Power Rating	2 W
Resistance Value	10 kOhm
Resistance Tolerance	± 10 %
Linearity	± 5 %
Bushing Thread	9,53 mm [0.375 in] x 32 NEF-2A
Bushing Length	9,53 mm [0.375 in]
Bushing Type	Standard
Shaft Diameter	6,35 mm [0.25 in]
Shaft Length	22,23 mm [0.875 in]
Shaft Ending	Slotted
Body	27.8 mm [1.094 in] diameter max. except at terminal standoff
Electrical Taper	Linear
Operating Temperature	-55 °C to 120 °C [-67 °F to 248 °F]
Working Voltage (Max.)	500 V
Rotational Life	100000 cycles
Mechanical Rotation	312°
Availability	Global
Series Name	380
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

contacts

Customer Service
Technical Support
Global Sales & Service
View Site Demo
Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



my links

Login to iCOM
Login to Rep/AD Portal
Login to Digital University

News Center

HONEYWELL ANNOUNCES
ADDITION TO RELIALIGN™
RESIDENTIAL DOOR
INTERLOCK SWITCHES THAT
FEATURE RUGGED, PLASTIC
HOUSING

HONEYWELL RELEASES
UNLIMITED POTENTIAL WITH
NEW LIMITLESS™ WIRELESS
SWITCHES

HONEYWELL'S XYR6000
WIRELESS POSITION SENSOR
ENABLES MONITORING IN
HAZARDOUS AREAS AND
REMOTE LOCATIONS

**MICRO SWITCH
Anniversary site**

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)

