# EXTECH® Product DATASHEET

# **Heavy Duty Hygro-Thermometer**

**Dual display of Relative Humidity and Temperature with PC interface** 


### **Features:**

- Fast response from 10 to 95% RH
- C/F switchable measures temperature from 32 to 122°F (0 to 50°C) with 0.1° resolution
- Utilizes high precision thin film capacitance sensor for RH and thermistor for temperature
- Accurate to 3% RH; 1.5°F/0.8°C
- · Data Hold and Auto Shut off
- Super large 1.4"(36mm) LCD display
- · Records Max/Min and AVG readings
- · Built-in RS-232 PC serial interface with optional Data Acquisition software and Datalogger
- Dimensions:7x2.9x1.3"(178x74x33mm)
- Weight:18oz (510g)
- Complete with remote 6.25"(159mm) probe with 36" (0.9m) cable, protective rubber holster, 9V battery

# **Interface Options:**

- Optional Windows® compatible Data Acquisition Software and serial cable enable user to display and capture readings on a PC, and set time intervals
- Optional battery operated Datalogger module stores over 8000 readings for later transfer to a PC





**Optional PC Software** 



## **Ordering Information**

407445......Heavy Duty Hygro-Thermometer 407445-NIST...Heavy Duty Hygro-Thermometer with NIST Certificate

#### **Accessories**

	33% RH Calibration Reference
	75% RH Calibration Reference
156119	117 VAC Adaptor
	220 VAC Adaptor
	Soft Vinyl Pouch Carrying Case
140001.	Hard Vinyl Carrying Case
	Data Acquisition program and cable
380340	Battery Operated Datalogger Module

