

RTD Dual Input Thermometer

Large LCD displays two RTD channels with audible alarm

Features:

- Switchable inputs for 100Ω Pt-385 and Pt-3926
- Large multi-function 4-1/2 digit(20000 count) LCD
- Resolution to 0.1° with basic accuracy of 0.05%
- Large 0.8" (20mm) LCD displays T1, T2 or the difference of T1-T2
- LCD displays Dual inputs plus Elapsed Time
- Rugged water resistant design with protective holster/stand
- Selectable °C/°F units
- MAX/MIN, AVG, REL, and HOLD functions
- Data hold and Auto power off
- Programmable HI/LO audible alarms
- Dimensions/Weight: 76x36x21" (192x91x53mm); 13oz(365g)
- Complete with rubber holster with stand and 9V battery; Stainless Steel RTD probes sold separately



CE

Specifications:			
Range	Range	Resolution	Accuracy ±(%rdg + digits)
100 Ω Pt-385	100 Ω Pt-3926		
-200° to 800°C	-200° to 630°C	0.1°	±(0.05% + 0.2°C)
-328° to 1472°F	-328° to 1166°F	0.1°	±(0.05% + 0.4°F)

Ordering Information:

- 421504RTD Dual input Thermometer
- 421504-NIST..RTD Dual input Thermometer w/NIST Certificate
- 850182RTD Stainless Steel General Purpose Probe
- 850183RTD Stainless Steel Surface Probe
- 850184RTD Stainless Steel Air Probe
- 409997Vinyl Pouch Carrying Case