Fuse Blocks, Holders and Accessories




POWR-GARD™ Products

571 Series Panel Mounted Fuseholders



Panel mount fuseholders are available for supplementary or Class CC branch circuit protection. Class CC fuses have a rejection feature on one end cap which mates with the rejection feature of Littelfuse Class CC fuse blocks and fuseholders to prevent the installation of fuses with lower voltage ratings or interrupting ratings. Watertight version must be front panel mounted.



SPECIFICATIONS

Voltage Rating: 600 Volts

Ampere Rating: 30 amperes for Class CC and

Midget fuses

Dielectric strength: 4000 Volts

Terminals: Tin-plated brass combination solder and

quick-connect

Molded parts: Black thermoplastic

Approvals: UL Recognized (File No. E14721) — 571 series

UL Recognized for branch circuit protection

— 571 OCC/RCC

CSA Certified (File No. LR7316)

ORDERING INFORMATION

	Part Number		Bottom	Fuse Length	For Use
	Standard	Watertight	Terminal	Range*	With
	571 027 571 028	571 027P 571 028P	Straight Rt. Angle	1 ⁵ / ₁₆ " — 1 ³ / ₈ "	Midget Fuses
	571 007 571 008	571 007P 571 008P	Straight Rt. Angle	1 ¹³ / ₃₂ " — 1 ¹ / ₂ "	Midget Fuses
	571 0CC 571 RCC	571 0CCP 571 RCCP	Straight Rt. Angle	1 ¹ / ₂ "	Class CC Fuses

^{*} Fuse diameter is ¹³/₃₂".

O-Rings: 901-184 (body) 901-260 (knob)

POWR-JAW Clip Clamps



POWR-JAW clamps improve the contact between fuse and clip. The unnecessary heat from poor contact due to the loss of spring force in the clips can cause nuisance fuse opening and premature aging of surrounding components.

- High temperature phenolic resin knob designed for the most severe environments.
- 7 sizes to provide effective coverage.
- Simple design makes installation easy.

Part Number	Volts	Amperes
LCC 1	250	0-30
LCC 2	250	35-60
LCC 2	600	0-30
LCC 4	600	35-60
LCC 5	250/600	70-100
LCC 6	250/600	110-200
LCC 7	250/600	225-400
LCC 8	250/600	450-600



