



Surface Mounting LEDs

5700 Series

T-41-21


SOT23 Package shape



Each lead has the same dimensions

Colour and lens type	Luminous intensity @ 20mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wave-length (nm)	Max power dissipation (mW)	Max continuous forward current (mA)
	1.0	2.0	650	75	25
Amber	1.0	2.0	610	75	25
Yellow	1.0	2.0	585	75	25
	2.5	2.0	563	75	25
Red/Amber	1.0/	2.0	650/	75	25
	1.0	2.0	610	75	25
Amber/Yellow	1.0/	2.0	610/	75	25
	1.0	2.0	585	75	25
Red/Green	1.0/	2.0	650/	75	25
	2.5	2.0	563	75	25

Quantity	1+	500+	1000+
5711R	18.40	15.82	13.98
5712A	19.70	16.94	14.97
5713Y	19.70	16.94	14.97
5714G	19.70	16.94	14.97
5721RA	36.70	31.56	27.89
5722YA	36.70	31.56	27.89
5723RG	36.70	31.56	27.89



Packaging

Standard package is milky white but for ease of identification the single colour red and green types are available with a red or green tinted diffuser. Supplied in standard 'Super 8' tape for automatic insertion equipment.

Soldering


Recommended soldering conditions are, Preheat 140 - 160°C for 1 minute max. Solder 210 - 230°C for 5 seconds max.

Operating temperatures


T_{opr} -25 to +75 °C
T_{stg} -30 to +85 °C

Pinout


Top view



Standard



Option 2




Two colour

In dual colour devices the first letter of the part number indicates the LED connected to pin 1




Lighthouse Style Circular LEDs - 2mm

5400 Series



Frequently specified for through-panel applications where a bright spot of light with a wide viewing angle is required
Milky white encapsulant types are available for secret colour and high on/off contrast ratio



T-41-21


Head is a 2mm dia cylinder, viewing angle is achieved with the flat matte emitting surface.
Available with or without leg pips for PCB standoff - suffix /A for no pips.

Colour and lens type	Luminous intensity @ 20mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wave-length (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	3.2	2.0	650	100	60	20
	3.2	2.0	650	100	60	20
	3.2	2.1	563	100	75	25
	3.2	2.1	563	100	75	25
Yellow-D	1.0	2.1	585	100	60	20
Amber-D	2.0	2.0	635	100	60	20


Quantity	1+	500+	1000+
5401RD	14.90	12.81	11.32
5402RW	14.90	12.81	11.32
5403GD	15.50	13.33	11.78
5404GW	15.50	13.33	11.78
5405YD	16.00	13.76	12.16
5406AD	16.00	13.76	12.16

Lighthouse Style Circular LEDs - 2.5mm

5400 Series



Frequently specified for through panel applications where a bright spot of light with a wide viewing angle is required
Milky white encapsulant types are available for secret colour and high on/off contrast ratio.




Head is a 2.5mm dia cylinder, wide viewing angle is achieved with the flat matte emitting surface.
Available with or without leg pips for PCB standoff - suffix /A for no pips

Colour and lens type	Luminous intensity @ 20mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wave-length (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	2.0	2.0	650	100	60	20
	2.0	2.0	650	100	60	20
	3.2	2.1	563	100	75	25
	3.2	2.1	563	100	75	25
Yellow-D	2.0	2.1	585	100	60	20
Amber-D	2.0	2.0	635	100	60	20


Quantity	1+	500+	1000+
5407RD/A	14.90	12.81	11.32
5408RW	14.90	12.81	11.32
5409GD/A	15.50	13.33	11.78
5410GW	15.50	13.33	11.78
5411YD/A	16.00	13.76	12.16
5412AD	16.00	13.76	12.16

Lighthouse Style Square LEDs - 2 x 2mm

5400 Series



Applications include mimic and multicolour indication.




Head is 2mm square and 2.7mm high.

Colour and lens type	Luminous intensity @ 20mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wave-length (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	1.0	2.0	650	100	50	20
	1.6	2.1	563	100	75	25
Yellow-D	1.6	2.1	585	100	60	20

Quantity	1+	500+	1000+
5413RD	14.90	12.81	11.32
5414GD	15.50	13.33	11.78
5415YD	16.00	13.76	12.16

Rectangular Style - Stacking LEDs 4.9 x 1.9mm


5200 Series




Unique design permits stacking for mimic applications etc.
Wide viewing angle is achieved by the flat matte emitting surface
Bi-colour is a three lead device

IMO ELECTRONICS LTD

Colour and lens type	Luminous intensity @ 20mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wave-length (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	2.0	2.0	650	100	60	20
	2.0	2.1	563	100	75	25
Yellow-D	2.0	2.1	585	100	60	20
Red/	2.0	2.0	635	100	60	20
Green-W	2.0	2.1	563	100	75	25




Rectangular LEDs stacked in 'X' and 'Y' directions.




Quantity	1+	500+	1000+
5201RD	13.96	12.01	10.61
5202GD	14.50	12.47	11.02
5203YD	15.00	12.90	11.40
5204RGW	40.00	34.40	30.40

Rectangular Style LEDs 7.5 x 2.5mm

5200 Series



Rectangular type with no flange to allow 'X' or 'Y' stacking with no gaps.
Applications include matrix displays, bargraphs etc.




Colour and lens type	Luminous intensity @ 10mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wave-length (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	1.0	2.0	650	100	60	20
	1.6	2.1	563	100	75	25
Yellow-D	1.0	2.1	585	100	60	20


Quantity	1+	500+	1000+
5211RD	14.90	12.81	11.32
5212GD	15.50	13.33	11.78
5213YD	16.00	13.76	12.16

Rectangular Style LEDs 2 x 3.8mm

5200 Series




Compact rectangular type with no flanges to allow 'X' or 'Y' stacking with no gaps.
Applications include matrix displays, bargraphs etc.



Colour and lens type	Luminous intensity @ 10mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wave-length (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	1.0	2.0	650	100	60	20
	1.6	2.1	563	100	75	25
Yellow-D	1.0	2.1	585	100	60	20

Quantity	1+	500+	1000+
5221RD	14.90	12.81	11.32
5222GD	15.50	13.33	11.78
5223YD	16.00	13.76	12.16

Tombstone Style LEDs




The flat sides of this package allow stacking to give a rounded bargraph effect. Applications include professional sound equipment, instrumentation and consumer products

Colour and lens type	Luminous intensity @ 10mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wavelength (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	10.0	2.0	650	35	60	20
	25.0	2.1	563	35	75	25
Yellow-D	10.0	2.1	585	35	60	20
Amber-D	10.0	2.1	610	35	60	20

Also available in Water Clear


5700 Series

T-41-21



Quantity	1+	500+	1000+
5701RD	18.44	14.75	13.39
5702GD	18.93	15.25	13.89
5703YD	19.43	15.75	14.40
5704AD	19.43	15.75	14.40

Triangular Style LEDs




Isosceles triangle style for annunciators and indicators. The unique design permits 'X' and 'Y' stacking for mimics etc.

Colour and lens type	Luminous intensity @ 20mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wavelength (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	2.0	2.0	650	100	60	20
	3.2	2.1	563	100	75	25
Yellow-D	2.0	2.1	585	100	60	20


5300 Series



Triangular LEDs stacked in 'X' direction, they can be used in conjunction with 5200 Series Rectangular Stacking LEDs.




□ = Emitting area



Quantity	1+	500+	1000+
5301RD	15.40	13.24	11.70
5302GD	16.00	13.76	12.16
5303YD	16.53	14.22	12.56


8mm Round LEDs

5800 Series



These popular LEDs provide a large soft spot of light and colour in applications requiring a bigger light emitter than standard 3 or 5mm LEDs.

Colour and lens type	Luminous intensity @ 20mA typical (mcd)	Forward voltage @ 10mA typical (VF)	Peak wavelength (nm)	Viewing angle half intensity (degrees)	Max power dissipation (mW)	Max continuous forward current (mA)
	6.0	2.0	650	50	60	20
	7.0	2.1	563	50	75	25
Yellow-D	4.0	2.1	585	50	60	20
Amber-D	14.0	2.0	610	50	60	20



Quantity	1+	500+	1000+
5800RD	35.00	30.10	26.60
5801GD	36.50	31.39	27.74
5802YD	37.65	32.38	28.61
5803AD	37.65	32.38	28.61