acc. to ISO/DIS 11014

Printing date 07/31/2003 Reviewed on 07/21/2003

1 Identification of substance

Product details

Trade name: <u>SOLDER ALLOYS CONTAINING LEAD</u>
Application of the substance / the preparation: Solder

Manufacturer/Supplier:

 Kester
 Tel.(847) 297-1600

 515 E. Touhy Ave.
 Fax.(847) 390-9338

 Des Plaines, IL 60018
 Fax.(847) 390-9338

Information department:

MSDS Coordinator Tel. (847) 699-5755

Emergency information:

CHEMTREC 24-Hour Emergency Telephone Number: (800)424-9300 CHEMTREC 24-Hour Emergency Telephone Number (Outside of the U.S. and Canada): (703)527-3887

2 Composition/Data on components

Chemical characterization

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
7440-31-5	tin	0-100%
7439-92-1	lead	0-100%
7440-36-0	antimony	0-100%
7440-50-8	copper	0-100%
7440-22-4	silver	0-100%
7440-69-9	bismuth	0-100%
7440-66-6	Zinc	0-100%

Additional information:

Composition and weight percent of solder alloys varies widely and can be determined by product label.

3 Hazards identification

WHMIS Hazard Symbols



Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Harmful by inhalation and if swallowed.

Danger of cumulative effects.

Possible risk of impaired fertility.

Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

(Contd. on page 2)

acc. to ISO/DIS 11014

Printing date 07/31/2003 Reviewed on 07/21/2003

Trade name: SOLDER ALLOYS CONTAINING LEAD

(Contd. of page 1)

Classification system: NFPA ratings (scale 0 - 4)



Health = 2 Fire = 0 Reactivity = 0

HMIS-ratings (scale 0 - 4)

HEALTH *2
FIRE 0
REACTIVITY 0

Health = *2 Fire = 0Reactivity = 0

4 First aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly. After eye contact: Rinse opened eye for several minutes under running water. After swallowing: Induce vomiting, if person is conscious. Seek medical help.

5 Fire fighting measures

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards caused by the material, its products of combustion or resulting gases:

Melted solder above 1000°F will liberate toxic lead and/or antimony fumes.

Protective equipment: Wear self-contained respiatory protective device.

6 Accidental release measures

Person-related safety precautions: Not required.

Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.

Measures for cleaning/collecting:

Melted solder will solidify on cooling and can be scraped up. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces.

7 Handling and storage

Handling:

Information for safe handling: Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires: Keep respiratory protective device available.

Storage

Requirements to be met by storerooms and receptacles: No special requirements. **Information about storage in one common storage facility:** Not required.

(Contd. on page 3)

acc. to ISO/DIS 11014

Printing date 07/31/2003 Reviewed on 07/21/2003

Trade name: SOLDER ALLOYS CONTAINING LEAD

(Contd. of page 2)

Further information about storage conditions: Store in dry conditions.

8 Exposure controls and personal protection

Additional information about design of technical systems: No further data; see item 7.

	ponents with limit values that require monitoring at the workplace:	
7440-31-5 tin		
PEL	2 mg/m³	
	Metal	
REL	2 mg/m³	
	Tin, Metal	
TLV	2 mg/m³	
7439	-92-1 lead	
PEL	0.05* mg/m³	
	as Pb	
REL	<0.1* mg/m³	
	as Pb; *Blood Pb <0.06 mg/100 g whole blood	
TLV	0.05 mg/m^3	
	as Pb; BEI	
7440	-36-0 antimony	
PEL	0.5 mg/m³	
REL	0.5 mg/m^3	
	as Sb	
TLV	0.5 mg/m^3	
7440	-50-8 copper	
PEL	0.1*;1** mg/m³	
	*fume **dusts & mists	
REL	0.1*;1** mg/m³	
	*Copper fume, as Cu **Copper dusts & mists, as Cu	
TLV	0.2*, 1** mg/m³	
	*fume; ** dusts&mists, as Cu	
7440	-22-4 silver	
PEL	0.01 mg/m³	
	0.01 mg/m^3	
TLV	0.1 mg/m^3	
A -1 -1	tional information:	

Additional information:

PEL = Permissible Exposure Limit (OSHA)

REL= Recommended Exposure Limit (NIOSH)

TLV= Threshold Limit Value (ACGIH)

OSHA= Occupational Safety and Health Administration

ACGIH= American Conference of Governmental Industrial Hygienists

NIOSH= National Institute for Occupational Safety and Health

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

Store protective clothing separately.

(Contd. on page 4)

acc. to ISO/DIS 11014

Reviewed on 07/21/2003 Printing date 07/31/2003

Trade name: SOLDER ALLOYS CONTAINING LEAD

(Contd. of page 3)

Breathing equipment:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or selfcontained breathing apparatus should be worn.

Protection of hands:



Protective gloves

Material of gloves:

Cloth gloves

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Safety glasses

9 Physical and chemical properties

General Information

Form:

Solid

Color:

Silver grey

Odor:

Mild

Change in condition

Melting point/Melting range: > 100°C (> 212°F) **Boiling point/Boiling range:** 1740°C (3164°F)

Flash point:

Not applicable.

Danger of explosion:

Product does not present an explosion hazard.

Density at 20°C (68°F):

> 7 g/cm³

Solubility in / Miscibility with

Water: Insoluble.

10 Stability and reactivity

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Materials to be avoided: Strong acids, strong oxidizers.

Dangerous reactions No dangerous reactions known.

(Contd. on page 5)

acc. to ISO/DIS 11014

Printing date 07/31/2003 Reviewed on 07/21/2003

Trade name: SOLDER ALLOYS CONTAINING LEAD

(Contd. of page 4)

Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

Acute toxicity:

Primary irritant effect:

on the skin: No irritant effect.

on the eye: Smoke during soldering can cause eye irritation.

through inhalation: May cause respiratory irritation. through ingestion: May be harmful if swallowed. **Sensitization:** No sensitizing effects known. **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

12 Ecological information

General notes: Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

Product:

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

DOT regulations:

Hazard class:

Not regulated.

Land transport ADR/RID (cross-border):

ADR/RID class:

Not regulated.

Maritime transport IMDG:

IMDG Class:

Not regulated.

Marine pollutant: No

(Contd. on page 6)

-USA

acc. to ISO/DIS 11014

Printing date 07/31/2003 Reviewed on 07/21/2003

Trade name: SOLDER ALLOYS CONTAINING LEAD

(Contd. of page 5)

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: -

Not regulated.

15 Regulations

USA The following information relates to product regulation specific to the USA.

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):		
None of the ingredient is listed.		
Section 313 (Specific toxic chemical listings):		
7439-92-1	lead	
7440-36-0	antimony	
7440-50-8	copper	
7440-22-4	silver	
7440-66-6	Zinc	

TSCA (Toxic Substances Control Act):

All ingredients are listed.

California Proposition 65

Chemicals known to cause cancer:

WARNING: This product contains a chemical known to the State of California to cause cancer.

7439-92-1	lead
7440-43-9	cadmium
7440-02-0	nickel

Chemicals known to cause reproductive toxicity:

WARNING: This product contains a chemical known to the State of California to cause birth defects and/or other reproductive harm.

ſ	7439-92-1	lead
ſ	7440-43-9	cadmium

Carcinogenicity categories

EPA (Environmental Protection Agency)		
7439-92-1	lead	B2
7440-50-8	copper	D
7440-22-4	silver	D
IARC (International Agency for Research on Cancer)		
7439-92-1 lead 2B		
NTP (National Toxicology Program)		

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

(Contd. on page 7)

acc. to ISO/DIS 11014

Printing date 07/31/2003 Reviewed on 07/21/2003

Trade name: SOLDER ALLOYS CONTAINING LEAD

(Contd. of page 6)

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

CANADA: The following information relates to product regulation specific to Canada.

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

WHMIS Classification:

D2A

D2B

Components on Ingredient List for WHMIS:

lead tin antimony copper silver

EUROPEAN UNION

The following information relates to product regulation specific to the directives of the Euopean Union.

Risk phrases:

Harmful by inhalation and if swallowed. Danger of cumulative effects. Possible risk of impaired fertility.

Safety phrases:

Keep out of the reach of children.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

Dispose of this material and its container to hazardous or special waste collection point.

Special labeling of certain preparations:

Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

16 Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing MSDS: Product Safety

Contact: Heather Holich, MSDS Coordinator Tel. (847)699-5755